



**CIB UNIGAS**

Let's light up tomorrow



## TECHNICAL CATALOGUE

Burners  
for Industrial Applications



2022/1-2023

[www.cibunigas.it](http://www.cibunigas.it)





**CIB UNIGAS**

Let's light up tomorrow



## TECHNICAL CATALOGUE

Burners  
for Industrial Applications



2022/1-2023

[www.cibunigas.it](http://www.cibunigas.it)

## WE UNDERSTAND YOUR MARKET

The worldwide success of CIB UNIGAS products is due to our adaptability. In fact we are able to adapt our know-how to the different market requests. As a demonstration of this ability, now the 85% of our turnover comes from exports, in particular from Russia and China.

Our strategic points are the compliance to different rules, the specific technical and promotional documentations we supply, the ability to fulfil special requirements and the constant participation at international exhibitions.



## QUALITY STANDARDS AND CIB UNIGAS: OUR COMMITMENT

In 1995 CIB UNIGAS products were certificated by German TÜV. From that moment the company has been complying to high quality standards in all its industrial processes.

## ADVANCING TOWARDS THE FUTURE

One of the goals of CIB UNIGAS was to strengthen the internal distribution of information and to create a new technical structure for the research and development of new industrial products.

The new facility accommodates the General Management, commercial offices, control and research labs and production workshops.

The qualification of our technicians and the investment in research and human resources, represent the living and continuous engagement to operate in a future assuring stability and dynamism to the company.



### **Innovation gets us there first**

Today the full compliance to emission standards is no longer sufficient to prevent the so called "greenhouse effect". For this reason all our products have always granted a level of pollutant emissions well lower than those imposed by the international regulations. Thanks to its "Zero Emission NOx" research project, CIB Unigas is playing a proactive role in the discovery of new technologies in order to create the most environmentally-friendly product possible.

### **Production philosophy**

Everything begins in our research laboratories, where a group of engineers is free to test new materials and technologies with the goal to discover burners more and more efficient and environmentally-sustainable. When a prototype is ready, it is tested based on parameters that are tighter than those required by the market.

This is the way we produce our products for both industrial and private applications. CIB Unigas' production method, based on excellence and constant improvement, does not prevent it from maintaining a formidable operation agility. In facts CIB Unigas is able to offer an infinite range of tailor made solutions that are surprisingly competitive in terms of cost and time.

# BURNER IDENTIFICATION FOR TYPE AND MODELS

## SERIES

TECNOPRESS NOVANTA CINQUECENTO  
MILLE DUEMILA TREMILA

## TYPE

TP..., TLX..., TG..., TN..., TPBY...,  
HTP..., HTLX..., KTP..., KTPBY...



## Model:

**M-. AB. S. GB. A. 1. 65. xx. xxx**

### FUEL

M - NATURAL GAS	K - KEROSENE
L - L.P.G.	D - HEAVY OIL up to 400 cSt at 50°C (50°E a 50°C)
B - BIOGAS	H - HEAVY OIL up to 4000 cSt at 50°C (530°E - 50°C)
C - TOWN GAS	MG - DUAL FUEL BURNERS NATURAL GAS - LIGHT OIL
G - LIGHT OIL	MD - DUAL FUEL BURNERS NATURAL GAS - HEAVY OIL up to 400 cSt at 50°C (50°E a 50°C)
A - BIO DIESEL	MH - DUAL FUEL BURNERS NATURAL GAS - HEAVY OIL up to 4000 cSt at 50°C (530°E a 50°C)



### OPERATION

AB - HIGH-LOW FLAME  
PR - PROGRESSIVE  
MD - FULLY MODULATING



### BLAST TUBE

S - STANDARD  
L - LONG



### COUNTRY DESTINATION

GB - UNITED KINGDOM  
... - AVAILABLE FOR OTHER COUNTRIES UPON REQUEST



### BURNER MANUFACTURE

A - STANDARD	G - CONTROL PANEL AND JUNCTION BOX
Y - SPECIAL	E - JUNCTION BOX



### EQUIPMENT

- 1 2 GAS VALVES + LEAKAGE CONTROL
- 8 2 GAS VALVES + LEAKAGE CONTROL AND MAXIMUM GAS PRESSURE SWITCH



### GAS CONNECTION

50 DN50	100 DN100	200 DN200
65 DN65	125 DN125	250 DN250
80 DN80	150 DN150	



### ELECTRONIC VERSION

EA	Medium-large burners complete with electronic cam	EF	Medium-large burners complete with electronic cam and temperature-compensated flue gas recirculation FGR without O <sub>2</sub> monitoring, without inverter
EB	Medium-large burners complete with electronic cam and inverter	EG	Medium-large burners complete with electronic cam, inverter and temperature-compensated flue gas recirculation FGR without O <sub>2</sub> monitoring
EC	Medium-large dual fuel burners complete with electronic cam	EP	Medium-large burners complete with electronic cam and temperature-compensated flue gas recirculation FGR with O <sub>2</sub> monitoring and without inverter
ED	Medium-large dual fuel burners complete with electronic cam and inverter	ER	Medium-large burners complete with electronic cam, inverter and temperature-compensated flue gas recirculation FGR with O <sub>2</sub> monitoring
ES	Medium-large burners complete with electronic cam, without O <sub>2</sub> control, without Inverter		
EO	Medium-large burners complete with electronic cam and O <sub>2</sub> control, without Inverter		
EI	Medium-large burners complete with electronic cam and Inverter, without O <sub>2</sub> control		
EK	Medium-large burners complete with electronic cam with O <sub>2</sub> control and with Inverter		




### FGR

FGR - flue gas recirculation



# EXAMPLE OF THE NEW RANGE CONFIGURATION



TYPE		MODEL					
TL	X 1030.1	M-	MD.	S.	GB.	G.	1. 100. ES
Model		Output		Fully modulating		Country	
	Low NO <sub>x</sub> firing head		Natural gas		United Kingdom	2 gas valves and leakage control	Gas connection
				Short blast tube		With separate electrical panel and junction box	Electronic version



TYPE		MODEL					
HTL	X 2020	MG.	MD.	S.	GB.	G.	1. 125. EF. FGR
Model		Output		Fully modulating		Country	
	Low NO <sub>x</sub> firing head		Natural gas		United Kingdom	2 gas valves and leakage control	Gas connection
			Light oil	Short blast tube		With separate electrical panel and junction box	Electronic version with flue gas recirculation

# INDEX

## NATURAL GAS LOW NOx BURNERS (Class 2 EN676)



	Type	Output kW	Operation	Page
	<b>TP - built-in electrical panel</b> TP120A - TP165A - TP205A TP90A - TP91A - TP92A - TP93A TP512A - TP515A - TP520A - TP525A TP1030 - TP1050 - TP1080	300÷39.000	PR MD	20
	<b>TP</b> TP120A - TP165A - TP205A TP90A - TP91A - TP92A - TP93A TP512A - TP515A - TP520A - TP525A TP1030 - TP1050 - TP1080	300÷39.000	PR MD	20
	<b>TP</b> TP120A - TP165A - TP205A TP90A - TP91A - TP92A - TP93A TP512A - TP515A - TP520A - TP525A TP1030 - TP1050 - TP1080 TP2000 - TP2500 TP3000	300÷39.000	PR MD (electronic version)	20
	<b>TP... VS</b> TP90 - TP91 - TP92 - TP93 TP515 - TP525 TP1030 - TP1080	320÷19.000	PR MD	25
	<b>TP... VS</b> TP90 - TP91 - TP92 - TP93 TP515 - TP525 TP1030 - TP1080	320÷19.000	PR MD (electronic version)	25

## NATURAL GAS LOW NOx BURNERS (Class 3 EN676)



Type	Output kW	Operation	Page
 <b>TLX</b> TLX83 - TLX115 - TLX225 TLX92R - TLX92.1 TLX512R - TLX512.1 - TLX515.1 TLX520.1 - TLX525.1 TLX1030R - TLX1030.1 TLX2020 - TLX2030 - TLX2040 TLX3050	200÷39.000	PR MD (electronic version)	28

# INDEX

## LIGHT OIL BURNERS

Type	Output kW	Operation	Page
 <b>TG</b> TG90 - TG91 - TG92 TG510 - TG515 - TG520 - TG525 TG1030 - TG1050 - TG1080 TG2000 - TG2500 TG3000	264÷39.000	PR MD	34
 <b>TG</b> TG90 - TG91 - TG92 TG510 - TG515 - TG520 - TG525 TG1030 - TG1050 - TG1080 TG2000 - TG2500 TG3000	264÷39.000	PR MD (electronic version)	34

## HEAVY OIL BURNERS

with viscosity up to 400 cSt at 50°C (50°E at 50°C)

Type	Output kW	Operation	Page
 <b>TN</b> TN90 - TN91 - TN92 TN510 - TN515 - TN520 - TN525 TN1030 - TN1050 - TN1080 TN2000 - TN2500 TN3000	264÷39.000	PR MD	38
			

## HEAVY OIL BURNERS

with viscosity up to 4000 cSt at 50°C (530°E at 50°C)

Type	Output kW	Operation	Page
 <b>TPBY</b> TPBY90 - TPBY91 - TPBY92 - TPBY93 TPBY510 - TPBY515 - TPBY520 - TPBY525 TPBY1030 - TPBY1050 - TPBY1080 TPBY2000 - TPBY2500 TPBY3000	670÷39.000	PR MD (electronic version)	40
 <b>TPBY ...VS</b> TPBY93 TPBY515 - TPBY525 TPBY1030 - TPBY1080	900÷19.000	PR MD (electronic version)	42

# INDEX

## DUAL FUEL BURNERS NATURAL GAS/LIGHT OIL LOW NOx (Class 2 EN676)



Type	Output kW	Operation	Page
 <p><b>HTP</b>            HTP120A - HTP165A - HTP205A            HTP90A - HTP91A - HTP92A - HTP93A            HTP512A - HTP515A - HTP520A -            HTP525A            HTP1030 - HTP1050 - HTP1080         </p>	300÷39.000	PR MD	46
 <p><b>HTP</b>            HTP120A - HTP165A - HTP205A            HTP90A - HTP91A - HTP92A - HTP93A            HTP512A - HTP515A - HTP520A -            HTP525A            HTP1030 - HTP1050 - HTP1080            HTP2000 - HTP2500            HTP3000         </p>	300÷39.000	PR MD (electronic version)	46
 <p><b>HTP... VS</b>            HTP90 - HTP91 - HTP92 - HTP93            HTP515 - HTP525            HTP1030 - HTP1080         </p>	320÷19.000	PR MD	51
 <p><b>HTP... VS</b>            HTP90 - HTP91 - HTP92 - HTP93            HTP515 - HTP525            HTP1030 - HTP1080         </p>	320÷19.000	PR MD (electronic version)	51

## DUAL FUEL BURNERS NATURAL GAS/LIGHT OIL LOW NOx (Classe 3 EN676)



Type	Output kW	Operation	Page
 <p><b>HTLX</b>          HTLX83 - HTLX115 - HTLX225          HTLX92R - HTLX92.1          HTLX512R - HTLX512.1 - HTLX515.1 -          HTLX520.1 - HTLX525.1          HTLX1030R - HTLX1030.1          HTLX2020 - HTLX2030 - HTLX2040          HTLX3050</p>	200÷39.000	PR MD (electronic version)	54

# INDEX

## DUAL FUEL BURNERS NATURAL GAS/HEAVY OIL with viscosity up to 400 cSt at 50°C (50°E at 50°C)


Type	Output kW	Operation	Page
 <p><b>KTP</b>            KTP90 - KTP91 - KTP92 - KTP93            KTP512 - KTP515 - KTP520 - KTP525            KTP1030 - KTP1050 - KTP1080            KTP2000 - KTP2500            KTP3000</p>	320÷39.000	PR MD	60
			

## DUAL FUEL BURNERS NATURAL GAS/HEAVY OIL with viscosity up to 4000 cSt at 50°C (530°E at 50°C)

Type	Output kW	Operation	Page
 <p><b>KTPBY</b>            KTPBY90 - KTPBY91 - KTPBY92 -            KTPBY93            KTPBY512 - KTPBY515 - KTPBY520 -            KTPBY525            KTPBY1030 - KTPBY1050 - KTPBY1080            KTPBY2000 - KTPBY2500            KTPBY3000</p>	320÷19.000	PR MD (electronic version)	64
 <p><b>KTPBY ...VS</b>            KTPBY93            KTPBY515 - KTPBY525            KTPBY1030 - KTPBY1080</p>	900÷19.000	PR MD (electronic version)	68


## TECHNICAL INFORMATIONS

Page



## **BURNERS DIMENSIONS**

71



## **FITTINGS / OPTIONS**

133

MICRO PROCESSOR CONTROLLED BURNERS WITH LMV 2... 3... MICROPROCESSOR for medium-large burners ELECTRONIC SUPERVISION AND CONTROL SYSTEM WITH LMV 5... for medium-large burners	135
FLAME CONTROL UNITS, SIGNALS AND FUNCTIONS	
SCOPE OF SUPPLY	146
GAS BURNERS	
GAS TRAINS MB-DLE	147
GAS TRAINS SIEMENS VGD	
GAS TRAINS DUNGS MBE	
PRESSURE REDUCTION GROUPS	151
NATURAL/LPG IGNITION BURNERS	152
LIGHT OIL PILOT BURNERS	153
REVERSIBLE GAS TRAIN	154
BURNERS OPERATING WITH COMBUSTION AIR HIGH TEMPERATURE	155
BURNER HEAD ORIENTATION	156
BURNER INSTALLATION	159
FACILE SYSTEM	166
ADJUSTMENT OF THE BURNERS	168

# INDEX

	Page
HOW TO CHOOSE A BURNER	171
EMISSIONS	
LOW NO <sub>x</sub> BURNERS - TECHNICAL NOTES	
WHY CHOOSE CIB UNIGAS	
MATCHING LOW NO <sub>x</sub> BURNER AND HEAT GENERATOR	174
FANS AND ACOUSTIC HOODS BOX FAN COVERS	
AIR PRESSURE AT THE BURNER HEAD	
SULFUR OXIDES EMISSIONS	
TYPES OF FUEL	
HEAVY OIL HEATING	
LIGHT OIL BURNERS	211
BURNERS WITH FREE-STANDING LIGHT OIL	
HEAVY OIL BURNERS	
LOW PRESSURE OIL HANDLING UNITS WITH SERVICE TANK	228
FLAME CONTROL SENSORS	229
SEPARATE ELECTRICAL PANELS FOR BURNERS	230
COMPRESSORS FOR BURNERS WITH PNEUMATIC ATOMISATION	231
ACCESSORIES	
COUNTERFLANGE SELECTION	233
FREQUENCY INVERTER FOR BURNERS ELECTRONICALLY CONTROLLED	
OPTIONS BURNERS	
OPTIONS GAS BURNERS	
OPTIONS LIGHT OIL BURNERS	238
OPTIONS HEAVY OIL BURNERS	
ACOUSTIC HOODS BOX ASSEMBLED ON WHEELED FRAME	



# tecnopress novanta cinquecento mille duemila tremila SERIES

## BURNERS FOR INDUSTRIAL APPLICATIONS WITH SEPARATE FAN

These industrial burners have been designed for all those applications in which single block models are, for whatever reason, unsuitable. For example when the requested output requires the use of a too large built-in fan motor, whenever hot combustion air is provided, or again, whenever the primary noise source must be moved to soundproofed areas.

The range goes from 200 kW to 39 MW in different constructive versions as required by the specific client requirements.

Aluminium casting is usually used for the lower power models (up to 19 MW), while steel construction is used for higher power models. This industrial burner design project was developed to obtain the greatest versatility in order to achieve customers targets, and compliance to the widest range of technical specifications.

For example, combustion heads with air inlet coming from above or below, axial or tangential air flow, registers for turbulence adjustment, and other features can be provided. This means that the machines can be highly customized in size and performance as desired.

All the combustion heads are available in the versions for liquid, gaseous or mixed fuels.

Customization in these cases is almost inevitable and entirely feasible within our range, and all such requests are carefully analysed, one by one.

- electronic or mechanical adjustment
- FGR flue gas re-circulation
- combustion oil handling unit
- combustion oil heating unit



TP1050

TG2500

TLX525.1 (Hot Air)



TLX1050



TLX2020



TLX520.1 (Hot Air)

The burners can burn with different type of the gasses: Natural Gas, LPG, Biogas and Gas process.

Options:

- oxygen trim control (at the stack) with continuous system regulation;
- VSD (inverter) trim control for the fan motor;
- air combustion temperature up to 250°C;
- modulating ratio up to 1:8, with moveable combustion head;
- continuous ventilation;
- remote control via bus protocol;
- gas pressure reducing unit, with inlet pressure up to 6 Bar;
- double gas train to operate with 2 types of gas;
- 3 fuels operation;
- ATEX electrical protection;
- On-board electrical panel, except for hot air versions.



TLX2020



TPBY2500



TP520

#### Burners with on-board electrical panel


The burners can be equipped with an on-board electrical panel.

The control panel can include or exclude the fan motor contactor and thermal relay.

This solution can be used with ambient air burners, not with hot air burners.





## NATURAL GAS LOW NOx BURNERS



# TP TYPE TP120A ... TP3000



GAS





# TP120A ... TP3000 **TP** TYPE

Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TP120A</b>	300	840	1.200
<b>TP165A</b>	320	1.154	1.650
<b>TP205A</b>	340	1.433	2.050
<b>TP90A</b>	320	1.610	2.300
<b>TP91A</b>	480	1.869	2.670
<b>TP92A</b>	480	2.135	3.050
<b>TP93A</b>	550	2.870	4.100
<b>TP512A</b>	600	3.150	4.500
<b>TP515A</b>	770	3.640	5.200
<b>TP520A</b>	1.000	4.480	6.400
<b>TP525A</b>	2.000	6.825	9.750
<b>TP1030</b>	2.500	9.310	13.300
<b>TP1050</b>	3.500	10.850	15.500
<b>TP1080</b>	3.500	13.300	19.000
<b>TP2000</b>	3.600	15.400	22.000
<b>TP2500</b>	4.500	18.400	27.000
<b>TP3000</b>	5.500	27.300	39.000




## TECHNICAL DETAILS

Type	Model	Power kW		Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.			Rp	
<b>TP120A</b>	M-.xx.S.xx.x.x.XXX.XX	300	1.200	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2"	- DN65 - DN80
<b>TP165A</b>	M-.xx.S.xx.x.x.XXX.XX	320	1.650	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2"	- DN65 - DN80
<b>TP205A</b>	M-.xx.S.xx.x.x.XXX.XX	340	2.050	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2"	- DN65 - DN80
<b>TP90A</b>	M-.xx.S.xx.x.x.XXX.XX	320	2.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP91A</b>	M-.xx.S.xx.x.x.XXX.XX	480	2.670	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP92A</b>	M-.xx.S.xx.x.x.XXX.XX	480	3.050	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP93A</b>	M-.xx.S.xx.x.x.XXX.XX	550	4.100	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP512A</b>	M-.xx.S.xx.x.x.XXX.XX	600	4.500	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP515A</b>	M-.xx.S.xx.x.x.XXX.XX	770	5.200	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP520A</b>	M-.xx.S.xx.x.x.XXX.XX	1.000	6.400	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>TP525A</b>	M-.xx.S.xx.x.x.XXX.XX	2.000	9.750	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>TP1030</b>	M-.xx.S.xx.x.x.XXX.XX	2.500	13.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>TP1050</b>	M-.xx.S.xx.x.x.XXX.XX	3.500	15.500	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>TP1080</b>	M-.xx.S.xx.x.x.XXX.XX	3.500	19.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>TP2000</b>	M-.xx.S.xx.x.x.XXX.XX	3.600	22.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>TP2500</b>	M-.xx.S.xx.x.x.XXX.XX	4.500	27.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>TP3000</b>	M-.xx.S.xx.x.x.XXX.XX	5.500	39.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150 - DN200	

# TP TYPE TP120A ... TP3000











GAS












# TP120A ... TP3000 **TP** TYPE



# TP TYPE TP120A ... TP3000




GAS



GAS



## TP90 ... TP1080 **TP...VS** TYPE



**TP...VS** TYPE

**TP90 ... TP1080**



GAS

Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TP90</b>	320	1.610	2.300
<b>TP91</b>	480	1.869	2.670
<b>TP92</b>	480	2.135	3.050
<b>TP93</b>	550	2.870	4.100
<b>TP515</b>	770	3.640	5.200
<b>TP525</b>	2.000	6.825	9.750
<b>TP1030</b>	2.500	9.310	13.300
<b>TP1080</b>	3.500	13.300	19.000









#### TECHNICAL DETAILS

Type	Model	Power kW		Auxiliary electrical power supply	Motor electrical power supply	Gas connections
		min.	max.			
<b>TP90</b>	M-xx.S.xx.VS.x.xxx.xx	320	2.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TP91</b>	M-xx.S.xx.VS.x.xxx.xx	480	2.670	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TP92</b>	M-xx.S.xx.VS.x.xxx.xx	480	3.050	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TP93</b>	M-xx.S.xx.VS.x.xxx.xx	550	4.100	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TP515</b>	M-xx.S.xx.VS.x.xxx.xx	770	5.200	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TP525</b>	M-xx.S.xx.VS.x.xxx.xx	2.000	9.750	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100
<b>TP1030</b>	M-xx.S.xx.VS.x.xxx.xx	2.500	13.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125
<b>TP1080</b>	M-xx.S.xx.VS.x.xxx.xx	3.500	19.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125


GAS






# TP90 ... TP1080 **TP...VS TYPE**

**TP90 VS PR-MD****TP92 VS PR-MD****TP515 VS PR-MD****TP1030 VS PR-MD****TP91 VS PR-MD****TP93 VS PR-MD****TP525 VS PR-MD****TP1080 VS PR-MD**

# TLX TYPE TLX83 ... TLX3050



GAS





# TLX83 ... TLX3050 **TLX** TYPE

Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TLX83</b>	200	580	830
<b>TLX115</b>	300	805	1.150
<b>TLX225</b>	230	1.000	2.280
<b>TLX92R</b>	340	1.890	2.700
<b>TLX92.1</b>	650	2.317	3.650
<b>TLX512R</b>	850	2.440	4.200
<b>TLX512.1</b>	700	3.147	4.500
<b>TLX515.1</b>	580	4.126	5.900
<b>TLX520.1</b>	650	4.760	6.800
<b>TLX525.1</b>	860	5.525	7.900
<b>TLX1030R</b>	1.090	6.475	9.250
<b>TLX1030.1</b>	1.550	9.790	14.000
<b>TLX2020</b>	2.000	11.200	16.000
<b>TLX2030</b>	2.400	16.083	23.000
<b>TLX2040</b>	3.900	22.050	31.500
<b>TLX3050</b>	4.900	27.300	39.000





## TECHNICAL DETAILS

Type	Model	Power kW		Auxiliary electrical power supply	Motor electrical power supply	Gas connections
		min.	max.			Rp
<b>TLX83</b>	M-.xx.S.xx.x.x.XXX.XX	200	830	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2" - DN65
<b>TLX115</b>	M-.xx.S.xx.x.x.XXX.XX	300	1.150	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/2 - 2" - DN65 - DN80
<b>TLX225</b>	M-.xx.S.xx.x.x.XXX.XX	230	2.280	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX92R</b>	M-.xx.S.xx.x.x.XXX.XX	340	2.700	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX92.1</b>	M-.xx.S.xx.x.x.XXX.XX	650	3.650	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX512R</b>	M-.xx.S.xx.x.x.XXX.XX	850	4.200	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX512.1</b>	M-.xx.S.xx.x.x.XXX.XX	700	4.500	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX515.1</b>	M-.xx.S.xx.x.x.XXX.XX	580	5.900	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX520.1</b>	M-.xx.S.xx.x.x.XXX.XX	650	6.800	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100
<b>TLX525.1</b>	M-.xx.S.xx.x.x.XXX.XX	860	7.900	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100
<b>TLX1030R</b>	M-.xx.S.xx.x.x.XXX.XX	1.090	9.250	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100
<b>TLX1030.1</b>	M-.xx.S.xx.x.x.XXX.XX	1.550	14.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125
<b>TLX2020</b>	M-.xx.S.xx.x.x.XXX.XX	2.000	16.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125
<b>TLX2030</b>	M-.xx.S.xx.x.x.XXX.XX	2.400	23.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125
<b>TLX2040</b>	M-.xx.S.xx.x.x.XXX.XX	3.900	31.500	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125 - DN150
<b>TLX3050</b>	M-.xx.S.xx.x.x.XXX.XX	4.900	39.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150 - DN200

# TLX TYPE TLX83 ... TLX3050








GAS



GAS










## TLX83 ... TLX3050 **TLX** TYPE




# TLX TYPE TLX83 ... TLX3050



GAS





## **LIGHT OIL BURNERS**



# TG TYPE TG90 ... TG3000

LIGHT OIL




Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TG90</b>	264	1.330	1.900
<b>TG91</b>	698	1.465	2.093
<b>TG92</b>	849	1.791	2.558
<b>TG510</b>	1.314	2.767	3.953
<b>TG515</b>	1.628	3.419	4.884
<b>TG520</b>	2.326	4.884	6.977
<b>TG525</b>	2.000	6.825	9.750
<b>TG1030</b>	2.500	9.310	13.300
<b>TG1050</b>	3.500	10.850	15.500
<b>TG1080</b>	3.500	13.300	19.000
<b>TG2000</b>	3.600	15.400	22.000
<b>TG2500</b>	4.500	18.400	27.000
<b>TG3000</b>	5.500	27.300	39.000

## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor kW	Auxiliary electrical power supply	Motor electrical power supply
		min.	max.			
<b>TG90</b>	G-.xx.x.xx.G.xx	264	1.900	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG91</b>	G-.xx.x.xx.G.xx	698	2.093	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG92</b>	G-.xx.x.xx.G.xx	849	2.558	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG510</b>	G-.xx.x.xx.G.xx	1.314	3.953	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG515</b>	G-.xx.x.xx.G.xx	1.628	4.884	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG520</b>	G-.xx.x.xx.G.xx	2.326	6.977	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG525</b>	G-.xx.x.xx.G.xx	2.000	9.750	4,0	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG1030</b>	G-.xx.x.xx.G.xx	2.500	13.300	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG1050</b>	G-.xx.x.xx.G.xx	3.500	15.500	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG1080</b>	G-.xx.x.xx.G.xx	3.500	19.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG2000</b>	G-.xx.x.xx.G.xx	3.600	22.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG2500</b>	G-.xx.x.xx.G.xx	4.500	27.000	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TG3000</b>	G-.xx.x.xx.G.xx	5.500	39.000	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz





## **HEAVY OIL BURNERS**



# TN TYPE TN90 ... TN3000

with viscosity up to 400 cSt at 50°C (50°E at 50°C) - MECHANICAL ATOMIZATION

HEAVY OIL



Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TN90</b>	264	1.330	1.900
<b>TN91</b>	698	1.465	2.093
<b>TN92</b>	849	1.791	2.558
<b>TN510</b>	1.314	2.767	3.953
<b>TN515</b>	1.628	3.419	4.884
<b>TN520</b>	2.326	4.884	6.977
<b>TN525</b>	2.000	6.825	9.750
<b>TN1030</b>	2.500	9.310	13.300
<b>TN1050</b>	3.500	10.850	15.500
<b>TN1080</b>	3.500	13.300	19.000
<b>TN2000</b>	3.600	15.400	22.000
<b>TN2500</b>	4.500	18.400	27.000
<b>TN3000</b>	5.500	27.300	39.000



## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor kW	Resistor kW	Auxiliary electrical power supply	Motor electrical power supply
		min.	max.				
<b>TN90</b>	D-.xx.S.xx.G.xx	264	1.900	1,1	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN91</b>	D-.xx.S.xx.G.xx	698	2.093	1,1	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN92</b>	D-.xx.S.xx.G.xx	849	2.558	1,1	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN510</b>	D-.xx.S.xx.G.xx	1.314	3.953	1,1	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN515</b>	D-.xx.S.xx.G.xx	1.628	4.884	1,5	12 + 18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN520</b>	D-.xx.S.xx.G.xx	2.326	6.977	2,2	18 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN525</b>	D-.xx.S.xx.G.xx	2.000	9.750	4,0	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN1030</b>	D-.xx.S.xx.G.xx	2.500	13.300	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN1050</b>	D-.xx.S.xx.G.xx	3.500	15.500	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN1080</b>	D-.xx.S.xx.G.xx	3.500	19.000	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN2000</b>	D-.xx.S.xx.G.xx	3.600	22.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN2500</b>	D-.xx.S.xx.G.xx	4.500	27.000	5,5/7,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TN3000</b>	D-.xx.S.xx.G.xx	5.500	39.000	5,5/7,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz

# TPBY TYPE TPBY90 ... TPBY3000

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

HEAVY OIL



Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TPBY90</b>	670	1.400	2.000
<b>TPBY91</b>	500	1.750	2.500
<b>TPBY92</b>	700	2.100	3.000
<b>TPBY93</b>	900	2.590	3.700
<b>TPBY510</b>	1.100	3.500	5.000
<b>TPBY515</b>	1.200	4.200	6.000
<b>TPBY520</b>	1.400	4.900	7.000
<b>TPBY525</b>	2.000	6.825	9.750
<b>TPBY1030</b>	2.550	9.310	13.300
<b>TPBY1050</b>	3.100	10.850	15.500
<b>TPBY1080</b>	3.800	13.300	19.000
<b>TPBY2000</b>	3.600	15.400	22.000
<b>TPBY2500</b>	4.500	18.400	27.000
<b>TPBY3000</b>	5.500	27.300	39.000




## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor kW	Resistor kW	Auxiliary electrical power supply	Motor electrical power supply
		min.	max.				
<b>TPBY90</b>	H-xx.S.xx.G.xx	670	2.000	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY91</b>	H-xx.S.xx.G.xx	500	2.500	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY92</b>	H-xx.S.xx.G.xx	700	3.000	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY93</b>	H-xx.S.xx.G.xx	900	3.700	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY510</b>	H-xx.S.xx.G.xx	1.100	5.000	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY515</b>	H-xx.S.xx.G.xx	1.200	6.000	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY520</b>	H-xx.S.xx.G.xx	1.400	7.000	0,75	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY525</b>	H-xx.S.xx.G.xx	2.000	9.750	1,1	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY1030</b>	H-xx.S.xx.G.xx	2.550	13.300	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY1050</b>	H-xx.S.xx.G.xx	3.100	15.500	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY1080</b>	H-xx.S.xx.G.xx	3.800	19.000	1,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY2000</b>	H-xx.S.xx.G.xx	3.600	22.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY2500</b>	H-xx.S.xx.G.xx	4.500	27.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY3000</b>	H-xx.S.xx.G.xx	5.500	39.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz

# TPBY...VS TYPE TPBY93 ... TPBY1080

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

HEAVY OIL




Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>TPBY93</b>	900	2.590	3.700
<b>TPBY515</b>	1.200	4.200	6.000
<b>TPBY525</b>	2.000	6.825	9.750
<b>TPBY1030</b>	2.550	9.310	13.300
<b>TPBY1080</b>	3.800	13.300	19.000

## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor	Resistor	Auxiliary electrical power supply	Motor electrical power supply
		min.	max.	kW	kW		
<b>TPBY93</b>	H-xx.S.xx.G.xx	900	3.700	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY515</b>	H-xx.S.xx.G.xx	1.200	6.000	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY525</b>	H-xx.S.xx.G.xx	2.000	9.750	0,75	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY1030</b>	H-xx.S.xx.G.xx	2.550	13.300	1,1	18 + 18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz
<b>TPBY1080</b>	H-xx.S.xx.G.xx	3.800	19.000	2,2	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz





## DUAL FUEL BURNERS NATURAL GAS/LIGHT OIL LOW NOx




# HTP TYPE HTP120A ... HTP3000



GAS/LIGHT OIL



GAS/LIGHT OIL






# HTP120A ... HTP3000 HTP TYPE

Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>HTP120A</b>	300	840	1.200
<b>HTP165A</b>	320	1.154	1.650
<b>HTP205A</b>	340	1.433	2.050
<b>HTP90A</b>	320	1.610	2.300
<b>HTP91A</b>	480	1.869	2.670
<b>HTP92A</b>	480	2.135	3.050
<b>HTP93A</b>	550	2.870	4.100
<b>HTP512A</b>	600	3.150	4.500
<b>HTP515A</b>	770	3.640	5.200
<b>HTP520A</b>	1.000	4.480	6.400
<b>HTP525A</b>	2.000	6.825	9.750
<b>HTP1030</b>	2.500	9.310	13.300
<b>HTP1050</b>	3.500	10.850	15.500
<b>HTP1080</b>	3.500	13.300	19.000
<b>HTP2000</b>	3.600	15.400	22.000
<b>HTP2500</b>	4.500	18.400	27.000
<b>HTP3000</b>	5.500	27.300	39.000

## TECHNICAL DETAILS









Type	Model	Power kW		Pump motor KW	Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.				Rp	
<b>HTP120A</b>	MG.xx.S.xx.x.x.XXX.XX	300	1.200	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2" - DN65 - DN80	
<b>HTP165A</b>	MG.xx.S.xx.x.x.XXX.XX	320	1.650	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2" - DN65 - DN80	
<b>HTP205A</b>	MG.xx.S.xx.x.x.XXX.XX	340	2.050	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2" - DN65 - DN80	
<b>HTP90A</b>	MG.xx.S.xx.x.x.XXX.XX	320	2.300	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP91A</b>	MG.xx.S.xx.x.x.XXX.XX	480	2.670	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP92A</b>	MG.xx.S.xx.x.x.XXX.XX	480	3.050	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP93A</b>	MG.xx.S.xx.x.x.XXX.XX	550	4.100	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP512A</b>	MG.xx.S.xx.x.x.XXX.XX	600	4.500	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP515A</b>	MG.xx.S.xx.x.x.XXX.XX	770	5.200	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP520A</b>	MG.xx.S.xx.x.x.XXX.XX	1.000	6.400	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTP525A</b>	MG.xx.S.xx.x.x.XXX.XX	2.000	9.750	4,0	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>HTP1030</b>	MG.xx.S.xx.x.x.XXX.XX	2.500	13.300	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>HTP1050</b>	MG.xx.S.xx.x.x.XXX.XX	3.500	15.500	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>HTP1080</b>	MG.xx.S.xx.x.x.XXX.XX	3.500	19.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>HTP2000</b>	MG.xx.S.xx.x.x.XXX.XX	3.600	22.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>HTP2500</b>	MG.xx.S.xx.x.x.XXX.XX	4.500	27.000	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>HTP3000</b>	MG.xx.S.xx.x.x.XXX.XX	5.500	39.000	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150 - DN200	

# HTP TYPE HTP120A ... HTP3000












# HTP120A ... HTP3000 HTP TYPE




# HTP TYPE HTP120A ... HTP3000





## HTP90 ... HTP1080 **HTP...VS** TYPE





Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>HTP90</b>	320	1.610	2.300
<b>HTP91</b>	480	1.869	2.670
<b>HTP92</b>	480	2.135	3.050
<b>HTP93</b>	550	2.870	4.100
<b>HTP515</b>	770	3.640	5.200
<b>HTP525</b>	2.000	6.825	9.750
<b>HTP1030</b>	2.500	9.310	13.300
<b>HTP1080</b>	3.500	13.300	19.000









## TECHNICAL DETAILS

Type	Model	Power kW		Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.			Rp	
<b>HTP90</b>	MG.xx.S.xx.VS.x.xxx.xx	320	2.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>HTP91</b>	MG.xx.S.xx.VS.x.xxx.xx	480	2.670	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>HTP92</b>	MG.xx.S.xx.VS.x.xxx.xx	480	3.050	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>HTP93</b>	MG.xx.S.xx.VS.x.xxx.xx	550	4.100	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>HTP515</b>	MG.xx.S.xx.VS.x.xxx.xx	770	5.200	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>HTP525</b>	MG.xx.S.xx.VS.x.xxx.xx	2.000	9.750	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65	- DN80 - DN100
<b>HTP1030</b>	MG.xx.S.xx.VS.x.xxx.xx	2.500	13.300	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80	- DN100 - DN125
<b>HTP1080</b>	MG.xx.S.xx.VS.x.xxx.xx	3.500	19.000	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100	- DN125



GAS/LIGHT OIL



## HTP90 ... HTP1080 **HTP...VS** TYPE



# HTLX TYPE HTLX83 ... HTLX3050



GAS/LIGHT OIL





Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>HTLX83</b>	200	580	830
<b>HTLX115</b>	300	805	1.150
<b>HTLX225</b>	230	1.000	2.280
<b>HTLX92R</b>	340	1.890	2.700
<b>HTLX92.1</b>	650	2.317	3.650
<b>HTLX512R</b>	850	2.440	4.200
<b>HTLX512.1</b>	700	3.147	4.500
<b>HTLX515.1</b>	580	4.126	5.900
<b>HTLX520.1</b>	650	4.760	6.800
<b>HTLX525.1</b>	860	5.525	7.900
<b>HTLX1030R</b>	1.090	6.475	9.250
<b>HTLX1030.1</b>	1.550	9.790	14.000
<b>HTLX2020</b>	2.000	11.200	16.000
<b>HTLX2030</b>	2.400	16.083	23.000
<b>HTLX2040</b>	3.900	22.050	31.500
<b>HTLX3050</b>	4.900	27.300	39.000






## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor KW	Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.				Rp	
<b>HTLX83</b>	MG.xx.S.xx.x.x.XXX.XX	200	830	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/4 - 1"1/2 - 2" - DN65	
<b>HTLX115</b>	MG.xx.S.xx.x.x.XXX.XX	300	1.150	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	1"1/2 - 2" - DN65 - DN80	
<b>HTLX225</b>	MG.xx.S.xx.x.x.XXX.XX	230	2.280	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX92R</b>	MG.xx.S.xx.x.x.XXX.XX	340	2.700	0,55	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX92.1</b>	MG.xx.S.xx.x.x.XXX.XX	650	3.650	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX512R</b>	MG.xx.S.xx.x.x.XXX.XX	850	4.200	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX512.1</b>	MG.xx.S.xx.x.x.XXX.XX	700	4.500	1,1	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX515.1</b>	MG.xx.S.xx.x.x.XXX.XX	580	5.900	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX520.1</b>	MG.xx.S.xx.x.x.XXX.XX	650	6.800	1,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>HTLX525.1</b>	MG.xx.S.xx.x.x.XXX.XX	860	7.900	4,0	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>HTLX1030R</b>	MG.xx.S.xx.x.x.XXX.XX	1.090	9.250	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>HTLX1030.1</b>	MG.xx.S.xx.x.x.XXX.XX	1.550	14.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>HTLX2020</b>	MG.xx.S.xx.x.x.XXX.XX	2.000	16.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>HTLX2030</b>	MG.xx.S.xx.x.x.XXX.XX	2.400	23.000	5,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>HTLX2040</b>	MG.xx.S.xx.x.x.XXX.XX	3.900	31.500	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125 - DN150	
<b>HTLX3050</b>	MG.xx.S.xx.x.x.XXX.XX	4.900	39.000	5,5/7,5	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150 - DN200	

# HTLX TYPE HTLX83 ... HTLX3050








GAS/LIGHT OIL











## HTLX83 ... HTLX3050 HTLX TYPE




# HTLX TYPE HTLX83 ... HTLX3050



GAS/LIGHT OIL






## DUAL FUEL BURNERS NATURAL GAS/HEAVY OIL



# KTP TYPE KTP90 ... KTP3000

GAS/HEAVY OIL

with viscosity up to 400 cSt at 50°C (50°E at 50°C) - MECHANICAL ATOMIZATION



Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>KTP90</b>	320	1.610	2.300
<b>KTP91</b>	480	1.869	2.670
<b>KTP92</b>	480	2.135	3.050
<b>KTP93</b>	550	2.870	4.100
<b>KTP512</b>	600	3.150	4.500
<b>KTP515</b>	770	3.640	5.200
<b>KTP520</b>	1.000	4.480	6.400
<b>KTP525</b>	2.000	6.825	9.750
<b>KTP1030</b>	2.500	9.310	13.300
<b>KTP1050</b>	3.500	10.850	15.500
<b>KTP1080</b>	3.500	13.300	19.000
<b>KTP2000</b>	3.600	15.400	22.000
<b>KTP2500</b>	4.500	18.400	27.000
<b>KTP3000</b>	5.500	27.300	39.000









## TECHNICAL DETAILS








Type	Model	Power kW		Pump motor kW	Resistor kW	Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.					Rp	
<b>KTP90</b>	MD.xx.S.xx.x.x.xxx.xx	320	2.300	1,1	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP91</b>	MD.xx.S.xx.x.x.xxx.xx	480	2.670	1,1	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP92</b>	MD.xx.S.xx.x.x.xxx.xx	480	3.050	1,1	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP93</b>	MD.xx.S.xx.x.x.xxx.xx	550	4.100	1,1	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP512</b>	MD.xx.S.xx.x.x.xxx.xx	600	4.500	1,5	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP515</b>	MD.xx.S.xx.x.x.xxx.xx	770	5.200	1,5	12 + 18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP520</b>	MD.xx.S.xx.x.x.xxx.xx	1.000	6.400	2,2	18 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTP525</b>	MD.xx.S.xx.x.x.xxx.xx	2.000	9.750	4,0	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>KTP1030</b>	MD.xx.S.xx.x.x.xxx.xx	2.500	13.300	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>KTP1050</b>	MD.xx.S.xx.x.x.xxx.xx	3.500	15.500	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>KTP1080</b>	MD.xx.S.xx.x.x.xxx.xx	3.500	19.000	5,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>KTP2000</b>	MD.xx.S.xx.x.x.xxx.xx	3.600	22.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>KTP2500</b>	MD.xx.S.xx.x.x.xxx.xx	4.500	27.000	5,5/7,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>KTP3000</b>	MD.xx.S.xx.x.x.xxx.xx	5.500	39.000	5,5/7,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150 - DN200	

# KTP TYPE KTP90 ... KTP3000

with viscosity up to 400 cSt at 50°C (50°E at 50°C) - MECHANICAL ATOMIZATION

GAS/HEAVY OIL







# KTPBY TYPE KTPBY90 ... KTPBY3000

GAS/HEAVY OIL

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION



Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>KTPBY90</b>	320	1.610	2.300
<b>KTPBY91</b>	480	1.869	2.670
<b>KTPBY92</b>	480	2.135	3.050
<b>KTPBY93</b>	550	2.870	4.100
<b>KTPBY512</b>	600	3.150	4.500
<b>KTPBY515</b>	770	3.640	5.200
<b>KTPBY520</b>	1.000	4.480	6.400
<b>KTPBY525</b>	2.000	6.825	9.750
<b>KTPBY1030</b>	2.500	9.310	13.300
<b>KTPBY1050</b>	3.500	10.850	15.500
<b>KTPBY1080</b>	3.500	13.300	19.000
<b>KTPBY2000</b>	3.600	15.400	22.000
<b>KTPBY2500</b>	4.500	18.400	27.000
<b>KTPBY3000</b>	5.500	27.300	39.000









## TECHNICAL DETAILS








Type	Model	Power kW		Pump motor kW	Resistor kW	Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.					Rp	
<b>KTPBY90</b>	MH.xx.S.xx.x.x.***.xx	320	2.300	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY91</b>	MH.xx.S.xx.x.x.***.xx	480	2.670	0,75	8	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY92</b>	MH.xx.S.xx.x.x.***.xx	480	3.050	0,75	12	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY93</b>	MH.xx.S.xx.x.x.***.xx	550	4.100	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY512</b>	MH.xx.S.xx.x.x.***.xx	600	4.500	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY515</b>	MH.xx.S.xx.x.x.***.xx	770	5.200	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY520</b>	MH.xx.S.xx.x.x.***.xx	1.000	6.400	0,75	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2"	- DN65 - DN80 - DN100
<b>KTPBY525</b>	MH.xx.S.xx.x.x.***.xx	2.000	9.750	1,1	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>KTPBY1030</b>	MH.xx.S.xx.x.x.***.xx	2.500	13.300	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>KTPBY1050</b>	MH.xx.S.xx.x.x.***.xx	3.500	15.500	1,1	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>KTPBY1080</b>	MH.xx.S.xx.x.x.***.xx	3.500	19.000	1,5	24 + 24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	
<b>KTPBY2000</b>	MH.xx.S.xx.x.x.***.xx	3.600	22.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>KTPBY2500</b>	MH.xx.S.xx.x.x.***.xx	4.500	27.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	
<b>KTPBY3000</b>	MH.xx.S.xx.x.x.***.xx	5.500	39.000	5,5	ON REQUEST	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN125 - DN150	

# KTPBY TYPE KTPBY90 ... KTPBY3000

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

GAS/HEAVY OIL







# KTPBY... VS TYPE KTPBY93 ... KTPBY1080

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

GAS/HEAVY OIL



Type	Min. modulation output kW	Min. application output kW	Max output kW
<b>KTPBY93</b>	550	2.870	4.100
<b>KTPBY515</b>	770	3.640	5.200
<b>KTPBY525</b>	2.000	6.825	9.750
<b>KTPBY1030</b>	2.500	9.310	13.300
<b>KTPBY1080</b>	3.500	13.300	19.000






## TECHNICAL DETAILS

Type	Model	Power kW		Pump motor	Resistor	Auxiliary electrical power supply	Motor electrical power supply	Gas connections	
		min.	max.	kW	kW	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	Rp
<b>KTPBY93</b>	MH.xx.S.xx.x.x.xxx.xx	550	4.100	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>KTPBY515</b>	MH.xx.S.xx.x.x.xxx.xx	770	5.200	0,75	18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	2" - DN65 - DN80 - DN100	
<b>KTPBY525</b>	MH.xx.S.xx.x.x.xxx.xx	2.000	9.750	0,75	24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN65 - DN80 - DN100	
<b>KTPBY1030</b>	MH.xx.S.xx.x.x.xxx.xx	2.500	13.300	1,1	18+18	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN80 - DN100 - DN125	
<b>KTPBY1080</b>	MH.xx.S.xx.x.x.xxx.xx	3.500	19.000	2,2	24+24	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	DN100 - DN125	


# KTPBY... VS TYPE KTPBY93 ... KTPBY1080

with viscosity up to 4000 cSt at 50°C (530°E at 50°C) - PNEUMATIC ATOMIZATION

GAS/HEAVY OIL



## BURNERS DIMENSIONS




# TP TYPE TP120A TP165A TP205A

GAS



## OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																															
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z	
TP120A	40	1253	1363	87	28	380	490	873	342	978	634	344	234	264	238	173	300	505	357	M10	330	216	250	401	233	456	131	327	540	-	502	198	155
TP120A	50	1253	1363	87	28	380	490	873	342	978	634	344	234	264	238	173	300	505	357	M10	330	216	250	401	233	469	131	342	526	-	502	198	155
TP120A	65	1253	1363	87	28	380	490	873	342	1062	718	344	234	264	284	173	300	505	357	M10	330	216	250	401	233	539	131	432	593	292	502	198	155
TP120A	80	1253	1363	87	28	380	490	873	342	1082	738	344	234	264	284	173	300	505	357	M10	330	216	250	401	233	559	131	538	565	310	502	198	155
TP165A	40	1318	1428	69	28	390	500	928	352	679	679	333	234	264	229	173	300	505	420	M10	330	220	250	408	233	465	130	335	569	-	575	210	155
TP165A	50	1318	1428	69	28	390	500	928	352	969	969	333	234	264	229	173	300	505	420	M10	330	220	250	408	233	465	130	335	529	-	575	210	155
TP165A	65	1318	1428	69	28	390	500	928	352	1002	1002	333	234	264	296	173	300	505	420	M10	330	220	250	408	233	533	130	403	565	292	575	210	155
TP165A	80	1318	1428	69	28	390	500	928	352	1082	1082	333	234	264	296	173	300	505	428	M10	330	220	250	408	233	574	130	538	565	310	575	210	155
TP205A	40	1431	-	69	28	503	-	928	352	679	679	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	472	130	342	569	-	575	210	155
TP205A	50	1431	-	69	28	503	-	928	352	969	969	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	472	130	342	529	-	575	210	155
TP205A	65	1431	-	69	28	503	-	928	352	1002	1002	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	562	130	432	565	292	575	210	155
TP205A	80	1431	-	69	28	503	-	928	352	1082	1082	333	254	270	287	173	300	505	453	M10	330	220	250	408	233	558	130	538	565	310	575	210	155

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# TP90A TP91A TP92A TP93A **TP TYPE**



## OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																													
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z	
		min. max.																													
TP90A	50	1356	454	28	490	866	305	1349	859	490	234	264	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	198	185
TP90A	65	1356	454	28	490	866	305	1543	1053	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	198	185
TP90A	80	1356	454	28	490	866	305	1574	1084	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	198	185
TP90A	100	1356	454	28	490	866	305	1657	1167	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	198	185
TP91A	50	1396	454	28	490	866	305	1349	859	490	265	295	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
TP91A	65	1396	454	28	490	866	305	1543	1053	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
TP91A	80	1396	454	28	490	866	305	1574	1084	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
TP91A	100	1396	454	28	490	866	305	1657	1167	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
TP92A	50	1396	454	28	490	866	305	1349	859	490	269	299	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
TP92A	65	1396	454	28	490	866	305	1543	1053	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
TP92A	80	1396	454	28	490	866	305	1574	1084	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
TP92A	100	1396	454	28	490	866	305	1657	1167	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
TP93A	50	1396	454	28	495	866	305	1349	859	490	304	344	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
TP93A	65	1396	454	28	495	866	305	1543	1053	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
TP93A	80	1396	454	28	495	866	305	1574	1084	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
TP93A	100	1396	454	28	495	866	305	1657	1167	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.



OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
TP512A	50	1485	536	25	530	955	314	1308	946	362	340	380	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	328	270
TP512A	65	1485	536	25	530	955	314	1331	969	362	340	380	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	328	270
TP512A	80	1485	536	25	530	955	314	1364	1002	362	340	380	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	328	270
TP512A	100	1485	536	25	530	955	314	1444	1082	362	340	380	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	328	270
TP515A	50	1485	536	25	530	955	314	1308	946	362	380	420	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	356	270
TP515A	65	1485	536	25	530	955	314	1331	969	362	380	420	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
TP515A	80	1485	536	25	530	955	314	1364	1002	362	380	420	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
TP515A	100	1485	536	25	530	955	314	1444	1082	362	380	420	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270
TP520A	50	1485	536	25	530	955	314	1308	946	362	400	440	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	385	270
TP520A	65	1485	536	25	530	955	314	1331	969	362	400	440	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	385	270
TP520A	80	1485	536	25	530	955	314	1364	1002	362	400	440	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	385	270
TP520A	100	1485	536	25	530	955	314	1444	1082	362	400	440	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	385	270
TP525A	65	1485	536	25	530	955	314	1331	969	362	434	484	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	419	270
TP525A	80	1485	536	25	530	955	314	1364	1002	362	434	484	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	419	270
TP525A	100	1485	536	25	530	955	314	1444	1082	362	434	484	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	419	270

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.



## OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
<b>TP1030</b>	80	1864	848	30	544	1341	540	1816	1219	520	464	504	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	372	329
<b>TP1030</b>	100	1864	848	30	544	1341	540	1816	1219	520	464	504	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	372	329
<b>TP1050</b>	80	1864	848	30	544	1341	540	1816	1219	520	489	539	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	408	329
<b>TP1050</b>	100	1864	848	30	544	1341	540	1816	1219	520	489	539	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>TP1080</b>	100	1864	848	30	544	1341	540	1816	1219	520	514	564	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>TP1080</b>	125	1864	848	30	544	1341	540	1816	1219	520	514	564	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	408	329

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.



OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
<b>TP2000</b>	100	2415	650	1675	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
<b>TP2000</b>	125	2415	650	1675	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
<b>TP2500</b>	125	2406	650	1675	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	698	425
<b>TP2500</b>	150	2406	650	1675	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	481	1468	698	425

GAS

**TP3000** **TP** TYPE

## OVERALL DIMENSIONS





Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR	S	U	V	W	Y	Z
<b>TP3000</b>	150	2513	750	1751	1847	1374	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	1113	239	215	874	1196	481	1468	651	425
<b>TP3000</b>	200	2513	750	1751	-	-	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	-	239	215	-	-	-	1468	651	425

# TP... VS TYPE TP90 TP91 TP92 TP93


GAS



## OVERALL DIMENSIONS



Boiler recommended drilling template




Air inlet flange

Type	DN	Overall dimensions (mm)																												
		A	B	C	D	E	F	FF	G	GG	H	HH	J	JJ	K	KK	L	LL	M	MM	NN	O	P	Q	R	S	U	V	W	Z
TP90	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
TP90	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
TP90	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
TP90	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
TP91	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
TP91	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
TP91	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
TP91	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
TP92	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
TP92	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
TP92	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
TP92	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
TP93	50	-	-	1122	1342	852	490	255	386	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
TP93	65	-	-	1122	1447	957	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
TP93	80	-	-	1122	1449	959	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
TP93	100	-	-	1122	1539	1049	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180




## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																									
		B	C	CC	D	Dk	E	F	GG	H	HH	J	JJ	K	KK	L	LL	M	OO	P	R	S	U	V	W	Z	
<b>TP515</b>	50	344	1287	-	1613	310	1071	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	605	843	216	970	235	
<b>TP515</b>	65	344	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235	
<b>TP515</b>	80	344	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235	
<b>TP515</b>	100	344	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235	
<b>TP525</b>	65	478	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235	
<b>TP525</b>	80	478	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235	
<b>TP525</b>	100	478	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235	



OVERALL DIMENSIONS



Air inlet flange

Boiler recommended drilling template


Burner flange

Type	DN	Overall dimensions (mm)																							
		B min.	C max.	CC	Dk	F	G	GG	H	HH	J	JJ	K	KK	LL	M	OO	P	R	S	U	V			
<b>TP1030</b>	80	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	736	1092	322	1170	330
<b>TP1030</b>	100	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	642	1092	382	1170	330
<b>TP1030</b>	125	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	754	1192	480	1170	330
<b>TP1080</b>	100	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	642	1092	382	1170	330
<b>TP1080</b>	125	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	754	1192	480	1170	330

GAS

# TLX83 TLX115 TLX225 TLX...FGR TYPE

OVERALL DIMENSIONS (TLX... - TLX...FGR)




Type	DN	Overall dimensions (mm)																															
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z	
TLX83	32	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	387	131	256	540	-	502	198	155
TLX83	40	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	458	131	327	540	-	502	198	155
TLX83	50	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	473	131	342	526	-	502	198	155
TLX83	65	1039	1189	87	28	300	450	705	342	1062	718	344	219	249	118	173	300	505	347	M10	330	216	250	401	233	563	131	432	593	292	502	198	155
TLX115	40	1169	1253	69	28	305	390	830	352	679	679	333	219	249	235	173	300	505	420	M10	330	220	250	408	233	472	127	325	569	-	575	210	155
TLX115	50	1169	1253	69	28	305	390	830	352	969	969	333	219	249	235	173	300	505	420	M10	330	220	250	408	233	472	127	338	529	-	575	210	155
TLX115	65	1169	1253	69	28	305	390	830	352	1002	1002	333	219	249	287	173	300	505	420	M10	330	220	250	408	233	275	127	406	565	292	575	210	155
TLX115	80	1169	1253	69	28	305	390	830	352	1082	1082	333	219	249	287	173	300	505	420	M10	330	220	250	408	233	284	127	538	565	310	575	210	155
TLX225	50	1264	1364	69	28	400	500	830	352	969	969	333	259	289	235	173	300	505	420	M10	330	220	250	408	233	472	127	338	529	-	575	210	155
TLX225	65	1264	1364	69	28	400	500	830	352	1002	1002	333	259	289	287	173	300	505	420	M10	330	220	250	408	233	275	127	406	565	292	575	210	155
TLX225	80	1264	1364	69	28	400	500	830	352	1082	1082	333	259	289	287	173	300	505	420	M10	330	220	250	408	233	284	127	538	565	310	575	210	155
TLX225	100	1264	1364	69	28	400	500	830	352	1082	1082	333	259	289	287	173	300	505	420	M10	330	220	250	408	233	284	127	642	565	353	575	210	155

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# TLX TLX...FGR TYPE TLX92R TLX92.1

GAS

OVERALL DIMENSIONS (TLX... - TLX...FGR)



Type	DN	Overall dimensions (mm)																															
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z	
TLX92R	50	1256	1356	454	28	390	490	866	305	1349	859	490	259	289	449	175	360	510	685	M12	424	300	300	610	300	522	148	374	624	870	228	185	
TLX92R	65	1256	1356	454	28	390	490	866	305	1543	1053	490	259	289	447	175	360	510	685	M12	424	300	300	610	300	632	148	484	846	292	870	228	185
TLX92R	80	1256	1356	454	28	390	490	866	305	1574	1084	490	259	289	447	175	360	510	685	M12	424	300	300	610	300	683	148	535	875	313	870	228	185
TLX92R	100	1256	1356	454	28	390	490	866	305	1657	1167	490	259	289	447	175	360	510	685	M12	424	300	300	610	300	790	148	642	942	353	870	228	185
TLX92.1	50	1286	1396	454	28	420	530	866	305	1349	859	490	284	316	449	175	360	510	685	M12	424	300	300	610	300	522	148	374	624	216	870	228	185
TLX92.1	65	1286	1396	454	28	420	530	866	305	1543	1053	490	284	316	447	175	360	510	685	M12	424	300	300	610	300	632	148	484	846	292	870	228	185
TLX92.1	80	1286	1396	454	28	420	530	866	305	1574	1084	490	284	316	447	175	360	510	685	M12	424	300	300	610	300	683	148	535	875	313	870	228	185
TLX92.1	100	1286	1396	454	28	420	530	866	305	1657	1167	490	284	316	447	175	360	510	685	M12	424	300	300	610	300	790	148	642	942	353	870	228	185


Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

GAS

# TLX512R TLX512.1 TLX515.1 TLX...FGR TYPE TLX520.1 TLX525.1



OVERALL DIMENSIONS (TLX... - TLX...FGR)




Type	DN	Overall dimensions (mm)																														
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
TLX512R	50	1385	1485	536	25	430	530	955	314	1308	946	362	309	349	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	311	270
TLX512R	65	1385	1485	536	25	430	530	955	314	1331	969	362	309	349	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	311	270
TLX512R	80	1385	1485	536	25	430	530	955	314	1364	1002	362	309	349	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	311	270
TLX512R	100	1385	1485	536	25	430	530	955	314	1444	1082	362	309	349	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	311	270
TLX512.1	50	1385	1485	536	25	430	530	955	314	1308	946	362	328	370	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	330	270
TLX512.1	65	1385	1485	536	25	430	530	955	314	1331	969	362	328	370	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	330	270
TLX512.1	80	1385	1485	536	25	430	530	955	314	1364	1002	362	328	370	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	330	270
TLX512.1	100	1385	1485	536	25	430	530	955	314	1444	1082	362	328	370	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	330	270
TLX515.1	50	1385	1485	536	25	430	530	955	314	1308	946	362	360	400	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	356	270
TLX515.1	65	1385	1485	536	25	430	530	955	314	1331	969	362	360	400	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
TLX515.1	80	1385	1485	536	25	430	530	955	314	1364	1002	362	360	400	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
TLX515.1	100	1385	1485	536	25	430	530	955	314	1444	1082	362	360	400	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270
TLX520.1	50	1385	1485	536	25	430	530	955	314	1308	946	362	385	425	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	356	270
TLX520.1	65	1385	1485	536	25	430	530	955	314	1331	969	362	385	425	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
TLX520.1	80	1385	1485	536	25	430	530	955	314	1364	1002	362	385	425	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
TLX520.1	100	1385	1485	536	25	430	530	955	314	1444	1082	362	385	425	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270
TLX525.1	65	1385	1485	536	25	430	530	955	314	1331	969	362	419	469	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
TLX525.1	80	1385	1485	536	25	430	530	955	314	1364	1002	362	419	469	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
TLX525.1	100	1385	1485	536	25	430	530	955	314	1444	1082	362	419	469	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# TLX TLX...FGR TYPE TLX1030R TLX1030.1

GAS

OVERALL DIMENSIONS (TLX... - TLX...FGR)




Type	DN	Overall dimensions (mm)																														
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	P	Q	R	S	U	V	W	Y	Z	
TLX1030R	80	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	448	329
TLX1030R	100	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	448	329
TLX1030R	125	1786	1886	848	30	445	545	1341	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	448	329
TLX1030.1	80	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	491	399
TLX1030.1	100	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	491	399
TLX1030.1	125	1786	1886	848	30	445	545	1341	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	491	399

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# TLX2020 TLX2030 TLX2040 **TLX** **TLX...FGR** TYPE



## OVERALL DIMENSIONS (TLX... - TLX...FGR)







Type	DN	Overall dimensions (mm)																												
		AS	AL	BS	BL	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR	S	U	V	W	Y	Z
<b>TLX2020</b>	100	2265	2415	500	650	1675	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
<b>TLX2020</b>	125	2265	2415	500	650	1675	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
<b>TLX2030</b>	100	2256	2406	500	650	1675	1847	1339	507	659	717	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	-	425
<b>TLX2030</b>	125	2256	2406	500	650	1675	1847	1339	507	659	717	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	-	425
<b>TLX2040</b>	125	2256	2406	500	650	1675	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	698	425
<b>TLX2040</b>	150	2256	2406	500	650	1675	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	-	1468	698	425

# TLX TLX...FGR TYPE TLX3050

GAS


OVERALL DIMENSIONS (TLX... - TLX...FGR)



Boiler recommended  
drilling template

Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
<b>TLX3050</b>	150	2513	750	1751	1847	1374	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	1113	239	215	874	1196	481	1468	651	425
<b>TLX3050</b>	200	2513	750	1751	-	-	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	-	239	215	-	-	-	1468	651	425


## OVERALL DIMENSIONS



Type	Overall dimensions (mm)																										
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z	
																					min.	max.					
<b>TG90</b>	1406	1556	454	28	340	490	1066	305	1349	859	490	234	264	449	175	360	510	685	M12	424	280	310	610	300	870	198	185
<b>TG91</b>	1366	1539	454	28	300	473	1066	305	1349	859	490	238	268	449	175	360	510	685	M12	424	280	310	610	300	870	228	185
<b>TG92</b>	1360	1533	454	28	294	467	1066	305	1349	859	490	266	296	449	175	360	510	685	M12	424	280	310	610	300	870	228	185

Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.


## OVERALL DIMENSIONS



Type	Overall dimensions (mm)																									
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z
<b>TG510</b>	1755	1675	536	25	300	520	1155	314	1308	946	362	329	369	494	175	460	532	707	M14	552	390	686	390	970	328	270
<b>TG515</b>	1755	1675	536	25	300	520	1155	314	1308	946	362	350	390	494	175	460	532	707	M14	552	390	686	390	970	328	270
<b>TG520</b>	1755	1675	536	25	300	520	1155	314	1308	946	362	370	410	494	175	460	532	707	M14	552	390	686	390	970	328	270
<b>TG525</b>	1755	1675	536	25	340	520	1155	314	1308	946	362	434	484	494	175	460	532	707	M14	552	390	686	390	970	328	270

Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.




## OVERALL DIMENSIONS




Type	Overall dimensions (mm)																									
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z
<b>TG1030</b>	2114	2308	848	30	350	544	1541	540	1816	1219	520	489	539	709	175	660	672	845	M16	651	460	1000	460	1175	372	329
<b>TG1050</b>	-	-	848	30	-	-	1541	540	1816	1219	520	-	-	709	175	660	672	845	M16	651	460	1000	460	1175	-	329
<b>TG1080</b>	2159	-	848	30	384	-	1541	540	1816	1219	520	671	731	709	175	660	672	845	M16	651	460	1000	460	1175	408	329

Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

OVERALL DIMENSIONS




Boiler recommended drilling template



Air inlet flange


Type	Overall dimensions (mm)																			
	A	B	C	D	E	F	G	H	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z
<b>TG2000</b>	2615	650	1875	1203	730	473	545	700	160	850	882	1043	M16	1117	395	1337	790	1468	545	425
<b>TG2500</b>	2615	650	1875	1203	730	473	698	760	160	850	882	1043	M16	1117	395	1337	790	1468	698	425

## OVERALL DIMENSIONS



Type	Overall dimensions (mm)																									
	A	B	C	D	E	F	G	H	JJ	K	KK	L	M	O	00	W	Y	Z	M	N	0	00	P	W	Y	Z
<b>TG3000</b>	2344	650	1694	1554	880	674	808	980	150	1150	1051	871	M16	575	1289	1776	808	575	M16	651	460	1000	460	1175	372	329


OVERALL DIMENSIONS



Type	Overall dimensions (mm)																										
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z	
<b>TN90</b>	1406	1556	454	28	340	490	1066	305	1349	859	490	262	292	449	175	360	510	685	M12	424	280	310	610	300	870	198	185
<b>TN91</b>	1364	1554	454	28	298	488	1066	305	1349	859	490	292	322	449	175	360	510	685	M12	424	280	310	610	300	870	228	185
<b>TN92</b>	1367	1557	454	28	301	491	1066	305	1349	859	490	292	322	449	175	360	510	685	M12	424	280	310	610	300	870	228	185

Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

## OVERALL DIMENSIONS




Type	Overall dimensions (mm)																									
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z
<b>TN510</b>	1495	1675	536	25	340	520	1155	314	1308	946	362	345	440	494	175	460	532	707	M14	552	390	686	390	977	328	270
<b>TN515</b>	1495	1675	536	25	340	520	1155	314	1308	946	362	384	440	494	175	460	532	707	M14	552	390	686	390	977	356	270
<b>TN520</b>	1495	1675	536	25	340	520	1155	314	1308	946	362	422	440	494	175	460	532	707	M14	552	390	686	390	977	385	270
<b>TN525</b>	1495	1675	536	25	340	520	1155	314	1308	946	362	434	440	494	175	460	532	707	M14	552	390	686	390	977	419	270

Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# TN TYPE TN1030 TN1050 TN1080

HEAVY OIL


## OVERALL DIMENSIONS



Type	Overall dimensions (mm)																									
	AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	W	Y	Z
<b>TN1030</b>	2114	2308	848	30	350	544	1541	540	1816	1219	520	422	472	709	175	660	672	845	M16	651	460	1000	460	1175	372	329
<b>TN1050</b>	2114	2308	848	30	350	544	1541	540	1816	1219	520	422	-	709	175	660	672	845	M16	-	460	1000	-	1175	-	329
<b>TN1080</b>	2159	-	848	30	384	-	1541	540	1816	1219	520	671	-	709	175	660	672	845	M16	-	460	1000	-	1175	408	329


Dimensions CC - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

## OVERALL DIMENSIONS




Type	Overall dimensions (mm)																				
	A	B	C	D	E	F	G	H	J	K	KK	L	M	N	O	OO	P	RR	W	Y	Z
<b>TN2000</b>	2615	650	1875	1203	730	473	545	700	160	850	882	1043	M16	1117	395	1337	790	215	1468	545	425
<b>TN2500</b>	2615	650	1875	1203	730	473	698	760	160	850	882	1043	M16	1117	395	1337	790	215	1468	698	425

OVERALL DIMENSIONS




Type	Overall dimensions (mm)																	
	A	B	C	D	E	F	G	H	JJ	K	KK	L	M	O	OO	W	Y	Z
<b>TN3000</b>	2344	650	1694	1694	880	674	808	980	150	1150	1051	871	M16	575	1289	1776	808	575

## OVERALL DIMENSIONS






Type	Overall dimensions (mm)																			
	A	AA	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	OO	RR	W	Y
<b>TPBY90</b>	1315	535	318	997	524	1250	590	527	306	346	175	460	532	707	M14	610	270	942	308	235
<b>TPBY91</b>	1318	535	321	997	524	1250	590	527	324	364	175	460	532	707	M14	610	270	942	308	235
<b>TPBY92</b>	1324	535	327	997	524	1250	590	527	365	405	175	460	532	707	M14	610	270	942	308	235
<b>TPBY93</b>	-	535	-	997	524	1250	590	527	-	-	175	460	532	707	M14	610	270	942	308	235

OVERALL DIMENSIONS




Type	Overall dimensions (mm)																			
	A	AA	B	C	CC	D	E	F	G	H	JJ	K	KK	L	M	OO	RR	W	Y	Z
<b>TPBY510</b>	1361	535	364	997	524	1250	590	527	387	427	175	460	532	707	M14	686	270	942	308	235
<b>TPBY515</b>	1365	535	368	997	524	1250	590	527	474	524	175	460	532	707	M14	686	270	942	308	235
<b>TPBY520</b>	1365	535	368	997	524	1250	590	527	474	524	175	460	532	707	M14	686	270	942	308	235
<b>TPBY525</b>	1365	535	368	997	524	1250	590	527	474	524	175	460	532	707	M14	686	270	942	308	235


## OVERALL DIMENSIONS




Burner flange



Counterflange



Boiler recommended drilling template




Air inlet flange

Type	Overall dimensions (mm)																					
	AS	AL	AA	BS	BL	C	CC	D	E	F	G	H	JJ	K	KK	L	M	O	00	W	Y	Z
<b>TPBY1030</b>	1721	-	800	353	-	1368	524	1250	590	645	633	693	175	660	670	845	M16	460	1000	1295	400	330
<b>TPBY1050</b>	1729	1939	800	361	571	1368	524	1250	590	645	671	731	175	660	670	845	M16	460	1000	1295	400	330
<b>TPBY1080</b>	1729	1939	800	361	571	1368	524	1250	590	645	671	-	175	660	670	845	M16	460	1000	1295	421	330


# TPBY TYPE TPBY2000 TPBY2500

HEAVY OIL

## OVERALL DIMENSIONS



Type	Overall dimensions (mm)																		
	A	B	C	D	E	F	G	H	JJ	K	KK	L	M	O	00	RR	W	Y	Z
<b>TPBY2000</b>	2293	550	1743	1480	730	750	700	760	160	850	883	1043	M16	395	1337	215	1468	530	425
<b>TPBY2500</b>	2293	550	1743	1480	730	750	810	870	160	850	883	1043	M16	395	1337	215	1468	530	425




**OVERALL DIMENSIONS**

Type	Overall dimensions (mm)																	
	A	B	C	D	E	F	G	H	JJ	K	KK	L	M	0	00	W	Y	Z
<b>TPBY3000</b>	2344	650	1694	1554	880	674	808	980	150	1150	1051	871	M16	575	1289	1776	808	575


# TPBY... VS TYPE TPBY93

HEAVY OIL


## OVERALL DIMENSIONS



Boiler recommended drilling template






Burner flange




Air inlet flange

Type	Overall dimensions (mm)																									
	A	AA	B	C	CC	D	E	F	FF	G	GG	H	HH	JJ	K	KK	L	LL	M	M12	M12	O	OO	P	RR	W
TPBY93	1361	535	304	997	524	1250	590	527	255	386	255	442	221	185	550	460	707	510	510	610	510	270	942	235		


## OVERALL DIMENSIONS



Boiler recommended drilling template




Burner flange



Air inlet flange

Type	Overall dimensions (mm)																					
	A	AA	B	C	CC	D	E	F	G	GG	H	HH	JJ	K	KK	L	LL	M	OO	RR	W	Z
<b>TPBY515</b>	-	535	-	-	524	1250	590	527	-	275	524	300	175	460	532	707	700	M16	686	270	942	235
<b>TPBY525</b>	1765	535	478	1287	524	1250	590	527	-	275	524	300	175	460	532	707	700	M16	686	270	942	235


OVERALL DIMENSIONS



Type	Overall dimensions (mm)																				
	A	AA	B	C	CC	D	E	F	G	GG	H	HH	JJ	K	KK	L	LL	M	OO	W	Z
<b>TPBY1030</b>	-	535	-	997	524	1250	590	527	-	275	693	300	175	460	532	707	700	M16	1000	1170	235
<b>TPBY1080</b>	-	535	-	997	524	1250	590	527	-	275	-	300	175	460	532	707	850	M16	1000	1170	235



## OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																																
		A	AA	AD	AG	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	PP	Q	QQ	R	S	U	V	W	Y	Z	
HTP120A	40	1363	87	28	280	500	873	342	978	634	344	300	330	238	173	300	505	357	M10	330	216	250	401	233	400	456	440	131	327	540	-	502	198	155
HTP120A	50	1363	87	28	280	500	873	342	978	634	344	300	330	238	173	300	505	357	M10	330	216	250	401	233	400	469	440	131	342	526	-	502	198	155
HTP120A	65	1363	87	28	280	500	873	342	1062	718	344	300	330	284	173	300	505	357	M10	330	216	250	401	233	400	539	440	131	432	593	292	502	198	155
HTP120A	80	1363	87	28	280	500	873	342	1082	738	344	300	330	284	173	300	505	357	M10	330	216	250	401	233	400	559	440	131	538	565	310	502	198	155
HTP165A	40	1428	69	28	-	500	928	352	679	679	333	234	264	229	173	300	505	420	M10	330	220	250	408	233	-	465	-	130	335	569	-	575	210	155
HTP165A	50	1428	69	28	-	500	928	352	969	969	333	234	264	229	173	300	505	420	M10	330	220	250	408	233	-	465	-	130	335	529	-	575	210	155
HTP165A	65	1428	69	28	-	500	928	352	1002	1002	333	234	264	296	173	300	505	420	M10	330	220	250	408	233	-	533	-	130	403	565	292	575	210	155
HTP165A	80	1428	69	28	-	500	928	352	1082	1082	333	234	264	296	173	300	505	428	M10	330	220	250	408	233	-	574	-	130	538	565	310	575	210	155
HTP205A	40	1431	69	28	-	503	928	352	679	679	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	-	472	-	130	342	569	-	575	210	155
HTP205A	50	1431	69	28	-	503	928	352	969	969	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	-	472	-	130	342	529	-	575	210	155
HTP205A	65	1431	69	28	-	503	928	352	1002	1002	333	254	270	233	173	300	505	453	M10	330	220	250	408	233	-	562	-	130	432	565	292	575	210	155
HTP205A	80	1431	69	28	-	503	928	352	1082	1082	333	254	270	287	173	300	505	453	M10	330	220	250	408	233	-	558	-	130	538	565	310	575	210	155

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.



OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																													
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z	
HTP90A	50	1556	454	28	490	1066	305	1349	859	490	234	264	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTP90A	65	1556	454	28	490	1066	305	1543	1053	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTP90A	80	1556	454	28	490	1066	305	1574	1084	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTP90A	100	1556	454	28	490	1066	305	1657	1167	490	234	264	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
HTP91A	50	1596	454	28	490	1066	305	1349	859	490	265	295	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTP91A	65	1596	454	28	490	1066	305	1543	1053	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTP91A	80	1596	454	28	490	1066	305	1574	1084	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTP91A	100	1596	454	28	490	1066	305	1657	1167	490	265	295	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
HTP92A	50	1596	454	28	490	1066	305	1349	859	490	269	299	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTP92A	65	1596	454	28	490	1066	305	1543	1053	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTP92A	80	1596	454	28	490	1066	305	1574	1084	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTP92A	100	1596	454	28	490	1066	305	1657	1167	490	269	299	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
HTP93A	50	1596	454	28	495	1066	305	1349	859	490	304	344	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTP93A	65	1596	454	28	495	1066	305	1543	1053	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTP93A	80	1596	454	28	495	1066	305	1574	1084	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTP93A	100	1596	454	28	495	1066	305	1657	1167	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185


Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.

GAS/LIGHT OIL

# HTP512A HTP515A HTP520A HTP525A **HTP** TYPE



## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
HTP512A	50	1685	536	25	530	1055	314	1308	946	362	340	380	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	284	270
HTP512A	65	1685	536	25	530	1055	314	1331	969	362	340	380	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	284	270
HTP512A	80	1685	536	25	530	1055	314	1364	1002	362	340	380	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	284	270
HTP512A	100	1685	536	25	530	1055	314	1444	1082	362	340	380	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	284	270
HTP515A	50	1685	536	25	530	1055	314	1308	946	362	380	420	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	328	270
HTP515A	65	1685	536	25	530	1055	314	1331	969	362	380	420	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	328	270
HTP515A	80	1685	536	25	530	1055	314	1364	1002	362	380	420	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	328	270
HTP515A	100	1685	536	25	530	1055	314	1444	1082	362	380	420	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	328	270
HTP520A	50	1685	536	25	530	1055	314	1308	946	362	400	440	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	328	270
HTP520A	65	1685	536	25	530	1055	314	1331	969	362	400	440	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	328	270
HTP520A	80	1685	536	25	530	1055	314	1364	1002	362	400	440	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	328	270
HTP520A	100	1685	536	25	530	1055	314	1444	1082	362	400	440	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	328	270
HTP525A	65	1685	536	25	530	1055	314	1331	969	362	434	484	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	328	270
HTP525A	80	1685	536	25	530	1055	314	1364	1002	362	434	484	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	328	270
HTP525A	100	1685	536	25	530	1055	314	1444	1082	362	434	484	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	328	270




Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

**HTP** TYPE HTP1030 HTP1050 HTP1080


GAS/LIGHT OIL




## OVERALL DIMENSIONS



### *Boiler recommended drilling template*



#### *Burner flange*




### *Air inlet flange*

Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z
<b>HTP1030</b>	80	2064	848	30	544	1541	540	1816	1219	520	464	504	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	372	329
<b>HTP1030</b>	100	2064	848	30	544	1541	540	1816	1219	520	464	504	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	372	329
<b>HTP1050</b>	80	2064	848	30	544	1541	540	1816	1219	520	489	539	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	408	329
<b>HTP1050</b>	100	2064	848	30	544	1541	540	1816	1219	520	489	539	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>HTP1080</b>	100	2064	848	30	544	1541	540	1816	1219	520	514	564	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>HTP1080</b>	125	2064	848	30	544	1541	540	1816	1219	520	514	564	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	408	329

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.






## OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
HTP2000	100	2615	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
HTP2000	125	2615	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
HTP2500	125	2606	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	698	425
HTP2500	150	2606	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	481	1468	698	425



OVERALL DIMENSIONS



Boiler recommended  
drilling template






Air inlet flange


Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
HTP3000	150	2713	750	1951	1847	1374	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	1113	239	215	874	1196	481	1468	651	425
HTP3000	200	2713	750	1951	-	-	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	-	239	215	-	-	-	1468	651	425




## OVERALL DIMENSIONS



### *Boiler recommended drilling template*



### *Burner flange*




### *Air inlet flange*

Type	DN	Overall dimensions (mm)																												
		A	B	C	D	E	F	FF	G	GG	H	HH	J	JJ	K	KK	L	LL	M	MM	NN	O	P	Q	R	S	U	V	W	Z
<b>HTP90</b>	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
<b>HTP90</b>	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
<b>HTP90</b>	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
<b>HTP90</b>	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
<b>HTP91</b>	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
<b>HTP91</b>	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
<b>HTP91</b>	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
<b>HTP91</b>	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
<b>HTP92</b>	50	-	-	1122	1342	852	490	255	-	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
<b>HTP92</b>	65	-	-	1122	1447	957	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
<b>HTP92</b>	80	-	-	1122	1449	959	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
<b>HTP92</b>	100	-	-	1122	1539	1049	490	255	-	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180
<b>HTP93</b>	50	-	-	1122	1342	852	490	255	386	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
<b>HTP93</b>	65	-	-	1122	1447	957	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
<b>HTP93</b>	80	-	-	1122	1449	959	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
<b>HTP93</b>	100	-	-	1122	1539	1049	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180




OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																								
		B	C	CC	D	Dk	E	F	GG	H	HH	J	JJ	K	KK	L	LL	M	OO	P	R	S	U	V	W	Z
<b>HTP515</b>	50	-	1287	-	1613	310	1071	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	605	843	216	970	235
<b>HTP515</b>	65	-	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235
<b>HTP515</b>	80	-	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235
<b>HTP515</b>	100	-	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235
<b>HTP525</b>	65	478	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235
<b>HTP525</b>	80	478	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235
<b>HTP525</b>	100	478	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235



## OVERALL DIMENSIONS



### *Air inlet flange*

### *Boiler recommended drilling template*


### *Burner flange*

Type	DN	Overall dimensions (mm)																							
		B	C min. max.	CC	Dk	F	G	GG	H	HH	J	JJ	K	KK	LL	M	00	P	R	S	U	V	W	Z	
<b>HTP1030</b>	80	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	736	1092	322	1170	330
<b>HTP1030</b>	100	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	642	1092	382	1170	330
<b>HTP1030</b>	125	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	754	1192	480	1170	330
<b>HTP1080</b>	100	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	642	1092	382	1170	330
<b>HTP1080</b>	125	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	754	1192	480	1170	330

# HTLX HTLX...FGR TYPE HTLX83 HTLX115 HTLX225

GAS/LIGHT OIL

OVERALL DIMENSIONS (HTLX... - HTLX...FGR)




Type	DN	Overall dimensions (mm)																													
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y
HTLX83	32	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	387	131	256	540	-	502 198 155
HTLX83	40	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	458	131	327	540	-	502 198 155
HTLX83	50	1039	1189	87	28	300	450	705	342	978	634	344	219	249	238	173	300	505	347	M10	330	216	250	401	233	473	131	342	526	-	502 198 155
HTLX83	65	1039	1189	87	28	300	450	705	342	1062	718	344	219	249	118	173	300	505	347	M10	330	216	250	401	233	563	131	432	593	292	502 198 155
HTLX115	40	1169	1253	69	28	305	390	830	352	679	679	333	219	249	235	173	300	505	420	M10	330	220	250	408	233	-	127	325	569	-	575 210 155
HTLX115	50	1169	1253	69	28	305	390	830	352	969	969	333	219	249	235	173	300	505	420	M10	330	220	250	408	233	-	127	338	529	-	575 210 155
HTLX115	65	1169	1253	69	28	305	390	830	352	1002	1002	333	219	249	287	173	300	505	420	M10	330	220	250	408	233	275	127	406	565	292	575 210 155
HTLX115	80	1169	1253	69	28	305	390	830	352	1082	1082	333	219	249	287	173	300	505	420	M10	330	220	250	408	233	284	127	538	565	310	575 210 155
HTLX225	50	1264	1364	69	28	400	500	830	352	969	969	333	259	280	235	173	300	505	420	M10	330	220	250	408	233	-	127	338	529	-	575 210 155
HTLX225	65	1264	1364	69	28	400	500	830	352	1002	1002	333	259	280	287	173	300	505	420	M10	330	220	250	408	233	275	127	406	565	292	575 210 155
HTLX225	80	1264	1364	69	28	400	500	830	352	1082	1082	333	259	280	287	173	300	505	420	M10	330	220	250	408	233	284	127	538	565	310	575 210 155
HTLX225	100	1264	1364	69	28	400	500	830	352	1082	1082	333	259	280	287	173	300	505	420	M10	330	220	250	408	233	284	127	642	565	353	575 210 155

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.



OVERALL DIMENSIONS (HTLX... - HTLX...FGR)




Type	DN	Overall dimensions (mm)																															
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	U	V	W	Y	Z	
		min. max.																															
HTLX92R	50	1456	1556	454	28	390	490	1066	305	1349	859	490	259	289	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTLX92R	65	1456	1556	454	28	390	490	1066	305	1543	1053	490	259	289	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTLX92R	80	1456	1556	454	28	390	490	1066	305	1574	1084	490	259	289	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTLX92R	100	1456	1556	454	28	390	490	1066	305	1657	1167	490	259	289	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
HTLX92.1	50	1486	1596	454	28	420	530	1066	305	1349	859	490	284	316	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
HTLX92.1	65	1486	1596	454	28	420	530	1066	305	1543	1053	490	284	316	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
HTLX92.1	80	1486	1596	454	28	420	530	1066	305	1574	1084	490	284	316	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
HTLX92.1	100	1486	1596	454	28	420	530	1066	305	1657	1167	490	284	316	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.

# HTLX HTLX...FGR TYPE HTLX512R HTLX512.1 HTLX515.1 HTLX520.1 HTLX525.1

GAS/LIGHT OIL

OVERALL DIMENSIONS (HTLX... - HTLX...FGR)



Type	DN	Overall dimensions (mm)																														
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z
HTLX512R	50	1585	1685	536	25	430	530	1155	314	1308	946	362	309	349	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	311	270
HTLX512R	65	1585	1685	536	25	430	530	1155	314	1331	969	362	309	349	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	311	270
HTLX512R	80	1585	1685	536	25	430	530	1155	314	1364	1002	362	309	349	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	311	270
HTLX512R	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	309	349	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	311	270
HTLX512.1	50	1585	1685	536	25	430	530	1155	314	1308	946	362	328	370	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	330	270
HTLX512.1	65	1585	1685	536	25	430	530	1155	314	1331	969	362	328	370	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	330	270
HTLX512.1	80	1585	1685	536	25	430	530	1155	314	1364	1002	362	328	370	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	330	270
HTLX512.1	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	328	370	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	330	270
HTLX515.1	50	1585	1685	536	25	430	530	1155	314	1308	946	362	360	400	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	356	270
HTLX515.1	65	1585	1685	536	25	430	530	1155	314	1331	969	362	360	400	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
HTLX515.1	80	1585	1685	536	25	430	530	1155	314	1364	1002	362	360	400	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
HTLX515.1	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	360	400	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270
HTLX515.1	80	1585	1685	536	25	430	530	1155	314	1331	969	362	419	469	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	336	270
HTLX515.1	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	419	469	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	336	270
HTLX520.1	50	1585	1685	536	25	430	530	1155	314	1308	946	362	385	425	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	336	270
HTLX520.1	65	1585	1685	536	25	430	530	1155	314	1331	969	362	385	425	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	336	270
HTLX520.1	80	1585	1685	536	25	430	530	1155	314	1364	1002	362	385	425	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	336	270
HTLX520.1	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	385	425	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	336	270
HTLX525.1	65	1585	1685	536	25	430	530	1155	314	1331	969	362	419	469	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	336	270
HTLX525.1	80	1585	1685	536	25	430	530	1155	314	1364	1002	362	419	469	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	336	270
HTLX525.1	100	1585	1685	536	25	430	530	1155	314	1444	1082	362	419	469	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	336	270

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.


In standard and electronic versions these dimensions may be smaller.

GAS/LIGHT OIL

# HTLX1030R HTLX1030.1 HTLX HTLX...FGR TYPE



OVERALL DIMENSIONS (HTLX... - HTLX...FGR)




Type	DN	Overall dimensions (mm)																														
		AS	AL	AA	AD	BS	BL	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z
HTLX1030R	80	1986	2086	848	30	445	545	1541	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	448	329
HTLX1030R	100	1986	2086	848	30	445	545	1541	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	448	329
HTLX1030R	125	1986	2086	848	30	445	545	1541	540	1816	1219	520	446	500	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	448	329
HTLX1030.1	80	1986	2086	848	30	445	545	1541	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	399	329
HTLX1030.1	100	1986	2086	848	30	445	545	1541	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	399	329
HTLX1030.1	125	1986	2086	848	30	445	545	1541	540	1816	1219	520	489	541	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	399	329

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

# HTLX HTLX...FGR TYPE HTLX2020 HTLX2030 HTLX2040

GAS/LIGHT OIL

OVERALL DIMENSIONS (HTLX... - HTLX...FGR)




Type	DN	Overall dimensions (mm)																												
		AS	AL	BS	BL	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR	S	U	V	W	Y	Z
HTLX2020	100	2465	2615	500	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
HTLX2020	125	2465	2615	500	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
HTLX2030	100	2456	2606	500	650	1875	1847	1339	507	659	717	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	-	425
HTLX2030	125	2456	2606	500	650	1875	1847	1339	507	659	717	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	-	425
HTLX2040	125	2456	2606	500	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	651	425
HTLX2040	150	2456	2606	500	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	-	1468	651	425

GAS/LIGHT OIL


# HTLX3050 HTLX...FGR TYPE

OVERALL DIMENSIONS (HTLX... - HTLX...FGR)



Type	DN	Overall dimensions (mm)																											
		A	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR	S	U	V	W	Y	Z
<b>HTLX3050</b>	150	2713	750	1951	-	1847	1374	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	1113	239	-	874	1196	481	1468	651	425
<b>HTLX3050</b>	200	2713	750	1951	-	-	-	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	-	239	-	-	-	-	1468	651	425


## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																													
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	0	00	P	Q	R	S	U	V	W	Y	Z	
<b>KTP90</b>	50	1593	454	28	527	1066	305	1349	859	490	274	304	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	198	185
<b>KTP90</b>	65	1593	454	28	527	1066	305	1543	1053	490	274	304	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	198	185
<b>KTP90</b>	80	1593	454	28	527	1066	305	1574	1084	490	274	304	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	198	185
<b>KTP90</b>	100	1593	454	28	527	1066	305	1657	1167	490	274	304	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	198	185
<b>KTP91</b>	50	1586	454	28	520	1066	305	1349	859	490	304	344	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
<b>KTP91</b>	65	1586	454	28	520	1066	305	1543	1053	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
<b>KTP91</b>	80	1586	454	28	520	1066	305	1574	1084	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
<b>KTP91</b>	100	1586	454	28	520	1066	305	1657	1167	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
<b>KTP92</b>	50	1586	454	28	520	1066	305	1349	859	490	304	344	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
<b>KTP92</b>	65	1586	454	28	520	1066	305	1543	1053	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
<b>KTP92</b>	80	1586	454	28	520	1066	305	1574	1084	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
<b>KTP92</b>	100	1586	454	28	520	1066	305	1657	1167	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185
<b>KTP93</b>	50	1586	454	28	520	1066	305	1349	859	490	304	344	449	175	360	510	685	M12	424	280	310	610	300	522	148	374	624	216	870	228	185
<b>KTP93</b>	65	1586	454	28	520	1066	305	1543	1053	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	632	148	484	846	292	870	228	185
<b>KTP93</b>	80	1586	454	28	520	1066	305	1574	1084	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	683	148	535	875	313	870	228	185
<b>KTP93</b>	100	1586	454	28	520	1066	305	1657	1167	490	304	344	447	175	360	510	685	M12	424	280	310	610	300	790	148	642	942	353	870	228	185

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models. In standard and electronic versions these dimensions may be smaller.


## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JU	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z
<b>KTP512</b>	50	1675	536	25	520	1055	314	1308	946	362	340	380	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	328	270
<b>KTP512</b>	65	1675	536	25	520	1055	314	1331	969	362	340	380	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	328	270
<b>KTP512</b>	80	1675	536	25	520	1055	314	1364	1002	362	340	380	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	328	270
<b>KTP512</b>	100	1675	536	25	520	1055	314	1444	1082	362	340	380	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	328	270
<b>KTP515</b>	50	1675	536	25	520	1055	314	1308	946	362	380	420	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	356	270
<b>KTP515</b>	65	1675	536	25	520	1055	314	1331	969	362	380	420	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	356	270
<b>KTP515</b>	80	1675	536	25	520	1055	314	1364	1002	362	380	420	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	356	270
<b>KTP515</b>	100	1675	536	25	520	1055	314	1444	1082	362	380	420	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	356	270
<b>KTP520</b>	50	1675	536	25	520	1055	314	1308	946	362	400	440	494	175	460	532	707	M14	552	390	686	390	765	160	605	843	216	977	385	270
<b>KTP520</b>	65	1675	536	25	520	1055	314	1331	969	362	400	440	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	385	270
<b>KTP520</b>	80	1675	536	25	520	1055	314	1364	1002	362	400	440	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	385	270
<b>KTP520</b>	100	1675	536	25	520	1055	314	1444	1082	362	400	440	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	385	270
<b>KTP525</b>	65	1675	536	25	520	1055	314	1331	969	362	434	484	494	175	460	532	707	M14	552	390	686	390	644	160	484	843	292	977	419	270
<b>KTP525</b>	80	1675	536	25	520	1055	314	1364	1002	362	434	484	494	175	460	532	707	M14	552	390	686	390	695	160	535	875	313	977	419	270
<b>KTP525</b>	100	1675	536	25	520	1055	314	1444	1082	362	434	484	494	175	460	532	707	M14	552	390	686	390	802	160	642	942	353	977	419	270

Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.


## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JU	K	KK	L	M	N	O	00	P	Q	R	S	U	V	W	Y	Z
<b>KTP1030</b>	80	2121	848	30	580	1541	540	1816	1219	520	600	660	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	372	329
<b>KTP1030</b>	100	2121	848	30	580	1541	540	1816	1219	520	600	660	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	372	329
<b>KTP1050</b>	80	2121	848	30	580	1541	540	1816	1219	520	633	693	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	310	1175	408	329
<b>KTP1050</b>	100	2121	848	30	580	1541	540	1816	1219	520	633	693	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>KTP1080</b>	100	2145	848	30	604	1541	540	1816	1219	520	671	731	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	350	1175	408	329
<b>KTP1080</b>	125	2145	848	30	604	1541	540	1816	1219	520	671	731	709	175	660	672	845	M16	651	460	1000	460	937	204	733	1092	478	1175	408	329


Dimensions CC - U - E - D refer to burners with maximum overall dimensions of hot air and mechanical version models.  
In standard and electronic versions these dimensions may be smaller.

## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
<b>KTP2000</b>	100	2615	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
<b>KTP2000</b>	125	2615	650	1875	1847	1339	507	545	700	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
<b>KTP2500</b>	125	2606	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	698	425
<b>KTP2500</b>	150	2606	650	1875	1847	1373	473	698	760	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	481	1468	698	425


## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	RR	S	U	V	W	Y	Z
<b>KTP3000</b>	150	2713	750	1951	1847	1374	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	1113	239	215	874	1196	481	1468	651	425
<b>KTP3000</b>	200	2713	750	1951	-	-	414	698	850	775	160	850	882	1042	M16	1117	395	1289	790	-	239	215	-	-	-	-	-	-


# KTPBY90 KTPBY91 KTPBY92 KTPBY93 **KTPBY** TYPE

## OVERALL DIMENSIONS





Type	DN	Overall dimensions (mm)																												
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	Q	R	S	TT	U	V	W	Y	Z
<b>KTPBY90</b>	50	1618	454	28	552	1066	305	1349	859	490	365	405	449	175	360	510	685	M12	424	300	610	522	148	374	524	624	216	870	198	185
<b>KTPBY90</b>	65	1618	454	28	552	1066	305	1543	1053	490	365	405	447	175	360	510	685	M12	424	300	610	632	148	484	524	846	292	870	198	185
<b>KTPBY90</b>	80	1618	454	28	552	1066	305	1574	1084	490	365	405	447	175	360	510	685	M12	424	300	610	683	148	535	524	875	313	870	198	185
<b>KTPBY90</b>	100	1618	454	28	552	1066	305	1657	1167	490	365	405	447	175	360	510	685	M12	424	300	610	790	148	642	524	942	353	870	198	185
<b>KTPBY91</b>	50	1618	454	28	552	1066	305	1349	859	490	365	405	449	175	360	510	685	M12	424	300	610	522	148	374	524	624	216	870	228	185
<b>KTPBY91</b>	65	1618	454	28	552	1066	305	1543	1053	490	365	405	447	175	360	510	685	M12	424	300	610	632	148	484	524	846	292	870	228	185
<b>KTPBY91</b>	80	1618	454	28	552	1066	305	1574	1084	490	365	405	447	175	360	510	685	M12	424	300	610	683	148	535	524	875	313	870	228	185
<b>KTPBY91</b>	100	1618	454	28	552	1066	305	1657	1167	490	365	405	447	175	360	510	685	M12	424	300	610	790	148	642	524	942	353	870	228	185
<b>KTPBY92</b>	50	1618	454	28	552	1066	305	1349	859	490	365	405	449	175	360	510	685	M12	424	300	610	522	148	374	524	624	216	870	228	185
<b>KTPBY92</b>	65	1618	454	28	552	1066	305	1543	1053	490	365	405	447	175	360	510	685	M12	424	300	610	632	148	484	524	846	292	870	228	185
<b>KTPBY92</b>	80	1618	454	28	552	1066	305	1574	1084	490	365	405	447	175	360	510	685	M12	424	300	610	683	148	535	524	875	313	870	228	185
<b>KTPBY92</b>	100	1618	454	28	552	1066	305	1657	1167	490	365	405	447	175	360	510	685	M12	424	300	610	790	148	642	524	942	353	870	228	185
<b>KTPBY93</b>	50	1580	454	28	514	1066	305	1349	859	490	410	460	449	175	360	510	685	M12	424	300	610	522	148	374	524	624	216	870	228	185
<b>KTPBY93</b>	65	1580	454	28	514	1066	305	1543	1053	490	410	460	447	175	360	510	685	M12	424	300	610	632	148	484	524	846	292	870	228	185
<b>KTPBY93</b>	80	1580	454	28	514	1066	305	1574	1084	490	410	460	447	175	360	510	685	M12	424	300	610	683	148	535	524	875	313	870	228	185
<b>KTPBY93</b>	100	1580	454	28	514	1066	305	1657	1167	490	410	460	447	175	360	510	685	M12	424	300	610	790	148	642	524	942	353	870	228	185

OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																													
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	OO	P	Q	R	S	TT	U	V	W	Y	Z
<b>KTPBY512</b>	50	1648	536	25	593	1055	314	1308	946	362	500	550	494	175	460	532	707	M14	552	390	686	390	765	160	605	524	843	216	977	319	270
<b>KTPBY512</b>	65	1648	536	25	593	1055	314	1331	969	362	500	550	494	175	460	532	707	M14	552	390	686	390	644	160	484	524	843	292	977	319	270
<b>KTPBY512</b>	80	1648	536	25	593	1055	314	1364	1002	362	500	550	494	175	460	532	707	M14	552	390	686	390	695	160	535	524	875	313	977	319	270
<b>KTPBY512</b>	100	1648	536	25	593	1055	314	1444	1082	362	500	550	494	175	460	532	707	M14	552	390	686	390	802	160	642	524	942	353	977	319	270
<b>KTPBY515</b>	50	1627	536	25	572	1055	314	1308	946	362	500	550	494	175	460	532	707	M14	552	390	686	390	765	160	605	524	843	216	977	319	270
<b>KTPBY515</b>	65	1627	536	25	572	1055	314	1331	969	362	500	550	494	175	460	532	707	M14	552	390	686	390	644	160	484	524	843	292	977	319	270
<b>KTPBY515</b>	80	1627	536	25	572	1055	314	1364	1002	362	500	550	494	175	460	532	707	M14	552	390	686	390	695	160	535	524	875	313	977	319	270
<b>KTPBY515</b>	100	1627	536	25	572	1055	314	1444	1082	362	500	550	494	175	460	532	707	M14	552	390	686	390	802	160	642	524	942	353	977	319	270
<b>KTPBY520</b>	50	1618	536	25	552	1055	314	1308	946	362	365	405	494	175	460	532	707	M14	552	390	686	390	765	160	605	524	843	216	977	335	270
<b>KTPBY520</b>	65	1618	536	25	552	1055	314	1331	969	362	365	405	494	175	460	532	707	M14	552	390	686	390	644	160	484	524	843	292	977	335	270
<b>KTPBY520</b>	80	1618	536	25	552	1055	314	1364	1002	362	365	405	494	175	460	532	707	M14	552	390	686	390	695	160	535	524	875	313	977	335	270
<b>KTPBY520</b>	100	1618	536	25	552	1055	314	1444	1082	362	365	405	494	175	460	532	707	M14	552	390	686	390	802	160	642	524	942	353	977	335	270
<b>KTPBY525</b>	65	1580	536	25	514	1055	314	1331	969	362	410	460	494	175	460	532	707	M14	552	390	686	390	644	160	484	524	843	292	977	328	270
<b>KTPBY525</b>	80	1580	536	25	514	1055	314	1364	1002	362	410	460	494	175	460	532	707	M14	552	390	686	390	695	160	535	524	875	313	977	328	270
<b>KTPBY525</b>	100	1580	536	25	514	1055	314	1444	1082	362	410	460	494	175	460	532	707	M14	552	390	686	390	802	160	642	524	942	353	977	328	270


## OVERALL DIMENSIONS




Boiler recommended drilling template



Air inlet flange




Counterflange



Burner flange


Type	DN	Overall dimensions (mm)																										
		A	AA	AD	B	C	CC	D	E	F	G	H	J	JJ	K	KK	L	M	O	00	Q	R	S	U	V	W	Y	Z
<b>KTPBY1030</b>	80	2009	848	30	571	1438	556	1816	1219	520	600	731	709	175	660	672	845	M16	460	1000	937	204	733	1092	310	1175	372	329
<b>KTPBY1030</b>	100	2009	848	30	571	1438	556	1816	1219	520	600	731	709	175	660	672	845	M16	460	1000	937	204	733	1092	350	1175	372	329
<b>KTPBY1050</b>	80	2009	848	30	571	1438	556	1816	1219	520	600	731	709	175	660	672	845	M16	460	1000	937	204	733	1092	310	1175	408	329
<b>KTPBY1050</b>	100	2009	848	30	571	1438	556	1816	1219	520	600	731	709	175	660	672	845	M16	460	1000	937	204	733	1092	350	1175	408	329
<b>KTPBY1080</b>	100	2042	848	30	604	1438	556	1909	1349	560	671	731	709	175	660	672	845	M16	460	1000	937	204	733	1192	350	1175	417	329
<b>KTPBY1080</b>	125	2042	848	30	604	1438	556	1909	1349	560	671	731	709	175	660	672	845	M16	460	1000	937	204	733	1192	478	1175	417	329

OVERALL DIMENSIONS






Type	DN	Overall dimensions (mm)																										
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR	S	U	V	W	Y	Z
<b>KTPBY2000</b>	100	2425	550	1875	1847	1339	507	700	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	353	1468	635	425
<b>KTPBY2000</b>	125	2425	550	1875	1847	1339	507	700	760	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	635	425
<b>KTPBY2500</b>	125	2425	550	1875	1847	1373	473	810	870	775	160	850	882	1468	M16	1117	395	1337	790	970	239	215	731	1195	481	1468	698	425
<b>KTPBY2500</b>	150	2425	550	1875	1847	1373	473	810	870	775	160	850	882	1468	M16	1117	395	1337	790	1114	239	215	875	1195	481	1468	698	425

OVERALL DIMENSIONS





Type	DN	Overall dimensions (mm)																				S	U	V	W	Y	Z	
		A	B	C	D	E	F	G	H	J	JJ	K	KK	L	M	N	O	00	P	Q	R	RR						
<b>KTPBY3000</b>	150	-	-	1951	1847	1374	414	-	-	775	160	850	882	1042	M16	1117	395	-	790	1113	239	-	874	1196	481	1468	-	425
<b>KTPBY3000</b>	200	-	-	1951	-	-	414	-	-	775	160	850	882	1042	M16	1117	395	-	790	-	239	-	-	-	-	-	-	-

OVERALL DIMENSIONS




Boiler recommended drilling template



Air inlet flange


Type	DN	Overall dimensions (mm)																												
		A	B	C	D	E	F	FF	G	GG	H	HH	J	JJ	K	KK	L	LL	M	MM	NN	O	P	Q	R	S	U	V	W	Z
<b>KTPBY93</b>	50	1361	304	1122	1342	852	490	255	386	255	442	221	449	185	550	510	695	510	M12	510	255	510	510	778	404	374	624	216	825	180
<b>KTPBY93</b>	65	1361	304	1122	1447	957	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	887	404	403	750	293	840	180
<b>KTPBY93</b>	80	1361	304	1122	1449	959	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	939	404	444	750	322	854	180
<b>KTPBY93</b>	100	1361	304	1122	1539	1049	490	255	386	255	442	221	447	185	550	510	695	510	M12	510	255	510	510	1046	404	524	824	382	867	180

OVERALL DIMENSIONS




Type	DN	Overall dimensions (mm)																								
		B	C	CC	D	Dk	E	F	GG	H	HH	J	JJ	K	KK	L	LL	M	OO	P	R	S	U	V	W	Z
<b>KTPBY515</b>	50	-	1287	-	1613	310	1071	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	605	843	216	970	235
<b>KTPBY515</b>	65	-	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235
<b>KTPBY515</b>	80	-	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235
<b>KTPBY515</b>	100	-	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235
<b>KTPBY525</b>	65	478	1287	-	1591	310	1049	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	484	843	292	970	235
<b>KTPBY525</b>	80	478	1287	-	1626	310	1084	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	535	875	313	970	235
<b>KTPBY525</b>	100	478	1287	-	1709	310	1167	542	275	-	300	494	175	750	532	707	700	M16	693	550	470	642	942	353	970	235

## OVERALL DIMENSIONS



Type	DN	Overall dimensions (mm)																							
		B	C min. max.	CC	Dk	F	G	GG	H	HH	J	JJ	K	KK	LL	M	OO	P	R	S	U	V	W	Z	
<b>KTPBY1030</b>	80	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	736	1092	322	1170	330
<b>KTPBY1030</b>	100	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	642	1092	382	1170	330
<b>KTPBY1030</b>	125	435	1660	1961	348÷383	340	450÷670	560	275	600	300	710	175	750	665	700	16	1000	550	200	754	1192	480	1170	330
<b>KTPBY1080</b>	100	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	642	1092	382	1170	330
<b>KTPBY1080</b>	125	422	1860	2161	348÷383	540	450÷670	700	350	750	375	710	175	900	665	850	16	1000	700	200	754	1192	480	1170	330

## FITTINGS / OPTIONS





# MICRO PROCESSOR CONTROLLED BURNERS




## WITH LMV 2... MICRO PROCESSOR

- EA Medium-large burners complete with electronic cam
- EB Medium-large burners complete with electronic cam and inverter
- EC Medium-large dual fuel burners complete with electronic cam
- ED Medium-large dual fuel burners complete with electronic cam and inverter

## WITH LMV 5... MICRO PROCESSOR

- ES Medium-large burners complete with electronic cam, without O<sub>2</sub> control, without Inverter.
- EO Medium-large burners complete with electronic cam and O<sub>2</sub> control, without Inverter
- EI Medium-large burners complete with electronic cam and Inverter, without O<sub>2</sub> control
- EK Medium-large burners complete with electronic cam with O<sub>2</sub> control and with Inverter
- EF Medium-large burners complete with electronic cam and temperature-compensated flue gas recirculation FGR without O<sub>2</sub> monitoring, without inverter
- EG Medium-large burners complete with electronic cam, inverter and temperature-compensated flue gas recirculation FGR without O<sub>2</sub> monitoring
- EP Medium-large burners complete with electronic cam and temperature-compensated flue gas recirculation FGR with O<sub>2</sub> monitoring and without inverter
- ER Medium-large burners complete with electronic cam, inverter and temperature-compensated flue gas recirculation FGR with O<sub>2</sub> monitoring




## WITH LMV 2... 3... MICROPROCESSOR for medium-large burners

CIB UNIGAS S.p.A. can provide medium size burners (up to 15.200 kW), with an electronic control system. It can be used both on single fuel burners (gas or light oil), and on dual fuel burners (gas/light oil).

### This system offers the following features:

- Reduction of mechanical moving parts
- Built-in burner management system (BMS)
- Integrated gas proving system
- Possibility to install different types of flame sensors, in order to use the electronic cam system on all applications
- Variable speed drive VSD (only on certain versions)
- Error-code display on screen in case of lock-out
- Possibility to program or to exclude the post purge time
- Display mode of operating hours



**Modbus communication**, upon request, except the base version.

**Optimal air/fuel ratio regulation**, with high precision and repeatability of the regulations made.

**Easy programming**, both through the AZL programmer, and the Siemens software.

# WITH LMV 2... 3... MICROPROCESSOR for medium-large burners



Model	Series	Fuel	LMV 20	LMV 26	LMV 27	LMV 37	AGM60
<b>EA</b>	TECNOPRESS NOVANTA CINQUECENTO	gas	●				
<b>EA</b>	MILLE DUEMILA	gas			●		
<b>EA</b>	TECNOPRESS NOVANTA CINQUECENTO	liquid fuel	●		● light oil		
<b>EA</b>	MILLE DUEMILA	liquid fuel			●		
<b>EB</b>	TECNOPRESS NOVANTA CINQUECENTO	gas				●	
<b>EB</b>	MILLE DUEMILA	gas				●	
<b>EB</b>	TECNOPRESS NOVANTA CINQUECENTO	liquid fuel				●	
<b>EB</b>	MILLE DUEMILA	liquid fuel				●	
<b>EC</b>	TECNOPRESS NOVANTA CINQUECENTO	dual fuel burners HR-KP		●			
<b>EC</b>	MILLE	dual fuel burners N		●			
<b>EC</b>	MILLE DUEMILA	dual fuel burners HR-KR		●			●
<b>EC</b>	TECNOPRESS NOVANTA CINQUECENTO	dual fuel burners KRBY		●			●
<b>EC</b>	MILLE DUEMILA	dual fuel burners KRBY		●			●
<b>ED</b>	TECNOPRESS NOVANTA CINQUECENTO	dual fuel burners HR-KR		●			
<b>ED</b>	MILLE	dual fuel burners N		●			
<b>ED</b>	MILLE DUEMILA	dual fuel burners HR-KR		●			●
<b>ED</b>	TECNOPRESS NOVANTA CINQUECENTO	dual fuel burners KRBY		●			●
<b>ED</b>	MILLE DUEMILA	dual fuel burners KRBY		●			●

● = SQM33.711A9




AZL 23

SQM33  
airSQM33  
gasSQM33  
liquid fuel

INVERTER

●	●	●		
●	●	●		
●	●		●	
●	●		●	
●	●	●		●
●	●	●		●
●	●		●	●
●	●		●	●
●	●	●		
●	●	●	●	
●	●	●	●	
●	●	●	●	●
●	●	●	●	●
●	●	●	●	●
●	●	●	●	●
●	●	●	●	●
●	●	●	●	●



# ELECTRONIC SUPERVISION AND CONTROL SYSTEM WITH LMV 5... for medium-large burners

CIB UNIGAS S.p.A has provided its burners with an electronic system of adjustment and control.

This innovative system, divided into two types of devices, can be used for both civil and industrial applications (up to 39 MW), and for burners which use a single or mixed fuel and with continuous or intermittent operation. This system allows the control of the various elements that play an important role in the correct mixture of the fuel and combustion air.

This solution allows to achieve the maximum precision in the combustion adjustment.


The system can be also expanded through interface with an oxygen control probe and/or a fan speed adjustment inverter, in order to improve the performance. In this way we can achieve high savings both in terms of fuel and electric consumption.

The adjustment and control system are made of a twin microprocessor electronic unit to integrate all burner's functions, and of a programming unit.

Integrated functions include:  
air/fuel ratio adjustment (with working point configuration possibility), PID temperature or pressure regulator, gas valve leakage control, adjustable cycle times, pre-configured fuel trains, and input/output configuration.

The programming levels are protected by password for the three types of user (OEM, service, final user); the dialogue between servocontrol and sensors is performed using twin channel CAN Bus protocol in order to guarantee the greatest safety and reliability. The unit can be installed directly on the machine or inside a separate electric control panel positioned not more than 100 meters far away from the burner.

Using the appropriate optional software, the system can be configured directly by PC.



## **Flame control box integrated functions:**

- Burner control;
- Built-in burner management system (BMS);
- Electronic cam;
- Power regulator;
- Gas valve leakage control system;
- Oxygen control;
- Inverter control;
- FGR control;
- Dialogue with BMS systems or PLC (MODBUS);
- Burner commissioning and configuration via PC-tool;
- Simple programming with AZL and PC-tool;
- Complete self-diagnostic function error memory, number of firings, burner operation time, clock, etc.;
- 3 levels of parameter access (manufacturer, servicing personell, final user);
- Remote diagnostics;
- All components can be easily interchanged;
- Parameter upgrading with PC-tool;
- Dialogue with MODBUS protocol.

# ELECTRONIC SUPERVISION AND CONTROL SYSTEM WITH LMV 5... for medium-large burners



Model	Series	Fuel	LMV 51.100	LMV 51.300	LMV 52.200	LMV 52.400
<b>ES</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas	●			
<b>ES</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	liquid fuel	●			
<b>ES</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners	●			
<b>EO</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas			●	
<b>EO</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners			●	
<b>EI</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas		●		
<b>EI</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	liquid fuel		●		
<b>EI</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners		●		
<b>EK</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas			●	
<b>EK</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners			●	
<b>EF</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas				●
<b>EF</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners				●
<b>EG</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas				●
<b>EG</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners				●
<b>EP</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas				●
<b>EP</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners				●
<b>ER</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	gas				●
<b>ER</b>	TECNOPRESS - NOVANTA CINQUECENTO - MILLE DUEMILA - TREMILA	dual fuel burners				●

\* Only monitoring

								
	AZL 5x	SQM4x air	SQM4x gas	SQM4x liquid fuel	SQM4x FGR	O <sub>2</sub> PROBE	FGR PROBE	INVERTER
•	•	•	•					
•	•	•		•				
•	•	•	•	•				
•	•	•	•	•		•		
•	•	•	•	•		•		
•	•	•	•					•
•	•	•		•				•
•	•	•	•	•				•
•	•	•	•	•		•		•
•	•	•	•	•		•		•
•	•	•	•		•		•	
•	•	•	•	•	•		•	
•	•	•	•	•	•		•	
•	•	•	•	•	•	*		
•	•	•	•	•	•	*		
•	•	•	•		•	*		
•	•	•	•		•	*		
•	•	•	•		•	*		

# FLAME CONTROL UNITS, SIGNALS AND FUNCTIONS

Progressive burners can be controlled by a 3-points signal (high/low flame) through the appropriate terminals. However, depending on the type of application and automation of the boiler, other types of signal can also be used, both at burner input (analogue modulation), and at the output (feedback signal proportional to load percentage, corresponding to actual output). A typical configuration in many boiler rooms may be, for example, using a 4÷20 mA input signal, with feedback through a potentiometer on the burner servomotor. Another very common case is the use of serial communication between several electronic control units in the boiler room. In this case different protocols (for example, Modbus), as well as different standards for signal connection and control (for example, RS-485), may be used.

BURNERS	CONTROL UNITS	FUELS	INPUT [←]				
			SINGLE FUEL	DUAL FUEL	3-point modulation (high/low flame)	analog modulation [4÷20 mA]	analog modulation [0÷10 V]
mechanical models	LME 73.000 + PME 73.831		●	●	●	○	○
electronic models (EA)	LMV 20.100		●	—	●	—	—
	LMV 27.100		●	—	●	—	—
	LMV 37.400		●	—	●	●	○
el. mod. (EB)	LMV 37.400		●	—	●	●	○
el. mod. (EC)	LMV 26.300		—	●	●	●	○
el. mod. (ED)	LMV 26.300		—	●	●	●	○
el. mod. (ES)	LMV 51.100		●	●	●*	●	●
el. mod. (EI)	LMV 51.300		●	●	●*	●	●
el. mod. (EO)	LMV 52.400		●	●	●*	●	●
el. mod. (EK)	LMV 52.400		●	●	●*	●	●

## NOTES:

**INPUT** analogue modulation

**OUTPUT** feedback signal proportional to load

● function available on standard burner

○ function available upon request; extra price may be applied on custom products

\* configurations subject to limitations; for technical details, please contact the nearest CIB Unigas branch office

## Configuration samples

1) Let's assume the project requires a burner R515A with direct interface to boiler control unit. Analogue input signal to the burner: 4÷20 mA (input from external load controller) Feedback signal to the boiler: potentiometer on servo drive, 0÷1000 Ω (output proportional to load percentage).

According to above table, first row, select a mechanical burner; in this case a simple progressive unit (PR) is enough.

For example, TP515A model M-PR.S.IT.Y.1.65

Letter "Y" identifies burner customization.

2) Let's suppose a different case. Plant specs require a modulating gas burner, with signal 0÷10 V (output proportional to load percentage). The burner has to work in continuous service mode (without stopping every 24 h).

In this case the selected control unit is a LMV37.400 (see table, 4th row) and the burner model is electronic, EA.

Thus, burner type TP515A model M-MD.S.IT.Y.1.65.EA

Some functions are present on standard CIB Unigas burners, others may be requested during quotation phase and will require, as a result, modifications to standard products (such as adding a signal converter at the input or output terminals). The following is a table list of available configurations, depending on the burner model and the required functions.

Customers are advised to specify in detail all the required functions when applying for a commercial offer, which will allow us to configure the correct burner model, including OEM parameters of electronic control units, where necessary.

If the desired signal combination is not included in this table, please contact our technical department in order to find a suitable solution.

OUTPUT [→]			OTHER FUNCTIONS			
load signal [4÷20 mA]	load signal [0÷10 V]	load signal [0÷1000 Ω]	INVERTER	OPERATION 24h/24h non-stop (continuous operation)	MODBUS via RS-485	OXYGEN CONTROL
○	○	○	-	-	-	-
-	-	-	-	-	-	-
○	○	-	-	-	○	-
○	○	-	-	○*	○	-
-	-	-	●	○*	○	-
○	○	-	-	-	○	-
-	-	-	●	-	○	-
●	○	-	-	●	●	-
●	○	-	●	●	●	-
●	○	-	-	●	●	●
●	○	-	●	●	●	●


3) Like in the previous example, let's suppose the designer requires to add VSD (variable speed drive, or inverter) to the fan motor instead of 0÷10 V signal. The control unit is still a LMV37.400 but the burner model is now EB (see table, 4th row).

Burner type TP515A model M-.MD.S.IT.Y.1.65.EB

4) Last example, similar to previous ones but suppose now that both functions are required (feedback signal and motor VSD), plus continuous service as before. The burner control unit must support all these functions at the same time, hence select an electronic cam LMV51.300 and a burner model EI (see table, 9th row). The burner will be an TP515A model M-.MD.S.IT.A.1.65.EI

## SCOPE OF SUPPLY

The specifications for the standard equipment included in the burners can be found on the following pages.  
More detailed information can be found in the operating instruction manual.




---

### GAS BURNERS

Pag. 147 - 148 - 149 - 150

---



---

### LIQUID FUEL BURNERS

Pag. 219 - 220 - 224 - 225 - 226 - 227

---

Dual fuel burners include all the necessary equipment for both gas and oil operation.

# GAS BURNERS

The gas and LPG burners include as standard supply: filter, ball manual valve (optional), pressure regulator, minimum gas pressure switch, butterfly valve.

On customer's request the maximum gas pressure switch and the tightness control function, pressure gauges (with ball valve), anti-vibration joint and other spare parts can be ordered separately.

This table includes all burner configurations according to burner type and size.

For a detailed review of these burners, it is possible to see the technical details in the diagrams.

SCHEMATIC DIAGRAM	1	2	3	4	5	6	7	8	9
		+	+		+	+	+	+	+
GAS TRAIN DUNGS MODEL	MB-DLE	MB-DLE	MB-DLE	MBE	MBE	MBE	MBE	MBE	DMV-DLE
GAS TRAIN SIEMENS MODEL	-	-	-	VGD	VGD	VGD-VRD	VGD	VGD-VRD	-
Max inlet gas pressure	360 mbar	360 mbar	360 mbar	500 mbar*	500 mbar	500 mbar*	500 mbar	500 mbar*	360 mbar
Leakage control		■	■		■	■	■	■	■
<b>BURNERS</b>									
TECNOPRESS (up to 2")	●	●	●						
TECNOPRESS (from 65)				●	●	●			
NOVANTA - CINQUECENTO					●	●			
MILLE - DUEMILA - TREMILA							●	●	
TECNOPRESS - NOVANTA - CINQUECENTO (Biogas)						●		●	●

\*700 mbar with pressure switch GW HP (except MBE 2").

VGD series gas train, DN50 and larger, are fitted with separate gas filters.


These are supplied complete with external gas filters. MB-DLE Multiblocs up to 2" are provided with built-in gas filter. The leakage control is included in all burners with power over 1200 kW.

This table includes only standard burners. CIB UNIGAS is ready to supply special configurations for individual orders.


# GAS TRAINS MB-DLE

MANUFACTURER | INSTALLER


Gas train with valves group MB-DLE  
(2 valves + gas filter + pressure governor).



Gas train with valves group MB-DLE  
(2 valves + gas filter + pressure governor) + leakage control VPS504.



Gas train with valves group MB-DLE  
(2 valves + gas filter + pressure governor) + leakage control pressure switch.




## LEGEND

- |   |   |    |  |
|---|---|----|--|
| 1 | Burner  | 6  | Gas filter   |
| 2 | Butterfly valve                                       | 7  | Anti-vibrating joint   |
| 3 | Leakage control device (optional if output < 1200 kW) | 8  | Manual cut off valve   |
| 4 | Maximum gas pressure switch (optional)                | 9  | Leakage control pressure switch (optional if output < 1200 kW) |
| 5 | Minimum gas pressure switch                           | 10 | Valves group   |


# GAS TRAINS SIEMENS VGD

MANUFACTURER | INSTALLER


Gas train with valve group VGD,  
c/w built-in pressure governor  
+ leakage control pressure switch.



Gas train with valve group VGD,  
c/w built-in pressure governor  
+ leakage control pressure switch.  
Pilot train with  
double valve and filter/governor.



Pilot train with double valve and pressure  
governor with filter.




## LEGEND

1	Burner	10	Valves group VGD
2	Butterfly valve	11	Pilot burner
3	-	12	Pilot valve
4	Maximum gas pressure switch (optional)	13	Pilot minimum gas pressure switch
5	Minimum gas pressure switch	14	Pilot pressure governor
6	Gas filter	15	Pilot anti-vibrating joint (optional)
7	Anti-vibrating joint	16	Pilot manual cut off valve (optional)
8	Manual cut off valve	17	Pilot gas reducer (optional)
9	Leakage control pressure switch		


# GAS TRAINS DUNGS MBE

MANUFACTURER | INSTALLER


Gas train with valve group MBE,  
c/w built-in pressure governor  
+ leakage control pressure switch  
+ max pressure switch.



Gas train with valve group MBE,  
c/w built-in pressure governor  
+ leakage control pressure switch  
+ max pressure switch.  
Pilot train with  
double valve and filter/governor.



Pilot train with double valve and pressure  
governor with filter.



## LEGEND

1	Burner	10	Valves group MBE
2	Butterfly valve	11	Pilot burner
3	-	12	Pilot valve
4	Maximum gas pressure switch	13	Pilot minimum gas pressure switch
5	Minimum gas pressure switch	14	Pilot pressure governor
6	Gas filter	15	Pilot anti-vibrating joint (optional)
7	Anti-vibrating joint	16	Pilot manual cut off valve (optional)
8	Manual cut off valve	17	Pilot gas reducer (optional)
9	Leakage control pressure switch		

# PRESSURE REDUCTION GROUPS

The standard burners are equipped with a gas train, with two safety valves, governor, filter and a pressure switch. The inlet pressure limits for the standard gas trains are shown in the table at page 147. For higher pressures up to 6 bar, pressure reducing units are available. The variants are described below.

## Pressure regulator supplied separately

In this case the delivery includes only the pressure reducer/pressure regulator with integrated lock-up valve pressure reducer/pressure regulator with integrated shut-off valve only. Production of a complete decompression station, is at customer's expense.



## Complete pressure reducing group, single line


This group consists of a 1st line pressure reducing station consisting of filter, pressure regulator, PPK, pressure gauges, valves and connecting pipes. The decompression station is supplied assembled. Option: The insulating dielectric connections are delivered separately.

## Complete pressure reducing group, with double line


This group consists of 2 parallel pressure reducing lines (one as a stand-by line); each line includes Gas filter, pressure regulator, safety valve, pressure gauge, cocks and connections. Decompression station is delivered assembled.

To order a complete control group, it is necessary to determine the type of gas:

1. type of gas to be used (natural gas, biogas or other)
2. The flow rate of the gas to be burnt (or which and how many burners are to be supplied)
3. Gas inlet pressure
4. Possible dimensional limits



**Fig. 01**  
Pressure reduction group on one line



**Fig. 02**  
Pressure reduction group with 2 lines

## LEGEND

1		Dielectric connection in the form of a cup (option)	4		Filter condition indicator (Option)	7		Safety shut-off valve valve (PPK)
2		Manual gas shut-off valve	5		Push button	8		Pressure regulator
3		Filter	6		Manometer	9		Safety relief valve (SSC) valve (PSK)

# NATURAL/LPG IGNITION BURNERS

The following burner models are equipped with pilot burner:

- 1000 series, single-head
- 90 / 500 series oil (single-head)
- Low-emission NO<sub>x</sub> burners, size 2000 and upwards

The following models are equipped with ignition electrodes:

- VS type burners (all)
- 90 / 500 series, gas and diesel (single-head)

SUMMARY TABLE: CONFIGURATIONS

Burners	Fuel types				
	gas	light oil	gas / light oil	heavy oil	gas / heavy oil
90 Series (single-head)	•	•	•	Δ	•
500 Series (single-head)	•	•	•	Δ	•
1000 Series (single-head)	Δ	Δ	Δ	Δ	Δ
Low NO <sub>x</sub> series (up to size 1030.1)	•	-	•	-	-
Low NO <sub>x</sub> series (2020 and larger)	Δ	-	Δ	-	-
VS series	•	•	•	•	•

• ignition with electrodes

Δ ignition with pilot burner

All pilot burners are designed to operate with natural gas or LPG.

Min/max supply pressure is 100÷360 mbar.

For complete pilot burner configuration, see page 150.

The price list includes the price of the pilot burner for all burners on which it is provided as standard (see table).

It is not possible to ignite with a pilot burner on the VS models.


However, it is possible to order burner size 90-500 (single-head burner) in a special configuration with pilot burner:

In this case, an extra charge must be added to the price of the standard burner.

# LIGHT OIL PILOT BURNERS

Upon customer's request it is possible to supply a light oil pilot burner instead of a gas burner. In this case the supply includes the components described below.

**Fig. 01**



## LEGEND

1	Light oil pilot burner	4	Pump and motor	7	Filter
2	Light oil fuel hose	5	Manometer holding cup	8	Manual ball valve (optional)
3	Electrical valve	6	Manometer		

Notes and limits on light oil use: oil must be supplied at a pressure of 0÷1,5 bar and a temperature not below 5°C. The fuel supply pressure at the pilot burner nozzle is 12 bar; the output is 40÷150 kW, depending on burner size. The final configuration of the light oil pilot burner train is variable, depending on customer's specifications. For example, if the standard burner already includes a pump (e.g. TG diesel burners), the ignition burner pump may be left out from the scope of supply because it is unnecessary.  
In case oil supply pressure higher than 1,5 bar, please contact CIB UNIGAS.

To order a burner with a light oil pilot burner, select a model equipped with gas ignition burner (see table on the previous page).

## REVERSIBLE GAS TRAIN


During the installation phase of the burner, the gas train can be installed either on the right or on the left side by simply turn the flanged connection in the desired direction.

The installation can be completed with anti-vibration joint, manual ball valves and other options.


All sizes (series 90, 500, 1000, 2000, 3000) are equipped with reversible gas train (right and left).

This applies to all models of gas and dual gas-light oil burners (e.g. for TP and HTP series).

On dual fuel gas-heavy oil burners (KTPBY and KTP) the gas outlet is exclusively located on the left side of the burner, due to the built-in oil pre-heater tanks.



*Example of burner with separate fan, model HTP1030A, with reversible gas train.*



*Examples of special configurations made on request, 2 gas types.*

## BURNERS OPERATING WITH COMBUSTION AIR HIGH TEMPERATURE

Some processes or industrial applications require the use of hot combustion air, mainly for the purpose of saving fuel and improving the efficiency of the boiler plant.

Burners with a separate fan and electrical panel, with appropriate modifications, can be used with hot combustion air temperatures of up to 250 °C.

When ordering, simply declare the required operating temperature of the combustion air.

Attention: the standard burners are able to operate at combustion air temperatures up to 50 °C; to order a modified burner capable of operating with hot combustion air, it is necessary to add an extra charge to standard burner price.



*Example of a burner with a separate fan, capable of handling high-temperature combustion air.  
Burner colour can be selected in the order.*

If a combustion air temperature higher than 250 °C is required, send a request to our R&D. CIB Unigas Technical Department is ready to review your project specifications and find a solution to satisfy every customer.


## BURNER HEAD ORIENTATION


Burners of this type are supplied with separate fans. The delivery includes motorised air damper with actuator, and a corrugated flange connecting the burner to air duct.

The duct and fan can be positioned according to the design, taking into account the specifications and limits of the location.

For example the fan is usually installed below or behind the boiler level, depending on customer's requirements.


Our burners can easily accept combustion air coming from four different directions, as shown in the following picture.





The desired orientation must be specified when ordering: example HTP1030A burner with combustion air inlet from above, position C




## BURNER HEAD ORIENTATION



The desired orientation must be specified when ordering: example TLX2020 burner with combustion air inlet from above, position C.

# BURNER INSTALLATION

BURNER AMBIENT AIR FROM BELOW



## LEGEND




- 1 Boiler
- 2 Burner

- 3 Fan ventilator
- 4 Cold combustion air regulation damper

B Ambient air

# BURNER INSTALLATION

BURNER AMBIENT AIR FROM ABOVE






## LEGEND

1 Boiler  
2 Burner

3 Fan ventilator  
4 Cold combustion air regulation damper

B Ambient air

BURNER HOT AIR FROM BELOW






#### LEGEND

- 1 Boiler
- 2 Burner
- 3 Fan ventilator
- 4 Cold combustion air regulation damper
- 9 Economizer

- B Ambient air
- C Heated air

# BURNER INSTALLATION

BURNER HOT AIR FROM ABOVE





## LEGEND

- 1 Boiler
- 2 Burner
- 3 Fan ventilator
- 4 Cold combustion air regulation damper
- 9 Economizer

- B Ambient air
- C Heated air

## BURNER AMBIENT AIR WITH FGR




### LEGEND

- |                  |   |                         |                          |
|------------------|---|-------------------------|--------------------------|
| 1 Boiler         | 4 Cold combustion air regulation damper | 7 FGR regulation damper | A Flue gas recirculation |
| 2 Burner         | 5 Differential pressure switch          | 8 FGR temperature probe | B Ambient air            |
| 3 Fan ventilator | 6 Condensate drain                      |                         |                          |

# BURNER INSTALLATION


BURNER HOT AIR FROM ABOVE WITH FGR BEFORE THE ECONOMIZER  
Used when the smoke temperature is < 200 °C before economizer



## LEGEND

1 Boiler	4 Cold combustion air regulation damper	7 FGR regulation damper	A Flue gas recirculation
2 Burner	5 Differential pressure switch	8 FGR temperature probe	B Ambient air
3 Fan ventilator	6 Condensate drain	9 Economizer	C Hot air

BURNER HOT AIR FROM ABOVE WITH FGR AFTER THE ECONOMIZER  
Used when the smoke temperature is > 200 °C before economizer



LEGEND

- |                  |   |                         |                          |
|------------------|---|-------------------------|--------------------------|
| 1 Boiler         | 4 Cold combustion air regulation damper | 7 FGR regulation damper | A Flue gas recirculation |
| 2 Burner         | 5 Differential pressure switch          | 8 FGR temperature probe | B Ambient air            |
| 3 Fan ventilator | 6 Condensate drain                      | 9 Economizer            | C Hot air                |


# FACILE SYSTEM

## THE FIRST BURNER WITH SELF REGULATION

The **FACILE** can also be applied to duo bloc burners by assembling the components as shown in the drawing.

## OVERTURNING THE PERSPECTIVE IS **FACILE**

The **FACILE** " project stems from the vision of creating an easy commissioning burner, and, at the same time, making it more efficient in terms of energy consumption. From the beginning, the goal was to observe the "machine" from a different point of view, away from the classic design stereotypes of the burner, and developing a new concept. The burner is no longer seen as a passive device but, on the contrary, interactive and autonomous in relation to the environmental variables and plant conditions.




### INDIRECT O<sub>2</sub> CONTROL

Indirect Oxygen Control: the air/gas ratio is guaranteed and corrected, measuring in real time the mass flow.



**FACILE** is provided with a system for remote data transmission which allows an analysis of the functioning by the end user, and a service of predictive maintenance.



### VARIABLE PERFORMANCE CURVE

Variable performance curve: the performance curve is automatically adapted to the peculiarities of the boiler. Moreover the system guarantees the correct combustion, by limiting the working point where the fan cannot provide the necessary air flow rate.

## A SMART SYSTEM

There are already electromechanical and electronic burner control systems which allow a certain elasticity and reactivity of the machine according to the change of external variables. However, we decided to go a step further and achieved a new technological breakdown in this field, by providing the machine with a "brain" which self-tune the fuel/air ratio in the initial start-up phase, and maintains the combustion throughout its use in an optimum range of safety and efficiency according to environmental variables and plant conditions.

## THERE IS A TECHNICIAN BUT YOU CAN'T SEE HIM

The main feature of the system is that it does not need the setting of the burner on plant, and therefore it skips the (sometimes) laborious and expensive commissioning operated by a qualified technician.

The fuel curves of the burner are automatically created by the system in the initial start-up phase, according to the type of generator and process. This phase, completely automatic, is generally carried out in 10/20 minutes time, and it does not need any intervention by a technician other than a general supervision. This saves a significant amount of time and resources in the initial start-up phase.

## AS SIMPLE AS **FACILE**

The system does not provide a "Closed Loop" type check with a feedback on combustion (Lambda sensor - O<sub>2</sub> sensor – probe CO), and it is ready to work without any changes which can affect the generator. Of course, the "Closed Loop" type check remains available as an optional. **FACILE** includes a full modulating system with settable PID parameters, which allow management of the thermoregulation function without adding further devices.

Furthermore the system manages the inverter to increase the power ratio between maximum and minimum, and to reduce the electrical consumption.




### SELF LEARNING IGNITION POINT

Self Learning - Ignition Point: the ignition point is automatically regulated on a capacity suitable to ensure an optimal ignition, always complying to the EN 676 standards. The ignition point can be chosen manually up to 50% of the maximum load.



### SELF LEARNING SERVO MOTORS SETTINGS

Self Learning - Servo Motors Settings: the system memorizes automatically the working curves of servo-motors to guarantee the functioning also in case of sensors malfunction. The interface warns the user about the change occurred. Based on the flow totalizers, the service can be easily scheduled.



### SELF CHECKING AIR/GAS RATIO

Self Checking - Air/Gas Ratio: the air/gas ratio is constantly monitored and adapted to guarantee the required power and to maintain the optimal efficiency of the installation.

## MORE THAN A SIMPLE BURNER

"**FACILE**" is not a simple burner, but a "combustion philosophy". With **FACILE** the burner operation is granted within its performance characteristics according to the applicable regulations. The system, thus, guarantees safety, and excludes any non-compliant adjustments.

**FACILE** is also equipped with a device for remote data control which allows to monitor burner operations and obtaining parameters and statistics useful to the end user. A specific platform is developed to the benefit of the technical servicemen in order to provide a predictive maintenance schedule, and to simplify the service management and costs.

# ADJUSTMENT OF THE BURNERS

When choosing the burner, the customer may select one among the following configurations.

## TN (single-stage)

Burners with single-stage regulation operate in ON-OFF configuration: when an external switch (e.g. the boiler regulation thermostat) closes, the burner is switched on, and then operates at maximum power. When the generator set-point is reached, the contact opens, the flame is switched off and the burner is kept in stand-by.

## AB (two-stage)

Burners with two-stage regulation operate in HIGH-LOW flame configuration: a signal from the boiler regulation thermostat takes the burner to high flame (maximum power); as soon as the high flame threshold is reached, the burner shifts quickly to low flame (minimum power). When the lower threshold is reached, the burner reverts to high flame. Boiler temperature will thus oscillate around the desired setpoint. If the thermostat limit threshold is exceeded, the flame is switched off and the burner goes into stand-by. The two-stage regulation allows higher efficiency.

## PR (progressive)

Conceptually, progressive burners operate like two-stage ones, i.e. with high-low flame type regulation. The difference is that transients between two stages follow a regulation control curve (combustion air-fuel ratio). AB burners are limited by the power difference between high flame and low flame stages; PR regulation, while retaining the same functional characteristics, does not pose such limits - the combustion is always well regulated, even at intermediate power outputs. Additionally, liquid fuel PR burners are equipped with a single by-pass (variable flow) nozzle instead of two nozzles (one for each stage); in case of variable load operation, load transients do not require large power jumps.

Note: if the boiler control unit requires burner control via an analogue input signal (e.g. 4 ÷ 20 mA or 0 ÷ 10 V), please select a PR model burner. When requesting a quotation, specify the signal type given by the control unit, and the required feedback signal (e.g. 0 ÷ 1000 Ω via potentiometer on the actuator).

Attention, the burner configuration may vary according to the specific requests. See page 144 for a detailed explanation of I/O signal options.

## MD (modulating)

Modulating burners are equivalent to PR ones, but supply includes by default a power regulator based on PID control system. The regulator synchronizes burner power and required load, via a feedback signal coming from a sensor installed on the boiler (also called modulation probe). Thermocouples can be used (for hot water and superheated water boilers, diathermic oil heaters, hot air generators, ovens and furnaces), or pressure transducers (for steam boilers). The air-fuel ratio is adjusted along a curve over the entire working range.

## PR or MD burners with electronic cam

Electronic cam burners employ the same operating principle as the corresponding mechanically regulated burners: the air-fuel ratio curve is stored in the electronic unit memory, rather than being physically set by a variable cam connected to servo motors. The electronic cam is extremely precise and offers several advantages, first of all it overcomes all limitations typical of mechanical linkages (e.g. tear and wear, play between the moving parts, hysteresis). On the other hand, control units are more sensitive to electromagnetic interference, therefore quality of power supply is a fundamental factor in thermal plant design.

Note: to order a modulating burner, please select the desired probe separately.

Controlled variable	Temperature/pressure range
Temperature	-15 ÷ 50 °C
Temperature	30 ÷ 130 °C
Temperature	0 ÷ 400 °C
Temperature	0 ÷ 1200 °C
Pressure	3 bar
Pressure	10 bar
Pressure	16 bar
Pressure	25 bar
Pressure	40 bar



Other sensors and/or different scales available upon request.

## Control range and modulating ratio of a burner

Each burner, whether with an on-board or separate fan, is characterized by its performance curve defined by the minimum and maximum output within which it can operate. The modulating ratio is defined as the actual ratio between the minimum and maximum output of a specific thermal group burner-boiler (or burner-generator). The Performance curve is therefore quite different from the modulating range of the burner.


To better understand this concept let's make an example:

Let's consider a burner with a performance curve of 1.000 kW – 5.000 kW matched to a boiler that requires an output of 5 MW. If we assume a modulating ratio of 1:4, the minimum achievable output is 5.000 kW:  $4 = 1.250$  kW.

The same burner, matched to a boiler which requires a max output of 4 MW, with exactly the same modulating ratio of 1:4, delivers a minimum output of 1.000 kW.

Let's consider the very same burner matched to a boiler which requires 3 MW only. Since the burner cannot work below its mechanical limits, it will operate with a reduced modulating ratio 1.000 kW:  $3.000$  kW = 1:3.

It's important to remember that the modulating ratio of any burner is strongly affected by the boiler on which it is installed.




To obtain the best performance, it is recommended to choose the burner with the widest possible modulating ratio, and the maximum output as close as possible to that required by the boiler.

For example, if the working point of the boiler (point A in the picture) can suit many burners, it is recommended to pick up the model whose maximum output is closer to that required (curve 1). This is the best choice, both economically (smaller burner size), and technically, because it provides the widest modulating ratio.

A burner similar to curve 2 in the example, could only operate at an output which is already close to its min limit, and this would not allow any modulating ratio, meaning a completely negative situation.

Finally, let us remember two additional factors that can affect the modulating ratio:

- the boiler or heat generator manufacturer, as a rule, writes the maximum recommended modulating ratio to prevent the temperature of the flue gases at the minimum output to fall below the condensation limit.
- liquid fuel burners are bounded to the modulating ratio of the nozzles (typically 1:3 - 1:4, except special applications).



# ADJUSTMENT OF THE BURNERS

## Burners with high modulating ratio


A special high modulating ratio customization is available on Class 2 gas and dual fuel burners with electronic control (variants with LMV51/52 units). This configuration can guarantee a ratio 1:6 between minimum and maximum power (1:10 with inverter).

This excellent performance is achieved by precisely dosing air flow at low power, while maintaining required flame stability. High modulation ratio is recommended when project specifications call for an extremely low minimum load, and it is not possible to achieve this with other means (e.g. several smaller burners in cascade control).

Typical examples include burners for condensing boilers, applications such as processing plants or furnaces, e.g. food cooking ovens.

X

However, it is not recommended to use such configuration when there is risk of acidic condensate formation at the chimney (exhaust gases temperature too low), or on ordinary steam boilers for example. The use of burners with a high modulating ratio should always be agreed upon with the boiler or furnace manufacturer.



# HOW TO CHOOSE A BURNER

## How to choose a duo-bloc burner at sea level and at altitude

To ensure a complete and safe combustion, the burner must be supplied with the correct flow of oxygen. The amount of oxygen available is proportional to the density of the combustion air, and the density depends on the environmental conditions.

For this reason, the performance curves of the burners are defined under standard environmental conditions at sea level with temperature 15 °C and pressure 101,3 kPa.

Of course, under real operating conditions, the temperature and pressure of the air change constantly. If the air density decreases (e.g. when summer temperatures are very high) also the oxygen available in one cubic meter of air is reduced and vice versa: this difference must therefore be taken into account.

Small daily variations are usually within the tolerance defined by the standard, so they are negligible.

On the other hand seasonal variations must be compensated, therefore it is suggested to schedule periodical checks of the combustion during the year. In this way, the formation of carbon monoxide (CO) is avoided, as the combustion is always in excess of air: typically the residual oxygen is fixed at 3%. It should be also remembered that the atmospheric pressure and air density decrease as the altitude increases. Up to 300 meters this variation is negligible. However in case the burner is intended to work in mountainous regions such as the Alps, it is necessary to recalculate the parameters of the system.

In order to avoid mistakes in calculations always remember to provide also the altitude of the plant at the moment of the enquiry!

The table on the right gives the correction factors to be applied to the calculations. Below is an example of how to choose a duo-bloc burner at altitude.

Suppose you have to select a burner intended for the city at altitude. This city is surrounded by mountains, and the thermal output plant will be built at approximately 1.000 meters above sea level.

The data of the boiler to be matched are:

- nominal output Pn	9.500 kW
- efficiency η	91 %
- back pressure in combustion chamber Cp	12 mbar
- fuel	natural gas

The first step is to calculate the output (Pb) required to the burner:

$$P_b = \frac{P_n}{\eta} = \frac{9.500}{0.91} = 10.339 \text{ kW}$$

Note the altitude of the plant above sea level (1.000 meters) and obtain the correction coefficients K1 and K2 from the table. In this case:

$$K_1 = 1,128$$

$$K_2 = 1,272$$

Installation height above sea level	CORRECTION FACTORS	
	K <sub>1</sub> (Power)	K <sub>2</sub> (Back-pressure in the combustion chamber)
300	1,036	1,074
400	1,049	1,100
500	1,061	1,127
600	1,074	1,154
700	1,087	1,182
800	1,100	1,211
900	1,114	1,241
1.000	1,128	1,272
1.200	1,155	1,334
1.400	1,184	1,402
1.600	1,213	1,472
1.800	1,243	1,546
2.000	1,276	1,628
2.400	1,342	1,801
2.800	1,410	1,988
3.200	1,483	2,199
3.600	1,561	2,437
4.000	1,644	2,703

Correct the output and back pressure by applying K1 and K2 respectively:


$$P_b (\text{corrected}) = P_b \times K_1 = 10.339 \times 1,128 = 11.775 \text{ kW}$$

$$C_p (\text{corrected}) = C_p \times K_2 = 12 \times 1,272 = 15,3 \text{ mbar}$$

The correct burner is TP1030.

# HOW TO CHOOSE A BURNER

To ensure a complete and safe combustion, the burner must be supplied with the correct flow of oxygen. The amount of oxygen available is proportional to the density of the combustion air, and the density depends on the environmental conditions.



Attention! The correction applied does not change the actual output that the burner must develop. If the boiler is always 9.500 kW, and the burner always develops 10.339 kW, then why was a 11.775 kW burner selected?

What has changed is the performance of the fan, which must deliver a sufficient oxygen flow to the fuel combustion.

The choice of burner is therefore made in the following way: the performance curve of the burner is maintained as if the system was located at sea level, but we pretend that the boiler requires a higher performance according to the K1 and K2 coefficients.

This operation is equivalent to maintaining the real working point, and reducing the performance curve of the burner. The result is the same but the calculation is simpler and faster.

## How to choose the correct ventilator

According to the application output or the fuel flow rate we need to calculate the needed air considering the following data:

- Output / Fuel air flow;
- Temperature of combustion air;
- Backpressure in the combustion chamber;
- Sea level altitude.

In order to size the correct fan motor the following calculation has to be made:

1. Air flow needed;
2. Pressure needed.

First of all we need to calculate the air flow needed in function of Nm<sup>3</sup>/h for gas or kg/h for oil and multiply it for the following coefficients:

Gas: K = 12

Light oil: K = 15,7

Heavy oil: K = 15

Example:

Burner capacity : 10.339 kW

$$10.339 \times 860/8.125 = 1.094 \text{ Nm}^3/\text{h} \text{ of gas}$$

The quantity of air will be:

$$1094 [\text{Nm}^3/\text{h}] \times 12 = 13.132 \text{ m}^3/\text{h} \text{ of air}$$

This value must be adjusted according to the following:

1. temperature of combustion air (standard 20 °C - table for different temperature);
2. sea level (refer to the table for correction factors);
3. air loss of the connecting pipes between burner head and ventilator (estimated to 5 %).

Example at 100 mt sea level:

Results will be the following for an installation at 100 m from the sea level and with 15 °C of air:  
 $13.132 \text{ [m}^3/\text{h}] \times 1,05 / 0,988 = 13.956 \text{ m}^3/\text{h}$

Example at 1500 mt sea level:

Results will be the following for an installation at 1500 m from the sea level and with 15 °C of air:  
 $13.132 \text{ [m}^3/\text{h}] \times 1,05 / 0,852 = 16.183 \text{ m}^3/\text{h}$

## TOTAL AIR PRESSURE

To finalize the calculation we shall consider the following:

- draught loss of burner head (see graphics for each burner);
- backpressure in the combustion chamber;
- additional loss given from accessories like heat exchanger, filters, ...;
- correction factor for safety: multiply value for 1,2.

Example of sea level:

Burner capacity: 10.339 kW 1094 Nm<sup>3</sup>/h gas for TP1030

- head loss = 25 mbar (see graph at pag. 189)
- backpressure installation = 12 mbar
- correction factor = value x 1,2

Total:  $(25+12) \times 1,2 = 44,4 \text{ mbar}$

Final calculated data for selecting the ventilator:

Air pressure = 44,4 mbar

Example of 1000 mt sea level:

Burner capacity: 11.775 kW

- head loss = 25 mbar (see graph at pag. 191)  $25 \times 1,128 = 32 \text{ mbar}$
- backpressure correction  $12 \times 1,4 = 16,8 \text{ mbar}$
- safety correction factor = value x 1,2

Total:  $(32+16,8) \times 1,2 = 58,5 \text{ mbar}$

Final data achieved for selecting the ventilator:

Air pressure = 58,5 mbar

Temperature (°C)	Air density (kg/m <sup>3</sup> )	CORRECTION FACTORS												
		Sea level altitude (m)												
		0	250	500	750	1000	1250	1500	1750	2000	2250	2500	2750	3000
0	1,293	1,073	1,042	1,012	0,982	0,954	0,926	0,899	0,873	0,847	0,823	0,799	0,775	0,753
5	1,270	1,054	1,023	0,993	0,965	0,936	0,909	0,883	0,857	0,832	0,808	0,784	0,761	0,739
10	1,247	1,035	1,005	0,976	0,947	0,920	0,893	0,867	0,842	0,817	0,793	0,770	0,748	0,726
15	1,226	1,017	0,988	0,959	0,931	0,904	0,878	0,852	0,827	0,803	0,780	0,757	0,735	0,714
20	1,205	1,000	0,971	0,943	0,915	0,888	0,863	0,837	0,813	0,789	0,766	0,744	0,722	0,701
25	1,185	0,983	0,955	0,927	0,900	0,874	0,848	0,823	0,799	0,776	0,754	0,732	0,710	0,690
30	1,165	0,967	0,939	0,911	0,885	0,859	0,834	0,810	0,786	0,763	0,741	0,720	0,699	0,678
40	1,128	0,936	0,909	0,882	0,857	0,832	0,807	0,784	0,761	0,739	0,717	0,697	0,676	0,657
50	1,093	0,907	0,881	0,855	0,830	0,806	0,782	0,760	0,738	0,716	0,695	0,675	0,655	0,636
60	1,060	0,880	0,854	0,829	0,805	0,782	0,759	0,737	0,715	0,695	0,674	0,655	0,636	0,617
80	1,000	0,830	0,806	0,782	0,760	0,737	0,716	0,695	0,675	0,655	0,636	0,618	0,600	0,582
100	0,946	0,786	0,763	0,740	0,719	0,698	0,678	0,658	0,639	0,620	0,602	0,585	0,567	0,551
150	0,834	0,693	0,672	0,653	0,634	0,615	0,598	0,580	0,563	0,547	0,531	0,515	0,500	0,486
200	0,746	0,619	0,601	0,584	0,567	0,550	0,534	0,519	0,504	0,489	0,475	0,461	0,448	0,434
250	0,675	0,560	0,544	0,528	0,513	0,498	0,483	0,469	0,456	0,442	0,429	0,417	0,405	0,393

# EMISSIONS

The subject of emissions is very wide and complex. The scientific literature in this field is under continuous update and there's no way to describe it briefly.

The boiler room is a source of pollution caused by the combustion of hydrocarbons. Combustion products consist mainly of nitrogen, carbon dioxide and steam delivered into the atmosphere through the chimney. The products of secondary combustion include a long list of chemicals, such as (CO), nitrogen oxides ( $\text{NO}_x$ ), fine particulate matter (PM) and others. The normative in force provide their max limits.

The level of emissions depends on many factors, including:

- fuel composition;
- shape of the combustion chamber and characteristics of the boiler;
- type of burner head.


For example, liquid fuels usually contain sulphur and other impurities.

These substances do not burn, therefore, if there is a need to reduce emissions, it is necessary to use a high performance burner or to use complex systems for the treatment of fumes.

The emissions of nitrogen oxide also depend on the characteristics of the combustion chamber and the combustion head.

Due to the fact that the limit values required by the technical standards for the environmental protection are more and more restricted, it is necessary to pay particular attention to propose a correct choice of burner and boiler.

CIB UNIGAS Technical Management keeps always an eye on new technologies to reduce emissions. For these reasons CIB UNIGAS has been investing in the development of low environmental impact burners.



All CIB UNIGAS burners are certified for both gaseous and liquid fuels in accordance with European standards and meet the requirements for polluting emissions.

Measurements of CO and NO<sub>x</sub> emissions are carried out on standard size boilers, on all test conditions.

**TABLE: LIMIT VALUES FOR EMISSIONS OF NITROGEN OXIDES AND CARBON MONOXIDE ACCORDING TO THE EUROPEAN STANDARD**

Type of fuel	Burner class	Unit of measurement	CO	NO <sub>x</sub>	Standards
natural gas	Class 1	mg/kWh	100	170	UNI EN 676
natural gas	Class 2	mg/kWh	100	>80 <120	UNI EN 676
natural gas	Class 3	mg/kWh	100	>60 <80	UNI EN 676
natural gas	Class 4	mg/kWh	100	<60	UNI EN 676
LPG gas	Class 1	mg/kWh	100	230	UNI EN 676
LPG gas	Class 2	mg/kWh	100	180	UNI EN 676
LPG gas	Class 3	mg/kWh	100	140	UNI EN 676
LPG gas	Class 4	mg/kWh	100	110	UNI EN 676
light oil	Class 1	mg/kWh	110	250	UNI EN 267
light oil	Class 2	mg/kWh	110	185	UNI EN 267
light oil	Class 3	mg/kWh	60	120	UNI EN 267

## CIB UNIGAS burners, NO<sub>x</sub> emissions:

- Low NO<sub>x</sub> gas burners correspond to Class 2, Ultra Low NO<sub>x</sub> burners without FGR correspond to Class 3.
  - LPG burners correspond to Class 1, Low NO<sub>x</sub> LPG burners correspond to Class 3;
  - Oil burners have a maximum NO<sub>x</sub> emission of 250 mg/kWh (Class 1);
  - Heavy fuel oil burners (non-standard fuel oil) can, in the worst case, reach a maximum NO<sub>x</sub> emission of 700 mg/kWh.
- CIB Unigas also offers Low NO<sub>x</sub> solutions for complex systems and revamping existing plants.
- As far as carbon monoxide (CO) is concerned, a properly set CIB UNIGAS burner delivers a very small CO level.

If necessary, CIB UNIGAS offers FGR solutions – these are burners with Flue Gas Recirculation system which deliver emissions of less than 50 or 30 mg/kWh. Burners with FGR are designed for installations with Low NO<sub>x</sub> emissions requirements, such as greenhouses or boilers in large residential areas where low levels of contaminants are a priority. Our FGR solutions meet environmental impact requirements.

**The burners belonging to the different classes of NO<sub>x</sub> emissions are identified by the following logos:**



Often non-EU countries follow different normatives and measurement conditions. To ensure that the levels of pollutant emissions are always correct, it is necessary to know exactly the conditions in which tests were carried out, i.e. measurement of the gas, the error, type of fuel, boiler size, atmospheric conditions, etc.

In addition, standards can use different units of measurement\*. Therefore for the comparison, it is necessary to translate the limit values expressed as follows in mg/kWh (milligrams per kilowatt hour), using the correct formula, depending on the selected fuel and residual oxygen in the exhaust gases.

\* For example: ppm (parts per million), mg/Nm<sup>3</sup> (milligrams per normal cubic meter), etc.

# LOW NO<sub>x</sub> BURNERS - TECHNICAL NOTES


## WHY DIFFERENT THERMAL GROUPS RELEASE DIFFERENT LEVELS OF NITROGEN OXIDES AT THE SAME OUTPUT?

The CO, NO<sub>x</sub> and other pollutants are strongly influenced by a number of factors, not always burner related. There are factors independent from the thermal plant, such as environmental conditions (altitude, humidity, fuel composition, etc...) and factors related in particular to the design of the generator. The most important factors are summarized below. It becomes evident that burner and boiler must be evaluated as a single thermal group, in order to comply to the rule on emission levels, or to the specific requirements of designers. The correct match between burner and boiler is discussed in greater detail on the following pages.

### BOILER TYPE




- type of generator (reverse flame, or 3 smoke-pass)
- dwell time of the flame within the combustion chamber
- heat exchange surface
- temperature and type of heat transfer fluid



### DIMENSIONS OF THE COMBUSTION CHAMBER




- combustion chamber internal gas circulation
- dwell time of the flame within the combustion chamber
- thermal load of the chamber



### THERMAL LOAD OF THE COMBUSTION CHAMBER




- flame temperature
- speed at which the NO<sub>x</sub> is formed



### BOILER TEMPERATURE




- flame temperature
- speed at which the NO<sub>x</sub> is formed



### THICKNESS OF THE REFRACRYORY OR BOILER DOOR



- length of the combustion head
- internal combustion gas circulation



Reverse flame boilers: contact our Technical Department.


## WHY CHOOSE CIB UNIGAS

### Relation between NO<sub>x</sub> emissions and CO

Emissions of nitrogen oxides and carbon monoxide are strongly correlated as both depend on the stoichiometry of the combustion. Excess of air affects both emissions and the efficiency of the generator. In a logic of compromise, reducing fuel consumption requires a reduction of excess air.

The limit is given by the emission of CO. In the burners of the previous generation this choice had priority on NO<sub>x</sub> emissions.

### THE "ECOLOGIC" BURNER SERIES HAS REACHED A GREAT GOAL: WIDE RANGE OF COMBUSTION FLEXIBILITY



The development of low burners emissions represent a real revolution in the way NO<sub>x</sub> and CO interact when changing the excess of air.


The new series of Low NO<sub>x</sub> burners from the CIB UNIGAS ensures zero CO values in a very wide range of operation, with residual oxygen between 0,5 % and 8 %, while maintaining low NO<sub>x</sub> emissions almost constant.

The advantage is obvious: the careful choice of the the generator makes possible, for example, to set the oxygen at 1,5 % without formation of CO; increasing the efficiency of the thermal group without deteriorate the NO<sub>x</sub> emissions.


Economical and ecological.



#### EMISSION LIMIT CO



#### NO<sub>x</sub> EMISSION LIMITS ON 3 SMOKE-PASS BOILERS



Reverse flame boilers: contact our Technical Department.

# MATCHING LOW NO<sub>x</sub> BURNER AND HEAT GENERATOR

## INTRODUCTION

To choose any burner, the following data are mandatory:

- Boiler type
- Burner input
- Backpressure in the combustion chamber
- Dimensions of the combustion chamber included the reverse smoke chamber
- NO<sub>x</sub> emissions requested, 80, 50, 30 mg/kWh

The procedure is divided into three steps:

- choosing the burner;
- to obtain the correct emissions
- choosing the blast tube length.

## CHOOSING THE BURNER

### Introduction



To clearly explain the procedure please follow the example.

Example:

Boiler type	3 pass
Furnace input	7.300 kW
Backpressure in combustion chamber	12 mbar
Dimensions of combustion chamber	Length L = 4.450 mm (4,45 m)
Smoke reverse chamber	Length L = 400 mm (0,4 m)
Total length of combustion chamber	Length TL = 4.850 mm (4,85 m)
Diameter	D = 1.250 mm (1,25 m)
Combustion chamber volume	D x D x 0,78 x TL 1,25 m x 1,25 m x 0,78 x 4,85 m = 5,91 m <sup>3</sup>
Thermal load MW/m <sup>3</sup>	Furnace input kW/Combustion chamber volume /1000 7.300/5,91/1.000 = 1,23 MW/m <sup>3</sup>
Gas type	Natural gas


Next step, identify the burners whose requested outputs are included within their performance curves.

## BURNER SELECTION FOR NO<sub>x</sub> < 80 mg/kWh



Consider the operating range of the burner chosen in the above diagram: draw a vertical line matching the furnace input value (7.300 kW) and a horizontal line matching the backpressure value (12 mbar) (Fig. 1).

The burner is suitable if the intersection is inside the performance curve (these curves are correct for the NO<sub>x</sub> < 80 mg/kWh). In this case we have 62 mg/kWh at 3 % O<sub>2</sub> (Fig. 2).



#### Reference conditions

- Measurement tolerances according to EN 676 standard
- Temperature: 20 °C
- Dried flue gases
- Barometric pressure: 1013 millibars
- Relative humidity: 70 % (equivalent to 10 g H<sub>2</sub>O/kg of air)
- Boiler temperature: 110 °C
- Fuel: G20 (natural gas, 100 % CH<sub>4</sub>)
- Three-smoke pass boiler

The final step is to check blast tube dimensions, in relation to combustion chamber, because they are a critical parameter to obtain the expected emissions.

Two conditions should be met:

- 1) It is recommended that the diameter of the chamber is 2,5 to 3 times larger than the diameter of the burner blast tube.
- 2) The low NO<sub>x</sub> blast tube must penetrate 150÷200 mm into the combustion chamber.

In the cited example, the boiler chamber diameter was 1.250 mm, so the optimal blast tube diameter lies in the range between 400 mm and 500 mm.


The dimensional table on page 83 shows that TLX525.1 blast tube diameter is equal to 419 mm, thus the first condition is met.

Regarding the blast tube length, suppose the boiler door is 350 mm thick, refractory included. The blast tube must penetrate at least 150 mm as said above, thus the long blast tube variant is selected (530 mm). The short blast tube (430 mm) is insufficient as it only penetrates by 80 mm into the combustion chamber.

In this case we have 180 mm.

To properly install the burner, please refer to Fig. 3 to the side.

Of course, it is possible to carry out the reverse procedure as well: given an emission limit that cannot be exceeded by design, the NO<sub>x</sub> diagram provides the admissible thermal load for a given heat generator. This way, designer can select a suitable boiler based on project specifications and required power. In any case, burner blast tube dimensions must be checked to complete the matching procedure.




# MATCHING LOW NO<sub>x</sub> BURNER AND HEAT GENERATOR

## BURNER SELECTION FOR NO<sub>x</sub> < 50 mg/kWh and < 30 mg/kWh

With NO<sub>x</sub> < 50 mg/kWh and < 30 mg/kWh we need to have a smoke recirculation (FGR).

The smoke recirculation decreases a percentage of the performance curves and increases the backpressure in the combustion chamber. This percentage depend also of the thermal load of the combustion chamber. In order to select the correct burner we can calculate the depowering percentage needed.

### SELECTION 1: TLX525.1...FGR




#### < 50 mg/kWh

In the selection 1 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **11 %**.

#### < 30 mg/kWh

In the selection 1 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **26 %**.

### SELECTION 2: TLX1030.1...FGR




#### < 50 mg/kWh

In the selection 2 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **9,5 %**.

#### < 30 mg/kWh

In the selection 2 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **23 %**.



#### < 50 mg/kWh


In the selection 1 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **11 %** and the backpressure in the combustion chamber increases

$$12 \times 1,25 = 15 \text{ mbar}$$

#### < 30 mg/kWh

In the selection 1 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **26 %** and the backpressure in the combustion chamber increases

$$12 \times 1,6 = 19,2 \text{ mbar}$$



#### < 50 mg/kWh

In the selection 2 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **9,5 %** and the backpressure in the combustion chamber increases


$$12 \times 1,2 = 14,4 \text{ mbar}$$

#### < 30 mg/kWh

In the selection 2 with the thermal load 1,22 MW/m<sup>3</sup> the percentage of the depowering of the burner is **23 %** and the backpressure in the combustion chamber increases


$$12 \times 1,54 = 18,48 \text{ mbar}$$

## SELECTION 1: TLX525.1...FGR



The burner TLX525.1 in the **selection 1** is outside of the performance curve, for this reason we can not choose this burner.

## SELECTION 2: TLX1030.1...FGR



The burner TLX1030.1 in the **selection 2** is correct because is inside of the performance curve with emissions 50 and 30 mg/kWh.

The final step is to check blast tube dimensions with a new burner selected, in relation to combustion chamber, because they are a critical parameter to obtain the expected emissions.

### SELECTION 1

It is recommended that the diameter of the chamber is 2,5 to 3 times larger than the diameter of the burner blast tube.

### SELECTION 2

The low NO<sub>x</sub> blast tube must penetrate 150÷200 mm into the combustion chamber.

In the cited example, the boiler chamber diameter was 1.250 mm, so the optimal blast tube diameter lies in the range between 400 mm and 500 mm.

The dimensional table on page 84 shows that TLX1030.1 blast tube diameter is equal to 491 mm, thus the first condition is met.


Regarding the blast tube length, suppose the boiler door is 350 mm thick, refractory included. The blast tube must penetrate at least 150 mm as said above, thus the long blast tube variant is selected (545 mm). The short blast tube (445 mm) is insufficient as it only penetrates by 95 mm into the combustion chamber.

In this case we have 195 mm.

To properly install the burner, please refer to Fig. 4 to the side. Of course, it is possible to carry out the reverse procedure as well: given an emission limit that cannot be exceeded by design, the NO<sub>x</sub> diagram provides the admissible thermal load for a given heat generator. This way, designer can select a suitable boiler based on project specifications and required power. In any case, burner blast tube dimensions must be checked to complete the matching procedure.


If design specifications are very demanding, for example if the boiler thermal load is extremely high, CIB Unigas offers a proven low NO<sub>x</sub> solution for your needs: the FGR (flue gas recirculation) system.

Please contact our Technical Dept for further details.








# MATCHING LOW NO<sub>x</sub> BURNER AND HEAT GENERATOR

NO<sub>x</sub> DIAGRAM IN REFERENCE TO THE THERMAL LOAD




OUTPUT REDUCTION IN REFERENCE TO THE BURNER PERFORMANCE CURVE








\* According to UNI EN 676 correction method; p amb 1013 mbar; t amb 20 °C; h 10 g/kg.

NO<sub>x</sub> DIAGRAM IN REFERENCE TO THE THERMAL LOAD




OUTPUT REDUCTION IN REFERENCE TO THE BURNER PERFORMANCE CURVE








\* According to UNI EN 676 correction method; p amb 1013 mbar; t amb 20 °C; h 10 g/kg.

# MATCHING LOW NO<sub>x</sub> BURNER AND HEAT GENERATOR

NO<sub>x</sub> DIAGRAM IN REFERENCE TO THE THERMAL LOAD




OUTPUT REDUCTION IN REFERENCE TO THE BURNER PERFORMANCE CURVE








\* According to UNI EN 676 correction method; p amb 1013 mbar; t amb 20 °C; h 10 g/kg.

NO<sub>x</sub> DIAGRAM IN REFERENCE TO THE THERMAL LOAD




OUTPUT REDUCTION IN REFERENCE TO THE BURNER PERFORMANCE CURVE




\* According to UNI EN 676 correction method; p amb 1013 mbar; t amb 20 °C; h 10 g/kg.

# MATCHING LOW NO<sub>x</sub> BURNER AND HEAT GENERATOR

NO<sub>x</sub> DIAGRAM IN REFERENCE TO THE THERMAL LOAD



OUTPUT REDUCTION IN REFERENCE TO THE BURNER PERFORMANCE CURVE



\* According to UNI EN 676 correction method; p amb 1013 mbar; t amb 20 °C; h 10 g/kg.

# FANS AND ACOUSTIC HOODS BOX FAN COVERS

## Delivery condition

- Fans: packing INCLUDED
- Acoustic hoods box fan covers: Packing INC.
- Fan hoods in special design with orientation LG/RD 180/225:

## Price quotation upon request

- Anti-vibration coupling at fan delivery: INCLUDED
- Packaging is included in the delivery (the packages consist of blank wooden crates, suitable for overland transport)



To order a centrifugal fan, it is necessary to specify its orientation.

The fan is available in the following configurations:








	0	45	90	135	180	225	270	315
↻ RD								
↻ LG								

Examples: RD45, RD270, LG90, ...

# AIR PRESSURE AT THE BURNER HEAD













TP TYPE















### TP TYPE











# AIR PRESSURE AT THE BURNER HEAD



TP...VS TYPE








### TLX - TLX...FGR TYPE










# AIR PRESSURE AT THE BURNER HEAD

TLX - TLX...FGR TYPE









### TG TYPE








# AIR PRESSURE AT THE BURNER HEAD

TG TYPE









### TN TYPE











# AIR PRESSURE AT THE BURNER HEAD

TN TYPE









### TPBY TYPE





# AIR PRESSURE AT THE BURNER HEAD

TPBY TYPE










### TPBY...VS TYPE



# AIR PRESSURE AT THE BURNER HEAD













HTP TYPE















### HTP TYPE












# AIR PRESSURE AT THE BURNER HEAD



HTP...VS TYPE









## HLX - HTLX...FGR TYPE











# AIR PRESSURE AT THE BURNER HEAD

HLX - HTLX...FGR TYPE









## KTP TYPE











# AIR PRESSURE AT THE BURNER HEAD

KTP TYPE









### KTPBY TYPE





# AIR PRESSURE AT THE BURNER HEAD

KTPBY TYPE



### KTPBY...VS TYPE



# SULFUR OXIDES EMISSIONS

The polluting emissions of sulphur oxides ( $\text{SO}_x$ ) mainly include sulphur dioxide ( $\text{SO}_2$ ) and trioxide ( $\text{SO}_3$ ). These chemicals are particularly aggressive and dangerous, both for the environment and human health.

However, sulphur oxides represent a separate case from  $\text{CO}$  and  $\text{NO}_x$  since their production during hydrocarbons combustion does not depend on the burner, nor on the boiler, but only on the quantity of sulphur already present in the fuel upstream of the process.

On one hand, higher quality gaseous fuels (like methane or LPG), include insignificant amounts of sulphur, and the use of these fuels minimizes hazardous emissions. On the other hand, the problem is evident in liquid fuels especially crude oil and heavy fuel oil, whose composition always includes a certain amount of sulphur as it will inevitably be oxidized in the combustion chamber and will produce  $\text{SO}_x$ .

It is possible to estimate the quantity of  $\text{SO}_x$  produced with the diagram on this page, or with the following procedure.

Given the quantity of sulphur present in the fuel expressed as a percentage by mass, just multiply this value by a numerical factor: 1.750.

The resulting number represents the emissions of  $\text{SO}_x$  at the chimney, expressed in mg/kWh.

## Example 1


Given a fuel that contains 0,5 % sulphur,  $\text{SO}_x$  emissions will be equal to  
 $0,5 \times 1.750 = 875 \text{ mg/kWh}$

On the contrary, once the  $\text{SO}_x$  emission limit is known for a given thermal plant, it is possible to calculate the maximum allowable sulphur concentration in the fuel, dividing by the same coefficient above.

## Example 2

Let's assume that emission limit required by project specifications is 300 mg/kWh  $\text{SO}_x$ .  
The maximum percentage of sulphur in the fuel can be 300:  $300 : 1.750 = 0,17$   
The numerical result represents directly the percentage in mass: 0,17 %.

If the fuel oil contains a higher fraction of sulphur, the required limit will be exceeded, regardless of burner or boiler selection!



Reference conditions


Heavy fuel oil with net heating value  $H_i = 9.800 \text{ kcal/kg}$   
Residual oxygen at the chimney  $O_2 = 3\% (\lambda = 1,15)$

# TYPES OF FUEL


CIB UNIGAS burners can be operated with a wide range of liquid and gaseous fuels. The first two letters in the burner model indicate the type or types of fuel/s used:

## Type:

Example TP... TLX... TG... TN... TPBY... HTP... HTLX... KTP... KTPBY...



## Model: M- . XX.X . XX



### The main fuels are:

Gases	Letter for model selection
natural gas	M
LPG	L
biogas	B
synthetic gas/town gas	C

Liquid	Letter for model selection
light diesel oil (LDO)	G
biodiesel	A
kerosene, arctic diesel, gas condensate	K
petroleum and heavy oil with a maximum viscosity of 89 cSt at 50 °C	P
heavy oil with a maximum viscosity of 59 cSt at 80 °C (example: M40)	D
heavy oil with a maximum viscosity of 1500 cSt at 50 °C (example: M100 and higher)	H

To select a dual-fuel burner, simply enter the appropriate letters in the model.

In the case of single-fuel burners, there is no second letter and a dash is written instead.

### Example 1

Dual fuel burner type HTP93A model MG.MD.S.GB.A.1.65 firing with natural gas (M) and light oil (G). If you want to choose the same burner but for LPG and light oil, replace the letter M (natural gas) with L (LPG). Then the burner will still be type HTP93A, but the model will change to LG.MD.S.GB.A.1.65

### Example 2

Requires a TG90 model G.-PR.S.GB.A with kerosene fuel (K) instead of light oil (G). The burner type remains unchanged TG90; only the model K.-PR.S.GB.A will change

# TYPES OF FUEL

## GAS BURNERS

Gas burners can be operated with different gas types, burner regulation and valves. Combustion head and other components may vary depending on the selected type of fuel. When ordering, it is necessary to specify the selected fuel; check the price list for the extra charge of the required variants.

Attention: if the customer needs to modify an existing burner because he wants to convert it to a different fuel, this operation might require substantial modifications to the components of the burner, not to mention a new adjustment of the combustion.

In such cases, it is advisable to contact our sales network, which will provide assistance in selecting a solution that meets client's requests.

## LPG

LPG is a mixture of hydrocarbons, consisting mainly of propane and butane. It is stored in liquid form, it is supplied to the burner through an evaporator, which supplies the liquefied gas to the burner in gaseous form. Given its high calorific value, these burners usually require a lower inlet pressure than for natural gas, and because of this with LPG a smaller diameter gas valve is possible although the outputs of natural gas and LPG burners are identical. Read the instructions to familiarise yourself with details.

## Biogas

Biogas consists of a mixture of different types of gases (mainly Natural gas) from the fermentation of organic animal and vegetable waste products. It is characterised by the fact that its calorific value is lower than that of natural gas, which means that, on an equal output, a higher gas pressure and larger gas valves diameter are required. In case of very low calorific value gas, biogas can be mixed with natural gas or other hydrocarbons in order to increase the calorific value.

Very often biogas undergoes a dehydration process due to the water vapour content. In addition, biogas contains sulphur compounds which form an acidic condensate at a certain humidity and temperature. As there is a certain risk of damage to the critical safety components such as valves, regulators, and other gas appliances, manufacturers are not willing to take the risk and set limit values for the gas mixtures (e.g. total absence of H<sub>2</sub>S and similar compounds). It is necessary to pay special attention to the selection of valves, gaskets and leakage control units. In addition, the biogas composition must be kept as constant as possible in order to ensure the correct quantity of combustion air, and for the safety of combustion.

## Syngas

Syngas is a mixture obtained usually from the gasification of coal or biomass. It may contain, in varying proportions, hydrogen (H<sub>2</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and others.

If syngas is used as fuel, fuel analyses must be submitted together with other technical specifications of the plant. Depending on the syngas components content, special modifications may be necessary to valves, since syngas can cause corrosion and contains water. In addition, since its heating value is lower than that of standard natural gas, a considerably higher inlet pressure will be required to produce the same output. In any case, we recommend that you contact our technical experts to check correct selection of the burner.

## Synthetic Natural Gas (SNG)

Synthetic natural gas is a substitute for conventional natural gas and should not be confused with it although their names looks very similar, because they are actually two completely different things.

The substitute for natural gas (SNG) is produced in such a way that it results in the same number of Wobbe as natural gas (approx. 55 MJ/m<sup>3</sup>), which means that it is interchangeable with natural natural gas.

For example, it is possible to take a 44 % / 56 % mixture of air and butane, or a mixture of air and propane in proportions of 32 % / 68 % - in both cases the Wobbe number will be 54,76 MJ/m<sup>3</sup>, so it is possible to use a burner with the very same valves and supply pressure as for natural gas.

However, in this case, it is also recommended that a fuel analyses is submitted for preliminary check before the selection is made.

Note that synthetic natural gas should also not be confused with liquefied natural gas, LNG.

In order to facilitate the selection of the optimum configuration, it is advisable to send the fuel analysis to our TECHNOLOGY INFORMATIONS. The following basic parameters require clarification:

- Gas or mixture composition
- Density under standard conditions
- Lower heating value
- Alternatively Wobbe Index.

And, of course, the available inlet pressure at customer's site!

Note: it must be remembered that in case of gases with a very low calorific value, it is possible to correct this parameter by mixing it with natural gas, propane or other hydrocarbons.

## **LIGHT OIL BURNERS**

Light oil burners can basically also be used for other liquid fuels such as, biodiesel, kerosene and arctic diesel fuel. However fuels such as kerosene, arctic diesel and gas condensate have a technological impact in the application of standard burners. Above all they have a low viscosity, a feature that affects the flow characteristics of pumps and nozzles; the customer must specify the type of fuel he wants to use before ordering. Furthermore, kerosene and gas condensate have a low lubricity value, so that the surfaces of the moving parts are subject to friction and abrasion. The lubricating film formed by the fuel is of great importance in order to reduce the friction between the gears, and Therefore, to guarantee the longevity of the pump. Normally the standard recommends a lubricating capacity of not more than 460 µm at 60 °C.

This parameter can be corrected by using additives or by mixing the fuel with light oil.

### **Biodiesel, vegetable oils or animal fats**

These oils are agricultural products of different origins (like rapeseed oil).

These oils may contain impurities (husks, fibres) and must therefore be carefully filtered. In general, diesel burners are usually also suitable for biodiesel, but under the condition that the characteristics such as viscosity, density and calorific value are identical.

Particular attention must be paid to the acidity value of the fuel, which depends on the amount of fatty acids present in the organic raw material. Normally, the acidity value should be below 15 mg KOH/g, as standard recommends.

### **Heating oil**

A very common and relatively cheap fuel, with intermediate characteristics between light oil fuel and light heavy oil.

Compared to light oil, it has a higher viscosity and may contain a higher percentage of sulphur.

Generally, it can be used with light oil burners, where the viscosity of heating oil is less than 8 cSt at 20°C.

Furthermore, the heating oil must be supplied to the burner at a temperature of at least + 10 °C.

If the viscosity is higher, it is advisable to use an oil burner (see the following paragraph).

A similar choice is made if the fuel cannot be heated before it is supplied to the burner: pay attention to winter conditions.

# **TYPES OF FUEL**

## **HEAVY OIL BURNERS**

Heavy oils are used in a wide range of applications, e.g. in oil extraction and refinery plants.

Heavy oil is relatively cheap compared to other refined hydrocarbons, however it requires a number of treatments before it can be pumped and burnt in traditional boiler plant. Correct operation of a burner depends entirely on the availability of the following devices and the execution of the operations described below.

- fuel sedimentation tank: the main tank is separated by pumps and filters from the service tank a circular fuel supply line to the burners. This way the fuel is separated from impurities, clay, water and possible paraffin.
- cascade filtration system: one filter is not enough, due to the number and different sizes of impurities present in the fuel oil.

The typical example is a cascade of filters connected in series, with filter cells of 1 mm, 500 µm, 250 µm, 125 µm; a cascade filtration system is not sufficient.

Filter cells of 1 mm, 500 µm, 250 µm, 125 µm; the filters must be cleaned frequently. In many cases, the filters must also be heated with additional resistors; in case of higher metal contents (e.g. in used oil), additional electromagnetic filters should be used.

- Heavy oil preheating: increased viscosity is a technological limitation for pumping stations. The heavy oil must be heated to a temperature sufficient to lower the viscosity to the limits of its delivery capability in order to be supplied to pumps. Normally, crude oil and light heavy oil (bunker fuel oil) are heated to a temperature of 40÷60 °C. In comparison, heavy fuel oils such as M100, must be reheated to 80÷100 °C before being supplied to the burner. Preheating may be achieved by means of heat exchangers or directly in the tank, using steam, hot water, electric heaters or other means.

- Heating cable bundling: all components of the fuel oil supply system should be bundled with heating cable thermally insulated, to ensure fast heating of oil, even after a long period of stand-by time; otherwise the pump will be subjected to start-up stress and switching on the burner will be very difficult or even impossible. Similarly, filters, valves, regulators must be equipped with auxiliary electric resistors and thermostats.

Heavy oil should, as far as possible, be free from water, which can damage pumps, and from paraffin which clogs the burner nozzles. It is advisable to suck heavy oil avoiding contact with the bottom of the tank where all dirt is accumulated.

- It is also necessary to avoid to overheat the fuel, mainly to avoid boiling it. The formation of gas bubbles in the piping system may cause damage to the pumps (cavitation) and may lead to a loss of flame, to a sudden stop of the motor and heavy oil system, followed by sudden shut-down of the burner. Another negative effect of overheating is coking of the fuel. At high temperature, asphaltenes (one of the many hydrocarbons contained in crude oil) react with paraffins to form hard agglomerates which deposit on the surface of the heat exchanger, causing possible hazardous conditions.

- Fuel supply pressure: the pump delivered with the burner must be powered at the minimum pressure defined by the manufacturer. It determines the allowable load loss, the length and diameter of the pipes and position of the tank. Find the NPSHR values in the operating instruction manual supplied along with the pumps.

If the fuel oil is handled properly, the fuel oil pump can operate reliably and efficiently for many years. So it is advisable to rely on the experience of qualified specialists, who are able to design the fuel supply system according to the rules of good technique.

Also, in the case of oil burners, at the ordering stage, it is recommended to provide fuel analyses to our Technical Department. This applies especially to crude oil and other heavy fuels with variable composition. The main parameters that need to be clarified are:

- the composition of the liquid fuel or mixture
- kinematic viscosity
- density under standard conditions
- calorific value
- acidity (vegetable oils)
- lubricity (paraffin, gas condensate)

And, of course, pressure and temperature at the fuel supply of the customer plant!

## Oil

Crude oil can be classified as follows.

Crude oil: A natural liquid fossil mixture of hydrocarbons with a wide physical and chemical composition, for the production of liquid fuels (gasoline, paraffin, diesel fuel, fuel oil), lubricating oils, bitumen and coke.

Marketable oil: oil prepared for delivery to consumers in accordance with the requirements of applicable normative and technical documents adopted in due course.

There is a significant difference in the use of these varieties of oils because many of the substances in the crude oil are aggressive. If they are present in significant quantities, then they interfere with the proper operation of the burner and may cause damage to the system.

## FUEL ATOMISATION

Liquid fuels are burnt by atomising them into microscopic droplets using nozzles.

The droplets quickly evaporate in the combustion chamber and the steam feeds the flame. Atomisation can take place by means of high-pressure mechanical nozzles (as on light oil or commercial heavy oil burners), or by pneumatic nozzles working at medium pressure, in case of very heavy liquid fuels. Pneumatic atomisation of fuel occurs due to the pressure of the atomisation means (compressed air, and/or steam) which is injected directly into the fuel oil stream and atomizes it to form an air-fuel mixture.

This choice during the project phase, allows for maximum flexibility in the use of all types of fuels whether in case of heavy fuel oil (M40, M100), crude oil, heating oil, bunker oil (F5, F12) or other liquid fuels. CIB UNIGAS burners provide the right degree of atomization, necessary for a complete and efficient combustion. Burners with pneumatic atomisation fuel are distinguished by the letter "H" in the model name, and are obligatory when the client chooses such high viscosity fuels burners (more than 1500 cSt at 50 °C), or highly polluted oils (e.g. used oil).

It is recommended to use steam for fuel atomisation. If the customer prefers to use compressed air, see recommendations for compressor selection (page 231).

### Please note that:

CIB UNIGAS does not provide any warranty for burners and components in the event that fuels do not comply with the specifications required by the standards. The use of substandard fuels may cause long-term damage to the burner and the whole system, thus reducing the equipment lifetime.

# HEAVY OIL HEATING

The TN, KTP, TPBY and KTPBY burner series are designed for heavy oil that can be used both as the main fuel, and as a reserve fuel.

The heavy oil must be supplied to the burner at a temperature sufficient for atomisation at the nozzle (example: 120÷130 °C). The higher the viscosity of the fuel, the higher will be the temperature required for heavy oil.

In a modern boiler room there is usually a service heavy oil tank, which is supplied by a low pressure fuel circuit (aka "ring"). In this circuit the heavy oil is maintained at a minimum temperature required for the discharge (example: 80°C).

This means that the heavy oil must be heated up before it reaches the burner.

The standard delivery of the burner does not include a fuel preheating station, but it is available as an optional.

The standard heavy oil heating station includes a heavy oil/steam heat exchanger mounted on a separate frame. As an alternative to steam, diathermic oil can also be used.

If the required oil flow rate is too high, several heat exchangers can be connected in parallel in order to create the required heat. For example, it is possible to supply two or more burners with just one heavy oil pre-heating station.




Example: Heavy oil heating station


To order a complete heavy oil heating station, it is necessary to specify:

1. Type of fuel to be heated (example: heavy oil M100)
2. The flow rate to be heated (or which and how many burners are to be powered, example: TBY1040 - 2 pcs.)
3. Input oil temperature and pressure (example: 80° C, 5 bar)
4. Heating means used (example: steam) and its characteristics (temperature, pressure, available flow rate).

**Fig. 01 - Heavy oil preheating station (example with one heat exchanger)**



**Fig. 02 - Heavy oil preheating station (example with 3 parallel heat exchangers)**



#### LEGEND

1	Air regulator	7	Ball valve (steam)
2	Thermostat	8	Condensation chamber
3	Manual ball valve	9	Flow indicator
4	Filter (steam)	10	Manual ball valve
5	Metering valve (steam)	11	Anti-vacuum valve
6	Manual ball valve	12	Tank - heat exchanger (fuel oil/steam)

Heavy oil components, flanged; steam components: PN16

#### Application of electric heaters for heavy oil heating

It is possible to assemble a heavy oil preheating station equipped with electric heaters by integrating or replacing the steam heat exchanger.

Attention: in this case the electrical power required is typically very high!

For comparison, let's take a fuel oil flow rate of 4000 kg/h, the required thermal step is 50 °C: under these conditions, the minimum power requirement is 120 kW. Larger size burners require, proportionally, higher outputs. Therefore, in case the customer decides to incorporate a fuel heating station with electrical heaters into the project, we recommend to evaluate this solution in cooperation with the technical department of CIB UNIGAS.

We will help you to choose the configuration that meets your needs.

## HEAVY OIL HEATING

In addition to the exchangers shown on the previous pages, it is possible to provide fuel storage tanks. The heavy storage tanks can also be equipped with water coils, steam coils or electrical heaters. These tanks are designed for low pressure ring heavy oil circuits.



# LIGHT OIL BURNERS

The light oil burners are equipped with a lance with nozzle. The nozzle operates with mechanical atomisation of fuel at high pressure (25 bar). Delivery includes filter, pump, regulator, safety valves, minimum pressure switch, pressure gauge.


The pump can be driven by a fan motor or a separate motor, depending on the burner models. In addition, separate connection hoses are available. See hydraulic diagrams.

The light oil fuel must be supplied to the burner at a pressure of 1÷2 bar and a temperature not lower than 5 °C.


The burner can be supplied from a tank in a straight line or from a low pressure fuel ring (which is preferable when several burners are working in one boiler room).

Attention: the low pressure fuel ring is not included in the standard delivery of the burner, but it is available as optional (see page 247).

**Fig. 01 - Light oil fuel feeding diagram: example for TG, HTP, HTLX series single-head burners (< 3 MW)**



**Fig. 02 - Light oil fuel feeding diagram: example for TG, HTP, HTLX series single-head burners (≥ 3 MW)**



## LEGEND

1	Manual ball valve	7	Maximum pressure switch	13	Servomotor
2	Light oil filter	8	3-way valve	14	Manometer
3	Pump and motor	9	Burner	15	Electrovalve
4	Pressure regulator	10	Manometer ball valve (option)	16	Combustion head
5	Hose	11	Manometer (option)		
6	Check valve	12	Flow regulator		

# LIGHT OIL BURNERS

Fig. 01 - Light oil unit of TG, HTP VS series (output < 3 MW)

COMPONENTS INTEGRATED INTO THE BURNER





Fig. 02 - Light oil unit of TG, HTP VS series (output ≥ 3 MW)

COMPONENTS INTEGRATED INTO THE BURNER




## LEGEND

1	Manual ball valve	8	3-way valve	14	Manometer
2	Light oil filter	9	Burner	15	Solenoid valve
3	Pump and motor	10	Manometer with manual ball valve (option)	16	Combustion head
4	Flow regulator	11	Manometer (option)		
5	Hose	12	Pressure regulator		
6	Check valve	13	Servomotor		
7	Maximum pressure switch				

Note: on some models the flow control valve can be integrated into the pump housing.

# BURNERS WITH FREE-STANDING LIGHT OIL

LIGHT OIL UNIT - Maximum dimensions of pump and fuel group



Burner size	Pump motor	A	H	B
up to 520	< 4 kW	790 mm	600 mm	620 mm
from 525	≥ 4 kW	990 mm	700 mm	670 mm

CIB Unigas light oil burners are also suitable for fuels that are not widely used, such as: arctic diesel, paraffin, gas condensate, biodiesel. However the characteristics of unconventional fossils fuels are very different, and therefore a technical evaluation must be carried out to assess their suitability.

In order to select a special burner suitable to your requirements, it is advisable to provide a fuel analysis.



# HEAVY OIL BURNERS

Heavy oil burners are divided into two main categories.

## TN, KTP series

These models are equipped with a lance and by-pass nozzle. The nozzle works with mechanical spraying at high pressure (25 bar). Delivery includes filter, pump, regulator, valves, thermostats.

One or two fuel preheater tanks, fitted with electrical resistors, can be found aboard the burner.

The pump may be driven by an impellor motor or a separate motor, depending on burner model. In addition, two connection hoses are available separately.

Please find below hydraulic diagrams.

## TPBY, KTPBY series

These models are equipped with a lance and pneumatic spraying nozzle.

Atomisation is carried out with compressed air or steam.

The delivery includes pressure relief valves, regulator and heavy oil pre-heaters

In addition, a compressed air circuit is also available (steam versions on request). Also included filter and hose connections for burner.

Note: the pressure pump (10 bar) connected to the electric motor is included only on request. See price list for details.

Note: a compressor is not included in the delivery of the burners.

For selection of a suitable compressor, see page 231.

The heavy oil must be supplied to the burner at 1÷2 bar.

The minimum temperature at the pump depends on the viscosity of the liquid fuel: for example in case of fuel oil M100, a supply temperature of 80÷100 °C is recommended, while temperature may be lowered in the case of crude oil.


The burner can be supplied directly from the tank in a straight line or through a low-pressure fuel ring (preferable when several burners are operating within the same boiler room).

Attention: a ring fuel circuit for multiple burners is not included as standard in the burner delivery, but can be ordered separately (see page 247).

## Pumps for TPBY, KTPBY pneumatic atomised burners

Burner size	Pump	Flow	Motor (power)	Motor (speed)	Connections dimensions	Max. Pressure (outlet)	Max Pressure (inlet)	Item number
90-91	KF-10.BCB	500 l/h	0,37 kW	1500 rpm	DN25	10 bar	2 bar	2590606
92-93-510-512	KF-15.BCB	800 l/h	0,55 kW	1500 rpm	DN25	10 bar	2 bar	2590612
515-520-525	KF-20.BCB	1100 l/h	0,55 kW	1500 rpm	DN25	10 bar	2 bar	2590610
1025-1030-1040-2050	KF-32.BCB	1800 l/h	1,10 kW	1500 rpm	DN32	10 bar	2 bar	2590613
2060-2080	KF-42.BCB	2400 l/h	1,10 kW	1500 rpm	DN32	10 bar	2 bar	2590615

Fig. 01 - Scheme for heavy fuel oil: example with TN, KTP series single-head burners



#### LEGEND

1		Oil filter	18		Electro-valve
2		Pump and motor	19		Minimal pressure switch
3		Heavy oil hose	20		Check valve
4		Manometer ball valve (option)	21		Flow regulator
5		Manometer (option)	22		Manometer ball valve
6		Safety valve	23		Manometer
7		Manual ball valve	24		Hose
8		Safety thermostat	25		Hand-operated steam tap (optional)
9		Minimal temperature thermostat	26		Steam filter (optional)
10		Maximum thermostat	27		Minimum pressure switch (Option)
11		Heating tank	28		Condensation separator (Option)
12		Pneumatic valve	29		Pneumatic valve (optional)
13		Flow regulator	30		Nonreturn valve (Option)
14		Servomotor	31		Condensate drain (Option)
15		3-way valve	32		Flow indicator (Option)
16		Combustion head	33		Pressure regulator
Pb		Temperature sensor (1, 3, 4)	34		Burner
17		Stabilisation filter	35		Pressure regulator

All oil components are flanged; all steam components are designed for PN16 pressure.

On customer's request it is possible to supply a pump mounted on a separate frame with a junction box and a collecting tray for

On customer's request we can deliver a pump mounted on a separate frame and equipped with a junction box and a collecting tray for heavy oil.

# BURNERS WITH FREE-STANDING HEAVY OIL

Burners with separate heavy oil (series TPBY, KTPBY) are equipped with lance and nozzle for pneumatic atomization of fuel. Atomisation of fuel is carried out with compressed air or alternatively with steam (optional). Delivery includes valves and fuel preheating tanks integrated into the burner, compressed air circuit, low pressure pump connected to an electric motor, filter and regulator. Pump, filter and hoses connected to the burner are delivered separately.

Refer to C.01÷04 for the complete diagram of the components included in the delivery.

Heavy fuel oil must be supplied to the burner at 1÷4 bar; the minimum temperature of pump depends on the viscosity of heavy fuel oil: e.g. in case of heavy fuel oil M100 oil, for example, a temperature of 80÷100 °C is recommended, while temperature may be lowered in the case of crude oil.

The burner can be supplied from a tank directly or by a return flow circuit (preferably when several burners are in operation in the same boiler room).

Attention: A ring fuel circuit for several burners is not included in the standard delivery of the burner, but can be ordered separately (see page 247).

Fig. 01 - Heavy oil unit for TPBY, KTPBY series, single-head burners (output < 10 MW)




Fig. 02 - Heavy oil for TPBY, KTPBY VS series burners (output < 10 MW)

COMPONENTS INTEGRATED INTO THE BURNER





Fig. 03 - Heavy oil for TPBY, KTPBY series burners, single-head burners (output ≥ 10 MW)


COMPONENTS INTEGRATED INTO THE BURNER



# BURNERS WITH FREE-STANDING HEAVY OIL

Fig. 04 - Heavy oil for TPBY, KTPBY VS series burners (output ≥ 10 MW)

## COMPONENTS INTEGRATED INTO THE BURNER



## LEGEND

1 Oil filter	12 Thermometer	23 Manometer
2 Pump and motor	13 Pneumatic valve	24 Hose
3 Fuel oil hose	14 Servo actuator	25 Hand-operated steam tap (optional)
4 Manometer holder cock	15 Flow regulator	26 Steam filter (optional)
5 Manometer	16 Combustion head	27 Minimum pressure switch (Option)
6 Safety valve	17 Stabiliser filter	28 Condensation separator (Option)
7 Manual cock	18 Electro-valve	29 Pneumatic valve (optional)
8 Safety thermostat	19 Minimal pressure switch	30 Nonreturn valve (Option)
9 Minimal temperature thermostat	20 Check valve	31 Condensate drain (Option)
10 Maximum temperature thermostat	21 Flow regulator	32 Flow indicator (Option)
11 Heating tank	22 Manometer holder-cock	

If oil components are flanged; all steam components are designed for PN16 pressure.

Upon customer's request it is possible to supply a pump mounted on a separate frame equipped with a junction box and a collecting tray for fuel oil.

Attention: the compressor is not included in the burner delivery.

See page 231 for selection of a suitable compressor.

To order a burner with pneumatic atomization of fuel by means of steam, it is necessary to add an extra charge to the price of the standard burner.

# OIL BURNERS

The standard scope of supply of oil burners include two flexible low-pressure hoses, filter, (supplied separately), pump, nozzle and combustion head, flow pressure regulator and shut-off valves.

The pressure gauges and other accessories can be ordered separately upon customer's request.

This table includes all burner configurations according to burner type, size and fuel.

Pressure pump unit (configurations):

1. Fuel pump
2. Pump integrated into the burner, connected to the motor (Suntec)
3. Motor and pump supplied separately - optional (Kral)
4. Group consisting of motor and pump mounted on a separate frame (Suntec)

More detailed information can be found in the operating instruction manual.

Series	Fuel	Filter	Configuration of oil pump and pump unit configuration			Tanks-heaters fuel oil heaters	Hoses low pressure
			1	2	3		
Burners with mechanical atomisation							
TG 90 - 500 - 1000 - 2000 - 3000	Light oil		■	■	●		■ ●
HTP HTLX TECNOPRESS 90 - 500 - 1000 - 2000 - 3000	Natural gas/Light oil		■	■	●		■ ●
Burners with mechanical atomisation							
TN 90 - 500 - 1000 - 2000 - 3000	Heavy oil		■	■	●	■	■ ●
KTP 90 - 500 - 1000 - 2000 - 3000	Natural gas/ Heavy oil		■			■	■ ■
Burners with pneumatic atomisation							
TPBY	Heavy oil		■	■		■	■
KTPBY	Natural gas/ Heavy oil		■	■		■	■
				pressure max. 10 bar		pressure max. 30 bar	


■ = what is supplied with the burner

● = equipment as requested by the customer


# LOW PRESSURE OIL HANDLING UNITS WITH SERVICE TANK

Very often, for a correct light and heavy oil burners operation, it is necessary to prepare an additional fuel supply line. In this case, rather than sucking the fuel from the tank through separate pipes suitable to each individual burner, a low-pressure supply circuit (normally 1 ÷ 2 bar) must be created. Two of the most common fuel oil configurations are simplified in the following diagrams.

**Fig. 01 - Example of a ring circuit for heavy fuel oil burners with mechanical atomization**



**Fig. 02 - Example of a ring circuit for heavy fuel oil burners with pneumatic atomization**



Below is a description, as an example, of some available solutions for oil preheating fuel supply to the burner. The daily storage service tank (no. 1 in the figure) is heated by a service boiler (no. 7) with a steam or hot water boiler. The target is to keep the heavy fuel oil liquid enough to keep the necessary pressure inside the ring circuit. The capacity of the service tank (no. 3) provides, if necessary, an additional temperature difference before supplying the oil to the burner (no. 5). The burners themselves are supplied through degassing tanks (no. 4), which separate the gas which forms in the heated oil.

On the back, below item no. 6, there's a pressure regulator.

CIB UNGAS can supply, upon request, pumping units for light and heavy fuel oil, pressure regulators and degassing tanks.

# FLAME CONTROL SENSORS

In order to ensure a safe ignition, the technical regulations require that all burners are provided with a flame detection sensor. The sensor sends a signal to the electronic flame control unit and if it fails, the control box immediately shuts off the valves, and stop burner operation. This is necessary to prevent unburned fuel from entering the combustion chamber, with possible risk of explosion.

Flame control sensors used on industrial burners fall into two main categories:

- Sensors that detect the intensity of gas ionisation. The flame is nothing more than a partially ionised gas, so by means of a potential difference it is possible to measure the intensity of ionisation using an electrode.
- Sensors measure electromagnetic radiation striking them, i.e. the photons produced by chemical reactions during the combustion process.

These sensors can be subdivided into models which detect flames in the infrared, visible or ultraviolet spectrum. In this category of sensors there are conventional photoelectric cells and sensors with photoresistors.

Photoresistors and photocells are semiconductor electronic components. The difference between them is in the way they detect the presence of a flame:

- A photocell uses the photoelectric effect to generate a current. The current signal is amplified and then read out by the electronic flame control unit of the burner. This is an active sensor type.
- The photoresistor is a component whose electrical resistance is inversely proportional to the amount of light striking it. In other words, its value in ohms ( $\Omega$ ), due to the effect of photoconductivity, decreases as the intensity of the incident light increases. At a constant voltage, the current flowing through the sensor is proportional to the intensity of the light source. It is a passive sensor.

The use of a flame control sensor of one type or another depends mainly on the geometric shape of the combustion head and the characteristics of the flame it monitors (its temperature and brightness), because, depending on the type of fuel used, the flame will be either more or less bright in certain ranges of the electromagnetic frequency spectrum.

Albeit to a lesser extent, the combustion chamber can also influence the choice of flame control sensor. For example, if the combustion chamber is made of refractory bricks, it can emit a false flame signal in the infrared spectrum, in this case, instead of the infrared sensor, you can choose either an ultraviolet sensor or an ionisation sensor.

The standard CIB UNIGAS burners are equipped with the sensors shown in the following table:

BURNERS	FUEL TYPES	FLAME CONTROL SENSORS		
		electrode ionisation	photocell	photoresistor
TECNOPRESS - 90 - 500	Natural gas	●	○	
1000 - 2000 - N	Natural gas	●	●	
C, E Series	Natural gas	●	△	
90 - 500 - 1000 - 2000	Natural gas		●	
90 - 500 - 1000 - 2000 - 3000	Dual fuel gas/light oil or combined gas/heavy oil		●	
C, E Series	Dual fuel gas/light oil		●	
TECNOPRESS - 90 - 500 - 1000 - 2000 - 3000	Light oil or heavy oil		△	●

## Legend

- Series burners
- Available on request
- △ Models with LMV5x

Models with ignition burner and photocell: see pag. 152

# SEPARATE ELECTRICAL PANELS FOR BURNERS

Standard burners are provided with integrated electrical panels which include all electronic automation and all necessary components for a correct and reliable operation.

Alternative solutions to the integrated control panel are available upon request:

- Wall mounted control panel according to customers' specifications.
- Floor standing electrical panel; it has its base, and it is provided with a tilting panel.
- Large electrical panel with base plate (Closet type); this type of panel allows to mount an inverter or other necessary electronical equipment.

All electrical panels are provided with a door lock.



Floor standing

Maximum dimensions			
Electrical panel type	width [mm]	depth [mm]	height [mm]
<b>Floor standing</b>	600 - 1000	500	1000
<b>Closet type</b>	600	400	2000
<b>Wall mounted</b>	400 - 600	200 - 300	600 - 700

Protection degree of self-supporting switchboards: IP55 (or higher upon request)

The dimensions indicated are valid for the configurations widely used in boiler rooms.

Based on the specifications of the heating system, it is possible to produce electrical panels of different sizes, or to prepare a common one to serve many burners.

Note: If you select the option "control cabinet type", you need to specify the cable entry position (cable entry from the bottom or top of the electrical panel housing).

Note: Some combinations have restrictions on the passage of signals from and to the outside to electronical equipment. To order a special electrical cabinet, the length of the electrical connections between the panel and the burner must be ascertained in advance.

For burners with a special configuration, please ask our Technical Department.



Closet type



Wall mounted

# COMPRESSORS FOR BURNERS WITH PNEUMATIC ATOMISATION

- Consider the data on the table here below as a guide to select a suitable compressor in case air is to be used for the atomisation of heavy fuel oil.
- The compressor can be supplied separately from the burner, compressors are out of our standard scope of supply.
- The air parameters are taken at standard conditions (temperature 15 °C and pressure 1.013 mbar).

If steam is used to atomise fuels, the pressure and flow rate are identical to that of compressed air. The steam must be dry saturated. Steam pressure must never exceed 12 bar (190 °C).

Attention: burners with separate fans, with pneumatic atomisation of fuel are by default designed for the use with compressed air. In case an alternative configuration (e.g. with steam) is needed, it is necessary to add an extra charge to burner price.

Burner type	Power [kW]	Air/steam flow rate [kg/h]	[St l/s]	Pressure [bar]
TPBY90	2.000	21,5	4,8	6÷8
TPBY91	2.500	26,9	6,0	6÷8
TPBY92	3.000	32,3	7,2	6÷8
TPBY93	3.700	39,8	8,9	6÷8
TPBY510	5.000	53,8	12,0	6÷8
TPBY515	6.000	64,5	14,3	6÷8
TPBY520	7.000	75,3	16,7	6÷8
TPBY525	9.750	104,7	23,3	6÷8
TPBY1030	13.300	142,9	31,7	6÷8
TPBY1050	15.500	166,6	37,0	6÷8
TPBY1080	19.000	204,2	45,4	6÷8
TPBY2000	22.000	236,4	52,3	8÷10
TPBY2500	27.000	290,1	64,5	8÷10
TPBY3000	39.000	419,1	93,1	8÷10
TPBY93 ...VS	3.700	37,8	8,9	6÷8
TPBY515 ...VS	6.000	64,5	14,3	6÷8
TPBY525 ...VS	9.750	104,7	23,3	6÷8
TPBY1030 ...VS	13.300	142,9	31,7	6÷8
TPBY1080 ...VS	19.000	204,2	45,4	6÷8

# COMPRESSORS FOR BURNERS WITH PNEUMATIC ATOMISATION

Burner type	Power [kW]	Air/steam flow rate [kg/h]	Air/steam flow rate [St l/s]	Pressure [bar]
KTPBY90	2.300	24,7	5,5	6÷8
KTPBY91	2.670	28,6	6,3	6÷8
KTPBY92	3.050	32,7	7,2	6÷8
KTPBY93	4.100	44,0	9,7	6÷8
KTPBY512	4.500	48,3	10,7	6÷8
KTPBY515	5.200	55,8	12,4	6÷8
KTPBY520	6.400	68,7	15,2	6÷8
KTPBY525	9.750	104,7	23,3	6÷8
KTPBY1030	13.300	142,9	31,7	6÷8
KTPBY1050	15.500	166,6	37,0	6÷8
KTPBY1080	19.000	204,2	45,4	6÷8
KTPBY2000	22.000	236,4	52,3	8÷10
KTPBY2500	27.000	290,1	64,5	8÷10
KTPBY3000	39.000	419,1	93,1	8÷10
KTPBY93 ...VS	3.023	32,4	7,2	6÷8
KTPBY515 ...VS	4.900	52,6	11,7	6÷8
KTPBY525 ...VS	7.600	81,6	18,1	6÷8
KTPBY1030 ...VS	12.100	130,0	28,9	6÷8
KTPBY1080 ...VS	19.000	204,2	45,4	6÷8




## ACCESSORIES

Accessories for gas, light oil or heavy fuel oil can be ordered together with the burners (see from pag. 236 to 244).

These accessories include:

- Modulation probe
- Spacer parts for fitting head
- Counter-flanges
- Leakage control
- Max. gas pressure switches
- Gas pressure regulators
- Regulators with filter for burner pilot
- Manual gas ball valve (screwed or flanged)
- Anti-vibration joint (screwed or flanged)
- Gas filters (up to 2 or 6 bar pressure)
- Gas pressure gauges
- Manual light oil ball valve for heating oil (screwed or flanged)
- Reinforced hoses for light oil, fuel oil
- Filters for light oil, fuel oil (screwed or flanged)
- Manometers for light oil, fuel oil
- Manometer holders for gauges
- Manometers-pressure gauges
- Heating cables (self-regulating) for fuel oil piping

To order accessories use the price list.



## COUNTERFLANGE SELECTION

The length of burner firing head is selected according to the rules laid down by the boiler manufacturers. For each boiler model, the designer recommends the precise firing head length (or min/max range) to adapt it to the thickness of the front wall or geometric shape of the combustion space.

In the absence of such indications, recommendations for good technique can be followed based on experience.

- Boilers with reverse combustion chamber (2 pass boilers): it is recommended to use a head of sufficient length to fit inside the combustion chamber by 50÷100 mm from the flue gas reversing chamber (class 3 low NO<sub>x</sub> burners: 150÷200 mm).
- 3-pass boilers: it is recommended to use a head of sufficient length to fit 50÷100 mm inside the combustion chamber (class 3 low NO<sub>x</sub> burners: 150÷200 mm).
- ovens and especially short combustion chambers with refractory lining: it is advisable to use a head that fits inside the combustion chamber with a blast tube entering the combustion chamber by no more than 20÷100 mm.

For non-standard heat generators or combustion chambers, CIB UNIGAS is always ready to examine equipment specifications in order to find a solution to satisfy any Customer's request.

Note: in rare cases where the available firing head length do not meet the required dimensions, it is possible to manufacture mid-length firing head to customer's specifications, or to fit a spacer between the burner flange and the boiler/furnace front.

Details about spacers can be found in the price list and catalogue for burners and accessories.

Regarding the execution of the hole on the front wall of the boiler, the catalogue tables indicate the diameters of the holes (H) and the position of the stud holes for fixing the burners.

In some cases, the diameter of the head (G) is wider than the diameter of the recommended hole (H). In these cases the following steps can be taken:

- Boilers or heat generators with a front door that opens: it is possible to make an opening hole with a reduced diameter, and then fit the head from the inside. Or, alternatively, drill a larger diameter hole, but then insert a counter flange.
- For boilers and heat generators that do not have an opening front door, the use of counter flange is mandatory.

The firing head for which the specified procedure is required are annotated in the dimension tables. If a counter flange is needed, the customer can have one taylor made, or use one of the drawings provided on the following pages. Upon request the counter flange can be included in the scope of supply.


Attention: the real length of the firing head should be reduced by approx. 25 mm to reckon for the thickness of the counter-flange and gasket.

\* Ask our technical department for more information.


Series	Item number
HTP120A	24300BL
TECNOPRESS (HTP165A - HTP205A)	24300DF
NOVANTA	24300V2
CINQUECENTO	24300Z6
MILLE	24300N7
DUEMILA	(*)

(\*) Inquire at the technical department of the branch responsible for your distributor.

PART NUMBER 24300BL





PART NUMBER 24300DF





# COUNTERFLANGE SELECTION



PART NUMBER 24300V2



PART NUMBER 24300Z6



PART NUMBER 24300N7



# FREQUENCY INVERTER FOR BURNERS ELECTRONICALLY CONTROLLED

Burners with electronic control and a separate fan can be supplied with a motor directly actuated or, as an alternative, indirectly actuated, i.e. via frequency inverter (Variable Speed Drive, VSD).

In order to choose a burner equipped with a frequency inverter with electronic control: EI or EK; then choose the frequency inverter, based on capacity of the fan motor (see tables on this page).

For example: VSD for a 55 kW motor.

## Terms of delivery (2 options)

**The frequency inverter is supplied separately**, it is not factory installed in the control cabinet.

- The frequency inverter is supplied separately from the burner, with IP55 protection, equipped with a metal plate for fastening to the wall of the boiler room.
- Braking resistors are delivered separately (IP65)
- Electromagnetic filter (EMC) class A1/B, suitable for shielded cable lengths up to 20 m.

## Frequency inverter already built into the inside of the electrical cabinet

- IP20 frequency inverter built into the burner control cabinet (protection class IP55) protection class IP55
- Braking resistors (degree of protection IP65)
- EMC filter, class A1/B, suitable for shielded cables up to 20 m long
- In this configuration the cost of the frequency inverter also includes the difference cost of a larger panel enclosure; refer to page 230 for data sheet electrical panels.



FREQUENCY INVERTERS SUPPLIED SEPARATELY FROM THE BURNER	
	Motor power, kW
VSD	3,0
VSD	4,0
VSD	5,5
VSD	7,5
VSD	9,2 / 11,0
VSD	15,0
VSD	18,5
VSD	22,0
VSD	30,0
VSD	37,0
VSD	45,0
VSD	55,0
VSD	75,0
VSD	90,0
VSD	110,0
VSD	132,0
VSD	160,0

Note: Packaging is included in the delivery (the packages are blank wooden crates, suitable for truck transport).

Power supply to frequency converters: 400 V AC 3N 50 Hz.

Shielded cable is not included in the delivery. If the cable that connects the frequency Inverter to the fan motor must be longer than 20 m, please advise when ordering and require a higher EMC filter class.

Warning: Burners in EB, ED, EI, EK, EG, EP ER, LG, LR configuration can only be operated via a frequency inverter otherwise they will not work.

However, it is possible to purchase a burner that is set to work with the frequency inverter, but configured at the same time to work without it by means of delta/star start-up.

In this case the customer can decide whether or not to use a frequency inverter at a later stage, on the basis of the system requirements.

# GENERAL OPTIONS BURNERS

## PROBES FOR MODULATORS



Variable to be checked	Temperature/Pressure scale	Code
Temperature	-15 ÷ 50 °C	2.56.01.35
Temperature	30 ÷ 130 °C	2.56.01.C3
Temperature	0 ÷ 400 °C	2.56.01.45
Temperature	0 ÷ 1200 °C	2.56.01.42
Pressure	3 bar	2.56.01.C4
Pressure	10 bar	2.56.01.C5
Pressure	16 bar	2.56.01.C6
Pressure	25 bar	2.56.01.C7
Pressure	40 bar	2.56.01.C8
FGR Probe	-	2.56.01.77

## KIT for automatic fuel switch

Model	Code
MIXMATIC	-



## SPACERS

Height mm	Burner type	Code
70	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.20
100	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.21
135	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.22
150	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.23
180	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.24
220	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.25
250	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.26
300	TP 120A 165A 205A - HTP 120A 165A 205A - TLX 83 115 225 - HTLX 83 115 225	3.07.03.50
50	90 SERIES	3.07.03.27
100	90 SERIES	3.07.03.28
150	90 SERIES	3.07.03.29
200	90 SERIES	3.07.03.30
250	90 SERIES	3.07.03.31
300	90 SERIES	3.07.03.32
350	90 SERIES	3.07.03.33
100	500 SERIES	3.07.03.34
110	500 SERIES	3.07.03.35
150	500 SERIES	3.07.03.36
180	500 SERIES	3.07.03.37
200	500 SERIES	3.07.03.38
250	500 SERIES	3.07.03.39
275	500 SERIES	3.07.03.53
300	500 SERIES	3.07.03.41
350	500 SERIES	3.07.03.42
400	500 SERIES	3.07.03.57
450	500 SERIES	3.07.03.43
100	1000 SERIES	3.07.03.49
150	1000 SERIES	3.07.03.44
200	1000 SERIES	3.07.03.46
250	1000 SERIES	3.07.03.45
300	1000 SERIES	3.07.03.52
450	1000 SERIES	3.07.03.56
500	1000 SERIES	3.07.03.58
100	DUEMILA SERIES (2020)	3.07.03.55
150	DUEMILA SERIES (2020)	3.07.03.62
300	DUEMILA SERIES (2020)	3.07.03.61
200	DUEMILA SERIES (2030)	3.07.03.60
300	DUEMILA SERIES (2030)	3.07.03.61

# OPTIONS GAS BURNERS

## MANUAL CUT OFF VALVES, THREADED (ball valve)



Gas connections	Model	Code
1"1/4	V32	2.81.00.04
1"1/2	V40	2.81.00.05
2"	V50	2.81.00.06

## MANUAL CUT OFF VALVES, FLANGED (ball valve)



Gas connections	Model	Code
DN65	V65	2.81.00.12
DN80	V80	2.81.00.13
DN100	V100	2.81.00.14
DN125	V125	2.81.00.71
DN150	V150	ON REQUEST
DN200	V200	ON REQUEST



## ANTI VIBRATING JOINT (threaded)

Gas connections	Model	Code
1"1/4	GA32	2.34.00.80
1"1/2	GA40	2.34.00.65
2"	GA50	2.34.00.66



## ANTI VIBRATING JOINT (flanged)

Gas connections	Model	Code
DN65	GA65	2.34.00.81
DN80	GA80	2.34.00.82
DN100	GA100	2.34.00.83
DN125	GA125	2.34.00.70
DN150	GA150	ON REQUEST
DN200	GA200	ON REQUEST



## GAS FILTERS (max inlet pressure 2 bar)

Gas connections	Model	Code
1"	F25	2.09.01.15
1"1/2	F40	2.09.01.05
2"	F50	2.09.01.06



## GAS FILTERS (flanged: max inlet pressure 2 bar)

Gas connections	Model	Code
DN65	F65	2.09.01.17
DN80	F80	2.09.01.18
DN100	F100	2.09.01.20
DN125	F125	2.09.01.28
DN150	F150	ON REQUEST
DN200	F200	ON REQUEST



**PRESSURE GOVERNORS WITH GAS FILTERS (threaded: Pe max 1 bar)**

Gas connections	Model	Code
½"	S.P.15	2.80.00.85
¾"	S.P.20	2.80.00.94
1"	S.P.25	2.80.00.72
1½"	S.P.40	2.80.00.65
2"	S.P.50	2.80.00.67



**PRESSURE GOVERNORS WITH GAS FILTERS (flanged: Pe max 1bar)**

Gas connections	Model	Code
DN65	S.P.65	2.80.00.69
DN80	S.P.80	2.80.00.71
DN100	S.P.100	2.80.00.74



**MAXIMUM PRESSURE**

Description	Code
GAS MAXIMUM PRESSURE SWITCH KIT	2.19.12.41



**SUPPORT FOR PRESSURE GAUGE**

Model	Code
Push button valve	2810010



**MANOMETER**

Model	Code
Glycerine gauge 0 ÷ 60 mbar	2520001
Glycerine gauge 0 ÷ 400 mbar	2520028
Glycerine gauge 0 ÷ 1 bar	2520030

# OPTIONS GAS BURNERS

## GAS PRESSURE REDUCING STATIONS

Gas pressure reducing stations (available for inlet pressures up to 6 bar and max flow rate corresponding to an output of 20.000 kW).

Type	Power (kW)	Capacity (Nm <sup>3</sup> /h)	Burners*	Max pressure (bar)
GRG30	3000	320	TP92A	6
GRG130	13000	1370	TP1030A	6
GRG200	20000	2100	2 x TP525A	6

Gas pressure reducing station according to the below scheme

The station includes all the components as shown in the picture (see scheme and legend)


The station is pre-assembled on a frame

Packaging included

The stations are ready to work with natural gas, matching and sizes can vary according to the pressure and type of gas.

Max inlet pressure over 6 bar: price upon request

\*The burner in an example of a typical installation, however the same station can supply different burners of smaller size.



# OPTIONS LIGHT OIL BURNERS



## VACUUM GAUGE

Model	Code
Glycerine vacuum gauge -1 ÷ 0 bar (1/4" connection)	2520008



## FILTERS

Model	Code
Filter 1" 0,1 big	2090018
Filter 51000/25 - 2"	2090022



## MANOMETER

Model	Code
Glycerine gauge 0 ÷ 40 bar (1/4" connection)	2520003
Glycerine gauge 0 ÷ 6 bar (1/4" connection)	2520006
Glycerine gauge 0 ÷ 10 bar (1/4" connection)	2520015
Glycerine gauge 0 ÷ 16 bar (1/4" connection)	2520014
Glycerine gauge 0 ÷ 25 bar (1/4" connection)	2520027



## SUPPORT FOR PRESSURE GAUGE manometer/vacuum gauge

Model	Gas connections	Code
Isolating valve (1/4" connection)	1/4"	2520005

## PRESSURE REGULATORS FOR LIGHT/HEAVY OIL RINGS

### LIGHT OIL PRESSURE REGULATOR GROUPS

Type	Capacity kg/h	Diameter
GRP-G2	350	3/4"
GRP-G4	650	3/4"
GRP-G7	1.000	1"
GRP-G10	1.600	1"
GRP-G13	2.000	1 1/2"
GRP-G20	3.000	1 1/2"

Pressure regulator group supplied pre-assembled (no frame).  
 Packaging included.  
 For greater flow rates, quotations upon request.

## OPTIONS LIGHT OIL BURNERS

### LOW PRESSURE OIL HANDLING UNIT (RING) - LIGHT OIL - 2 PUMPS IN PARALLEL (ONE AS BACK-UP)

Type	Capacity kg/h	Power kW	Diameter	Dimensions a x b x h (mm)
GS-G2	350	2.300	1"	1.200 x 900 x 500
GS-G4	650	4.300	1"1/2	1.300 x 900 x 600
GS-G7	1.000	6.600	1"1/2	1.400 x 1.200 x 600
GS-G10	1.600	10.600	DN50	1.500 x 1.200 x 700
GS-G13	2.000	13.300	DN50	1.600 x 1.400 x 700
GS-G20	3.000	20.000	DN50	1.800 x 1.400 x 800

### LOW PRESSURE OIL HANDLING UNIT (RING) - LIGHT OIL - SINGLE PUMP

Type	Capacity kg/h	Power kW	Diameter	Dimensions a x b x h (mm)
GS-G2s	350	2.300	1"	1.200 x 600 x 500
GS-G4s	650	4.300	1"1/2	1.300 x 600 x 600
GS-G7s	1.000	6.600	1"1/2	1.400 x 800 x 600
GS-G10s	1.600	10.600	DN50	1.500 x 800 x 700

The output is referred to the burners which can be supplied by the low pressure ring.

The flow rate is referred to the light oil flow rate pumped into the ring.

Dimensions are indicative.

Dimensions do not include the electrical panel, the panel can be installed on the oil ring, or wall-hung (dimensions 400x250x600h mm).

For greater flow rates, quotations upon request.

In order to pick up the correct oil ring to your application, refer to the output and choose the larger ring size. Match the ring to the regulation group of the same size. To finish the job remember to choose the degassing tanks (the use of degassing tanks is mandatory when 2 or more burners are supplied by the same ring, only recommended in all other cases).



# OPTIONS HEAVY OIL BURNERS

## HEAVY OIL FILTERS



Model	Code
Filter 1" 0,3 micron big up to burner size 90-500	2090207
Filter 1½" 0,3 for PBY90-500	2090236
Filter 51000/05 F (flanged DN50) (1000-2000 burners series)*	2090237
Magnetic filter 1½" max 500 kg/h	2090245

\*With 300 W heater

## VACUUM GAUGE



Model	Code
Glycerine vacuum gauge -1 ÷ 0 bar (¼" connection)	2520008

## MANOMETER




Model	Code
Glycerine gauge 0 ÷ 6 bar (¼" connection)	2520035
Glycerine gauge 0 ÷ 10 bar (¼" connection)	2520036
Glycerine gauge 0 ÷ 16 bar (¼" connection)	2520033
Glycerine gauge 0 ÷ 25 bar (¼" connection)	2520034
Glycerine gauge 0 ÷ 40 bar (¼" connection)	2520019

## SUPPORT FOR PRESSURE GAUGE manometer / vacuum gauge



Model	Code
Isolating valve (¼" connection)	2520005

## DEGASSING BOTTLE



Model	Diameter	Code
Threaded	1"½	3040117
Flanged	DN40	3040121

## BELT HEATER CABLE FOR PIPES



Model	Type	Code
Power 64 Watt/meter	each meter	ON REQUEST

## MANUAL CUT OFF VALVE (BALL VALVE)



Model	Code
1"	2810024
1½"	2810025
2"	2810031
2½"	ON REQUEST

## OPTIONS HEAVY OIL BURNERS

### OIL PRE-HEATING TANK (STEAM/DIATERMIC OIL)

Type	Capacity kg/h	Tank volume liters	Electrical heaters kW	Max temperature °C	Max pressure bar
HTS5	500	500	12	80÷100	5
HTS10	1.000	1.500	18	80÷100	5
HTS20	2.000	2.000	24	80÷100	5
HTS30	3.000	3.000	24	80÷100	5
HTS40	4.000	4.000	24	80÷100	5

Vertical cylindrical tanks, provided with electrical resistance and spiral heat exchanger.

Upon order please specify if the spiral must be provided for diathermic oil or steam.

Electrical panel mounted aboard.

Packaging included.

The oil flow rate is indicative: it can vary according to the type of fuel and to the thermal step required.

### OIL PRE-HEATING TANK (ONLY ELECTRICAL RESISTANCES/HOT WATER)

Type	Capacity kg/h	Tank volume liters	Electrical heaters kW	Max temperature °C	Max pressure bar
HT2	200	200	8	80÷100	5
HT5	500	500	12	80÷100	5
HT10	1.000	1.500	18	80÷100	5
HT20	2.000	2.000	24	80÷100	5
HT30	3.000	3.000	24	80÷100	5
HT40	4.000	4.000	24	80÷100	5

Vertical cylindrical tanks, provided with electrical resistance and spiral heat exchanger (optional).

Upon order please specify electrical resistances only or hot water coil.

Electrical panel mounted aboard.

Packaging included.

The oil flow rate is indicative: it can vary according to the type of fuel and to the thermal step required.



## CRUDE AND HEAVY OIL PRESSURE REGULATOR GROUPS

Type	Capacity kg/h	Diameter
GRP-D2	500	DN50
GRP-D4	800	DN50
GRP-D7	1.300	DN50
GRP-D10	2.000	DN50
GRP-D13	2.500	DN50
GRP-D20	4.000	DN50

Pressure regulator group supplied pre-assembled (no frame).

Packaging included.

For greater flow rates, quotations upon request.



## LOW PRESSURE OIL HANDLING UNIT (RING) - HEAVY/RAW OIL - 2 PUMPS IN PARALLEL (ONE AS BACK-UP)

Type	Capacity kg/h	Power kW	Diameter	Dimensions a x b x h (mm)
GS-D2	500	2.700	DN50	1.300 x 900 x 800
GS-D4	800	4.500	DN50	1.500 x 900 x 800
GS-D7	1.300	6.900	DN50	1.600 x 1.200 x 800
GS-D10	2.000	10.800	DN50	1.600 x 1.200 x 800
GS-D13	2.500	13.900	DN50	1.800 x 1.500 x 800
GS-D20	4.000	20.000	DN50	1.800 x 1.500 x 800

## LOW PRESSURE OIL HANDLING UNIT (RING) - HEAVY/RAW OIL - SINGLE PUMP

Type	Capacity kg/h	Power kW	Diameter	Dimensions a x b x h (mm)
GS-D2s	500	2.700	DN50	1.300 x 600 x 800
GS-D4s	800	4.500	DN50	1.500 x 600 x 800
GS-D7s	1.300	6.900	DN50	1.600 x 800 x 800
GS-D10s	2.000	10.800	DN50	1.600 x 800 x 800

The output is referred to the burners which can be supplied by the low pressure ring.

The flow rate is referred to the heavy oil flow rate pumped into the ring.

Dimensions are indicative.

Dimensions do not include the electrical panel, the panel can be installed on the oil ring, or wall-hung (dimensions 400 x 250 x 600 h mm).

For greater flow rates, quotations upon request.

In order to pick up the correct oil ring to your application, refer to the output and choose the larger ring size. Match the ring to the regulation group of the same size. To finish the job remember to choose the degassing tanks (the use of degassing tanks is mandatory when 2 or more burners are supplied by the same ring, only recommended in all other cases).




## ACOUSTIC HOODS BOX ASSEMBLED ON WHEELED FRAME

All burners in this catalogue have lower than standard noise levels.

If a further reduction of the noisiness is required, the customer has at disposal a series of acoustic hoods box that can be integrated in the system.

The noise reduction range varies from 5 to 15 dB(A), depending on the design specification. For even greater abatements, please consult our technical department.



# Certificate





**CIB UNIGAS**

Let's light up tomorrow

**C.I.B. UNIGAS S.p.A.**

Via L. Galvani, 9 - 35011 CAMPODARSEGO (PD) - Italy

Tel. +39 049 9200944 - Fax +39 049 9200945

Fax Export +39 049 9202105

cibunigas@cibunigas.it

[www.cibunigas.it](http://www.cibunigas.it)



FAC-SIMILE

To print this catalogue we have used paper certified FSC®, Forest Stewardship Council®, supplied by producers respecting the environment, the forests, and who can exhibit specific product certifications.